

# CEMENT JOB REPORT



<b>CUSTOMER</b> BAYSWATER EXPLORATION &		<b>DATE</b> 16-JUL-14	<b>F.R. #</b> 10011082443		<b>SERV. SUPV.</b> Justin R Sturgiss									
<b>LEASE &amp; WELL NAME</b> GILBERT #17-22 - API 05123396840000		<b>LOCATION</b> 15-7N-67W		<b>COUNTY-PARISH-BLOCK</b> Weld Colorado										
<b>DISTRICT</b> Brighton		<b>DRILLING CONTRACTOR RIG #</b> Fort 5		<b>TYPE OF JOB</b> Intermediate										
<b>SIZE &amp; TYPE OF PLUGS</b>		<b>LIST-CSG-HARDWARE</b>		<b>MECHANICAL BARRIERS</b>		<b>MD</b> <b>TVD</b> <b>HANGER TYPES</b> <b>MD</b> <b>TVD</b>								
4-1/2" Top Cem Plug, Nitrile cvr, Phe		Float Collar, Dif Fill, 4-1/2 - 8rd												
		Guide Shoe, Cement Nose, 4-1/2 i												
		Cement Basket, Slip On, 4-1/2 in												
<b>MATERIALS FURNISHED BY BJ</b>				<b>PHYSICAL SLURRY PROPERTIES</b>										
<b>LAB REPORT NO.</b>				<b>SACKS OF CEMENT</b>	<b>SLURRY WGT PPG</b>	<b>SLURRY YLD FT<sup>3</sup></b>								
Mud Clean I					8.5	20								
Fresh Water					8.34	20								
Premium Lite HS Cement + Adds				677	12	2.42								
50:50 (POZ:Class G) + Adds				539	14.4	1.22								
Fresh Water					8.34	128.3								
<b>Available Mix Water</b> 900 Bbl.		<b>Available Displ. Fluid</b> 571 Bbl.		<b>TOTAL</b>		576.99 287.91								
<b>HOLE</b>			<b>TBG-CSG-D.P.</b>				<b>COLLAR DEPTHS</b>							
<b>SIZE</b>	<b>% EXCESS</b>	<b>DEPTH</b>	<b>ID</b>	<b>OD</b>	<b>WGT.</b>	<b>TYPE</b>	<b>MD</b>	<b>TVD</b>	<b>GRADE</b>	<b>SHOE</b>	<b>FLOAT</b>	<b>STAGE</b>		
7.875	0	8280	4	4.5	11.6	CSG	8258		N-80	8258	8255.7	0		
<b>LAST CASING</b>			<b>PKR-CMT RET-BR PL-LINER</b>			<b>PERF. DEPTH</b>		<b>TOP CONN</b>		<b>WELL FLUID</b>				
<b>ID</b>	<b>OD</b>	<b>WGT</b>	<b>TYPE</b>	<b>MD</b>	<b>TVD</b>	<b>BRAND &amp; TYPE</b>		<b>DEPTH</b>	<b>TOP</b>	<b>BTM</b>	<b>SIZE</b>	<b>THREAD</b>	<b>TYPE</b>	<b>WGT.</b>
8.1	8.63	24	CSG	815	815	NO PACKER		0	0	0	4.5	8RD	WATER BASED	9.8
<b>DISPL. VOLUME</b>		<b>DISPL. FLUID</b>		<b>CAL. PSI</b>	<b>CAL. MAX PSI</b>	<b>OP. MAX</b>	<b>MAX TBG PSI</b>		<b>MAX CSG PSI</b>		<b>MIX WATER</b>			
<b>VOLUME</b>	<b>UOM</b>	<b>TYPE</b>		<b>WGT.</b>	<b>BUMP PLUG</b>	<b>TO REV.</b>	<b>SQ. PSI</b>	<b>RATED</b>	<b>Operator</b>	<b>RATED</b>	<b>Operator</b>			
128.3	BBLS	Fresh Water		8.34	2461	0	0	0	0	7780	6224	TANK		
<b>Circulation Prior to Job</b>														
Circulated Well: Rig <input checked="" type="checkbox"/> BJ <input type="checkbox"/>				Circulation Time: 3.5				Circulation Rate: 6 BPM						
Mud Density In: 9.8 LBS/GAL				Mud Density Out: 9.8 LBS/GAL				PV & YP Mud In: 26		PV & YP Mud Out: 26				
Gas Present: NO <input checked="" type="checkbox"/> YES <input type="checkbox"/>				Units:				Solids Present at End of Circulation:		NO <input checked="" type="checkbox"/> YES <input type="checkbox"/>				
<b>Displacement And Mud Removal</b>														
Displaced By: Rig <input type="checkbox"/> BJ <input checked="" type="checkbox"/>				Amount Bled Back After Job: 1.25 BBLS										
Returns During Job: <input type="checkbox"/> NONE <input type="checkbox"/> PARTIAL <input checked="" type="checkbox"/> FULL				Method Used to Verify Returns: SIGHT										
Cement Returns at Surface: <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO				Were Returns Planned at Surface: <input type="checkbox"/> NO <input checked="" type="checkbox"/> YES										
Pipe Movement: <input type="checkbox"/> ROTATION <input type="checkbox"/> RECIPROICATION <input type="checkbox"/> NONE <input type="checkbox"/> UNABLE DUE TO STUCK PIPE														
Centralizers: <input type="checkbox"/> NO <input checked="" type="checkbox"/> YES				Quantity: 20				Type: <input type="checkbox"/> BOW <input type="checkbox"/> RIGID						
Job Pumped Through: <input type="checkbox"/> CHOKE MANIFOLD <input type="checkbox"/> SQUEEZE MANIFOLD <input checked="" type="checkbox"/> MANIFOLD <input type="checkbox"/> NO MANIFOLD														
<b>Plugs</b>														
Number of Attempts by BJ: Competition:				Wiper Balls Used: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES Quantity:										
Plug Catcher Used: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES				Parabow Used: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES										
Was There a Bottom: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES				Top of Plug: FT Bottom of Plug: FT										
<b>Squeezes (Update Original Treatment Report for Primary Job)</b>														
BLOCK SQUEEZE <input type="checkbox"/> SHOE SQUEEZE <input type="checkbox"/> TOP OF LINER SQUEEZE <input type="checkbox"/> PLANNED <input type="checkbox"/> UNPLANNED <input type="checkbox"/>														
Liner Packer: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES				Bond Log: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES				PSI Applied: Fluid Weight: LBS/GAL						
<b>Casing Test (Update Original Treatment Report for Primary Job)</b>														
Casing Test Pressure: PSI With LBS/GAL Mud						Time Held: Hours Minutes								
<b>EXPLANATION: TROUBLE SETTING TOOL, RUNNING CSG, ETC. PRIOR TO CEMENTING: NONE</b>														

# CEMENT JOB REPORT



## Shoe Test (Update Original Treatment Report for Primary Job)

Depth Drilled out of Shoe: FT	Target EMW: LBS/GAL	Actual EMW: LBS/GAL
Number of Times Tests Conducted:	Mud Weight When Test was Conducted: LBS/GAL	

Problems Before Job (I.E. Running Casing, Circulating Well, ETC)  
NONE

Problems During Job (I.E. Lost Returns, Equipment Failure, Bulk Delivery, Foaming, ETC)  
NONE

Problems After Job (I.E. Gas at Surface, Float Equipment Failed, ETC)  
NONE

PRESSURE/RATE DETAIL						EXPLANATION	
TIME HR:MIN.	PRESSURE - PSI		RATE BPM	Bbl. FLUID PUMPED	FLUID TYPE	SAFETY MEETING: BJ CREW <input checked="" type="checkbox"/> CO. REP. <input checked="" type="checkbox"/>	
	PIPE	ANNULUS				TEST LINES	4558 PSI
						CIRCULATING WELL - RIG <input checked="" type="checkbox"/> BJ <input type="checkbox"/>	
03:00	0	0	0	0	0	ARRIVED ON LOCATION	
04:30	0	0	0	0	0	RIG STARTED CIRCULATING	
06:30	0	0	0	0	0	SPOTTED TRUCKS	
08:15	0	0	0	0	0	SAFETY MEETING WITH COMPANY MAN	
08:46	4558	0	0	0	0	PRESSURE TEST	
08:47	392	0	3.3	20	MUD CLEA	START MUD CLEAN SPACER	
08:52	453	0	4.7	20	H2O	START DYED WATER SPACER	
09:00	580	0	5	291	CMT	START LEAD CEMENT @ 12.0 PPG	
10:02	216	0	4.5	116	CMT	START TAIL CEMENT @ 14.4 PPG	
10:30	0	0	0	0	0	SHUT DOWN, WASH LINES, DROP LATCH DOWN PLUG	
10:40	154	0	7.2	105	H2O	START DISPLACEMENT WITH FRESH WATER	
10:54	0	0	0	0	0	SHUT DOWN, GET MORE WATER	
11:00	1758	0	3	23.3	H2O	SLOWED RATE	
11:11	3105	0	0	0	0	BUMPED PLUG FROM 2330 PSI TO 3105 PSI	
11:15	0	0	0	0	0	CHECKED FLOAT, IT HELD, 1.25 BBLS BLED BACK, 70 BBLS OF CEMENT TO THE PIT, GOOD RETURNS THROUGHOUT.	

BUMPED PLUG	PSI TO BUMP PLUG	TEST FLOAT EQUIP.	BBL.CMT RETURNS/ REVERSED	TOTAL BBL. PUMPED	PSI LEFT ON CSG	SPOT TOP OUT CEMENT	Service Supervisor Signature:
<input checked="" type="checkbox"/> Y <input type="checkbox"/> N	3105	<input checked="" type="checkbox"/> Y <input type="checkbox"/> N	70	575	0	Y <input checked="" type="checkbox"/> N	