

WELL NAME: Kodak 10  
FIELD: Windsor - Wattenberg  
SHL: qtr-qtr SWNW Section 27 Township 6N Range 67W  
BHL: qtr-qtr SENW Section 29 Township 6N Range 67W  
COUNTY: Weld STATE: CO API: 05-123-37257

OPERATOR: Extraction Oil & Gas  
FORMATION: Niobrara

**SURFACE CASING**  
SIZE: 9 5/8"  
WEIGHT: 36#  
GRADE: J-55  
CONNECTION: LTC  
HOLE DEPTH: 810  
CSG DEPTH: 798  
INCL @ SHOE: 4°  
CEMENT: 335 sx 14.2#  
TOC: Surface  
HOLE SIZE: 13 1/2"

**INTERMEDIATE CASING**  
SIZE: 7"  
WEIGHT: 26#  
GRADE: P-110  
CONNECTION: LTC  
HOLE DEPTH: 7,504  
CSG DEPTH: 7,491  
INCL @ SHOE: 88°  
CEMENT: 480 SX 12.7 ppg  
275 SX 13.8 ppg  
TOC: Surface  
HOLE SIZE: 8 3/4"

**TIE-BACK STRING**  
SIZE:   
WEIGHT:   
GRADE:   
CONNECTION:   
CSG DEPTH:

GROUND LEVEL: 4,770'  
KELLY BUSHING: 24.0'  
SPUD DATE: 12/31/2015  
COMP DATE:

**PRODUCTION LINER**  
SIZE: 4 1/2"  
WEIGHT: 13.5#  
GRADE: P-110  
CONNECTION: TXP  
HOLE DEPTH: 16,905  
LINER TOP: 6,587  
INCL @ LT: 13°  
LINER SHOE: 16,901  
CEMENT: 866 sx econocem  
TOC: 6,587  
HOLE SIZE: 6 1/8"

**PRODUCTION TUBING**  
SIZE:   
WEIGHT:   
GRADE:   
DEPTH:   
INCL @ EOT:



9 5/8" csg @  
798' (4° incl)

KOP - 6,727'

EOT @ ' ( incl)

Liner Top @ 6587' (13° incl)

8 3/4" hole @ 7504'  
7" csg @ 7491' (88° incl)

Stage	Plug Depth	Perf Cluster 1	Perf Cluster 2	Perf Cluster 3	Perf Cluster 4	Perf Cluster 5	Total ft of Perfs	SPF	# of Holes	Stage Length	Fluid (bbl)	Sand (lbs)	Stage	Plug Depth	Perf Cluster	Perf Cluster 2	Perf Cluster	Perf Cluster	Perf Cluster 5	Total ft of Perfs	SPF	# of Holes	Stage Length	Fluid (bbl)	Sand (lbs)
1		11920-25	11905-10	11895-200	11880-85	11860-65	25	6	150	5,405															
2	11,500									250															
3	11,250									250															
4	11,000									105															
5	10,895									105															
6	10,790									105															
7	10,685									105															
8	10,580									105															
9	10,475									105															
10	10,370									105															
11	10,265									105															
12	10,160									105															
13	10,055									105															
14	9,950									105															
15	9,845									105															
16	9,740									105															
17	9,635									105															
18	9,530									105															
19	9,425									105															
20	9,320									105															

**Frac Stimulation**

Total Fluid: bbls  
Total Sand: lbs 40/70  
lbs 30/45 white  
lbs 20/40 resin  
- lbs  
0 lbs/ft

**Completion Notes**

\*  
\*  
\*  
\*

399' Avg Stage Length

Liner Shoe @ 16901'

MD 16,905  
TVD 6,970

62 61 60 59 58 57 56 55 54 53 52 51 50 49 48 47 46 45 44 43 42 41 40 39 38 37 36 35 34 33 32 31 30 29 28 27 26 25 24 23 22 21 20 19 18 17 16 15 14 13 12 11 10 9 8 7 6 5 4 3 2 1