PEAK WIRELINE SERVICES, INC

DUAL SPACED CEMENT BOND LOG

Company: AUSTRALIAN OIL COMPANY
Well: BEAGLE A3
Field: BEAGLE
County: BASS
State: GIPPSLAND
Country: AUSTRALIA
Permanent Datum: GROUND LEVEL
Elevation: 0 m
Log Measured From: KELLY BUSHING
Drilling Measured From: KELLY BUSHING
Elevation: 0 m
Elevation: 0 m
Date: 31-Dec-01
Run Number: ONE
Depth Driller: 1700 m
Depth Logger: 1700 m
Bottom Logged Interval: 1700 m
Top Logged Interval: 0 m
Casing Driller: 339.7 mm @ 0 m
Casing Logger: 339.7 mm @ 0 m
Bit Size: 311.1 mm
Type Fluid in Hole: SEAWATER
Density: 1.03 g/cm3
Viscosity: 0 s
Fluid Loss: 0 ml
Source of Sample: CIRCULATED
Rm @ Measured Temp: 0.1 ohmm @ 0 °C
Rmf @ Measured Temp: 0.1 ohmm @ 0 °C
Rmc @ Measured Temp: 0.1 ohmm @ 0 °C
Source of Rmf and Rmc: CALCULATED
Rm @ BHT: 0.1 ohmm @ 0 °C
Time Since Circulation: 0 hrs
Max Recorded Temp: 0 °C
Equipment Number: 0
Location: 0
Recorded By: 0
Witnessed By: 0

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except to the extent of gross or wilful negligence on our part, be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Database File: Ideal01.db
Dataset Pathname: pass1
Presentation Format: cbl
Dataset Creation: Tue Mar 31 08:25:43 2015 by Log Gist CasedHole 10071
Charted by: Depth in Feet scaled 1:240

CCL 0 150
GR (GAPI) 0 150
Cable Locator

Amplitude (mV) 100.000 0
Variable Density 1200 200
Travel Time (usec) 800 400

0
50
100
150
200
250
300
350
400
450
500
550
600
650
700
750
800
850
900
950
1000
1050
1100
1150
1200
1250
1300
1350
1400
1450
1500
1550
1600
1650
1700