

## WELLBORE DIAGRAM

Bayswater Expl. and Prod., LLC

Kaiser 6-10

SENW 10-6N-65W

2237 FNL 2150 FWL

Weld, CO

05-123-32162

5/29/2014

CR

Directions: WCRs 70 at 45, 1/2 N, 1/2 W, 0.2 S into

G.L.= 4773

K.B.= 4785

12

8-5/8" 24# set at 581', 12.25" hole

420 sks cmt w/ 3% CaCl and 0.125 lbs/sk floccel, 15.2 PPG, Yield 1.18

TTOC= 1696'

<< >>

**Niobrara "A" 6,842'-6,864', 4 spf, 5/29/14**

Frac "A" Bench, 5/29/2014, FR Water 157,305 gal. and 99,580 lbs 30/50 sand.

**CIFP @ 6,900', 5/29/14**

<< >>

**Niobrara "B" 6,970'-6,990', 4 spf, 5/22/14**

Frac "B" & "C" Bench, 5/29/2014, FR Water 338,448 gal. and 225,480 lbs 30/50 sand.

<< >>

**Niobrara "C" 7,012'- 7032', 5/22/14**

<< >>

**CIBP @ 7,090', w/ 2 sks cmnt, 5/22/14**

**Codell: 7125-7143, 4 spf, 3/17/11**

Initial frac 3/20/11: 1479 bbl FR slick water pad, 4891 bbls same w/ 171,153# 30/50 sand.

PDTD=7746

TD=7788

4-1/2" 11.6 # N80 CSG set @ 7763' (7-7/8" Hole)

Cmnt'd Lead: 540 sks Premium Lite, 12.5 ppg, 2.0 yield

Tail: 210 sks 50-50 Poz, 13.5 ppg, 1.71 yield