

Whiting Petroleum Corp.

Weld County, CO

Sec 7-T10N-R57W

Horsetail #07E-0636D

Hz

Plan: Plan #1

Standard Planning Report

29 January, 2015





Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07E-0636D
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07E-0636D	Survey Calculation Method:	Minimum Curvature
Wellbore:	Hz		
Design:	Plan #1		

Project	Weld County, CO		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Colorado Northern Zone		

Site		Sec 7-T10N-R57W			
Site Position:		Northing:	1,558,450.14 usft	Latitude:	40° 51' 14.300 N
From:	Lat/Long	Easting:	3,469,810.15 usft	Longitude:	103° 48' 5.960 W
Position Uncertainty:	0.00 usft	Slot Radius:	13.200 in	Grid Convergence:	1.10 °

Well	Horsetail #07E-0636D					
Well Position	+N/-S	-54.63 usft	Northing:	1,558,399.32 usft	Latitude:	40° 51' 13.760 N
	+E/-W	198.35 usft	Easting:	3,470,009.51 usft	Longitude:	103° 48' 3.379 W
Position Uncertainty		0.00 usft	Wellhead Elevation:		Ground Level:	4,925.70 usft

Wellbore	Hz				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2010	1/5/2015	7.89	67.44	53,087

Design	Plan #1			
Audit Notes:				
Version:	Phase:	PROTOTYPE	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.00	0.00	0.00	0.50

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	0.00	
650.00	5.00	170.00	649.68	-10.74	1.89	2.00	2.00	0.00	170.00	
5,157.00	5.00	170.00	5,139.53	-397.58	70.10	0.00	0.00	0.00	0.00	
5,407.00	0.00	0.00	5,389.21	-408.31	72.00	2.00	-2.00	0.00	180.00	
5,545.92	0.00	0.00	5,528.14	-408.31	72.00	0.00	0.00	0.00	0.00	
6,364.10	90.00	359.93	6,049.00	112.55	71.38	11.00	11.00	0.00	359.93	PBHL 0636D
13,474.72	90.00	359.93	6,049.00	7,223.17	63.00	0.00	0.00	0.00	0.00	PBHL 0636D



Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07E-0636D
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07E-0636D	Survey Calculation Method:	Minimum Curvature
Wellbore:	Hz		
Design:	Plan #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	0.00
Build 2°/100'									
500.00	2.00	170.00	499.98	-1.72	0.30	-1.72	2.00	2.00	0.00
600.00	4.00	170.00	599.84	-6.87	1.21	-6.86	2.00	2.00	0.00
650.00	5.00	170.00	649.68	-10.74	1.89	-10.72	2.00	2.00	0.00
Hold 5° Inc									
700.00	5.00	170.00	699.49	-15.03	2.65	-15.00	0.00	0.00	0.00
800.00	5.00	170.00	799.11	-23.61	4.16	-23.57	0.00	0.00	0.00
900.00	5.00	170.00	898.73	-32.19	5.68	-32.14	0.00	0.00	0.00
1,000.00	5.00	170.00	998.35	-40.78	7.19	-40.71	0.00	0.00	0.00
1,100.00	5.00	170.00	1,097.97	-49.36	8.70	-49.28	0.00	0.00	0.00
1,200.00	5.00	170.00	1,197.59	-57.94	10.22	-57.85	0.00	0.00	0.00
1,300.00	5.00	170.00	1,297.21	-66.53	11.73	-66.42	0.00	0.00	0.00
1,400.00	5.00	170.00	1,396.83	-75.11	13.24	-74.99	0.00	0.00	0.00
1,500.00	5.00	170.00	1,496.45	-83.69	14.76	-83.56	0.00	0.00	0.00
1,553.76	5.00	170.00	1,550.00	-88.31	15.57	-88.17	0.00	0.00	0.00
Upper Pierre									
1,600.00	5.00	170.00	1,596.07	-92.28	16.27	-92.13	0.00	0.00	0.00
1,700.00	5.00	170.00	1,695.69	-100.86	17.78	-100.70	0.00	0.00	0.00
1,800.00	5.00	170.00	1,795.31	-109.44	19.30	-109.27	0.00	0.00	0.00
1,900.00	5.00	170.00	1,894.93	-118.03	20.81	-117.84	0.00	0.00	0.00
2,000.00	5.00	170.00	1,994.55	-126.61	22.32	-126.41	0.00	0.00	0.00
2,100.00	5.00	170.00	2,094.17	-135.19	23.84	-134.98	0.00	0.00	0.00
2,200.00	5.00	170.00	2,193.78	-143.77	25.35	-143.55	0.00	0.00	0.00
2,300.00	5.00	170.00	2,293.40	-152.36	26.86	-152.12	0.00	0.00	0.00
2,400.00	5.00	170.00	2,393.02	-160.94	28.38	-160.69	0.00	0.00	0.00
2,500.00	5.00	170.00	2,492.64	-169.52	29.89	-169.26	0.00	0.00	0.00
2,600.00	5.00	170.00	2,592.26	-178.11	31.41	-177.83	0.00	0.00	0.00
2,700.00	5.00	170.00	2,691.88	-186.69	32.92	-186.40	0.00	0.00	0.00
2,800.00	5.00	170.00	2,791.50	-195.27	34.43	-194.97	0.00	0.00	0.00
2,900.00	5.00	170.00	2,891.12	-203.86	35.95	-203.54	0.00	0.00	0.00
3,000.00	5.00	170.00	2,990.74	-212.44	37.46	-212.11	0.00	0.00	0.00
3,100.00	5.00	170.00	3,090.36	-221.02	38.97	-220.68	0.00	0.00	0.00
3,200.00	5.00	170.00	3,189.98	-229.61	40.49	-229.24	0.00	0.00	0.00
3,300.00	5.00	170.00	3,289.60	-238.19	42.00	-237.81	0.00	0.00	0.00
3,400.00	5.00	170.00	3,389.22	-246.77	43.51	-246.38	0.00	0.00	0.00
3,500.00	5.00	170.00	3,488.84	-255.36	45.03	-254.95	0.00	0.00	0.00
3,511.21	5.00	170.00	3,500.00	-256.32	45.20	-255.91	0.00	0.00	0.00
Hygiene									
3,600.00	5.00	170.00	3,588.46	-263.94	46.54	-263.52	0.00	0.00	0.00
3,661.78	5.00	170.00	3,650.00	-269.24	47.47	-268.82	0.00	0.00	0.00
Lower Pierre									
3,700.00	5.00	170.00	3,688.08	-272.52	48.05	-272.09	0.00	0.00	0.00
3,800.00	5.00	170.00	3,787.70	-281.11	49.57	-280.66	0.00	0.00	0.00
3,900.00	5.00	170.00	3,887.32	-289.69	51.08	-289.23	0.00	0.00	0.00
4,000.00	5.00	170.00	3,986.94	-298.27	52.59	-297.80	0.00	0.00	0.00
4,100.00	5.00	170.00	4,086.55	-306.85	54.11	-306.37	0.00	0.00	0.00
4,200.00	5.00	170.00	4,186.17	-315.44	55.62	-314.94	0.00	0.00	0.00
4,300.00	5.00	170.00	4,285.79	-324.02	57.13	-323.51	0.00	0.00	0.00
4,400.00	5.00	170.00	4,385.41	-332.60	58.65	-332.08	0.00	0.00	0.00



Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07E-0636D
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07E-0636D	Survey Calculation Method:	Minimum Curvature
Wellbore:	Hz		
Design:	Plan #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
4,500.00	5.00	170.00	4,485.03	-341.19	60.16	-340.65	0.00	0.00	0.00
4,600.00	5.00	170.00	4,584.65	-349.77	61.67	-349.22	0.00	0.00	0.00
4,700.00	5.00	170.00	4,684.27	-358.35	63.19	-357.79	0.00	0.00	0.00
4,800.00	5.00	170.00	4,783.89	-366.94	64.70	-366.36	0.00	0.00	0.00
4,900.00	5.00	170.00	4,883.51	-375.52	66.21	-374.93	0.00	0.00	0.00
5,000.00	5.00	170.00	4,983.13	-384.10	67.73	-383.50	0.00	0.00	0.00
5,100.00	5.00	170.00	5,082.75	-392.69	69.24	-392.07	0.00	0.00	0.00
5,157.00	5.00	170.00	5,139.53	-397.58	70.10	-396.95	0.00	0.00	0.00
Drop 2°/100'									
5,200.00	4.14	170.00	5,182.40	-400.95	70.70	-400.32	2.00	-2.00	0.00
5,300.00	2.14	170.00	5,282.24	-406.35	71.65	-405.71	2.00	-2.00	0.00
5,407.00	0.00	0.00	5,389.21	-408.31	72.00	-407.67	2.00	-2.00	0.00
Hold Vertical									
5,500.00	0.00	0.00	5,482.22	-408.31	72.00	-407.67	0.00	0.00	0.00
5,532.78	0.00	0.00	5,515.00	-408.31	72.00	-407.67	0.00	0.00	0.00
P200 Marker									
5,545.92	0.00	0.00	5,528.14	-408.31	72.00	-407.67	0.00	0.00	0.00
KOP, Build 11°/100'									
5,547.79	0.21	359.93	5,530.00	-408.31	72.00	-407.67	11.00	11.00	0.00
P300 Marker									
5,550.00	0.45	359.93	5,532.22	-408.30	72.00	-407.66	11.00	11.00	0.00
5,567.79	2.41	359.93	5,550.00	-407.86	72.00	-407.21	11.00	11.00	0.00
P350 Marker									
5,600.00	5.95	359.93	5,582.12	-405.51	71.99	-404.87	11.00	11.00	0.00
5,650.00	11.45	359.93	5,631.52	-397.95	71.98	-397.31	11.00	11.00	0.00
5,700.00	16.95	359.93	5,679.98	-385.69	71.97	-385.05	11.00	11.00	0.00
5,723.19	19.50	359.93	5,702.00	-378.44	71.96	-377.80	11.00	11.00	0.00
Sharon Springs									
5,728.50	20.08	359.93	5,707.00	-376.64	71.96	-376.00	11.00	11.00	0.00
Niobrara									
5,749.96	22.44	359.93	5,727.00	-368.86	71.95	-368.22	11.00	11.00	0.00
Top A Chalk									
5,750.00	22.45	359.93	5,727.03	-368.84	71.95	-368.20	11.00	11.00	0.00
5,790.70	26.93	359.93	5,764.00	-351.85	71.93	-351.21	11.00	11.00	0.00
Top A Marl									
5,800.00	27.95	359.93	5,772.26	-347.56	71.93	-346.92	11.00	11.00	0.00
5,812.24	29.30	359.93	5,783.00	-341.70	71.92	-341.06	11.00	11.00	0.00
A Marl									
5,822.62	30.44	359.93	5,792.00	-336.53	71.91	-335.89	11.00	11.00	0.00
Top Upper B									
5,850.00	33.45	359.93	5,815.23	-322.05	71.90	-321.41	11.00	11.00	0.00
5,855.73	34.08	359.93	5,820.00	-318.86	71.89	-318.22	11.00	11.00	0.00
Base Upper B									
5,876.54	36.37	359.93	5,837.00	-306.86	71.88	-306.22	11.00	11.00	0.00
Top Lower B									
5,900.00	38.95	359.93	5,855.57	-292.53	71.86	-291.89	11.00	11.00	0.00
5,901.84	39.15	359.93	5,857.00	-291.37	71.86	-290.73	11.00	11.00	0.00
Base Lower B									
5,910.94	40.15	359.93	5,864.00	-285.57	71.85	-284.93	11.00	11.00	0.00
Top B Marl									
5,950.00	44.45	359.93	5,892.89	-259.28	71.82	-258.64	11.00	11.00	0.00
5,980.47	47.80	359.93	5,914.00	-237.32	71.80	-236.69	11.00	11.00	0.00



Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07E-0636D
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07E-0636D	Survey Calculation Method:	Minimum Curvature
Wellbore:	Hz		
Design:	Plan #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)	
Top C Chalk										
5,992.53	49.13	359.93	5,922.00	-228.29	71.78	-227.66	11.00	11.00	0.00	
Middle C Chalk										
6,000.00	49.95	359.93	5,926.85	-222.61	71.78	-221.98	11.00	11.00	0.00	
6,014.47	51.54	359.93	5,936.00	-211.41	71.76	-210.77	11.00	11.00	0.00	
Middle C Marl										
6,046.26	55.04	359.93	5,955.00	-185.93	71.73	-185.29	11.00	11.00	0.00	
Lower C Chalk										
6,050.00	55.45	359.93	5,957.13	-182.85	71.73	-182.22	11.00	11.00	0.00	
6,079.18	58.66	359.93	5,973.00	-158.37	71.70	-157.74	11.00	11.00	0.00	
Lower C Marl										
6,100.00	60.95	359.93	5,983.47	-140.37	71.68	-139.74	11.00	11.00	0.00	
6,145.98	66.01	359.93	6,004.00	-99.24	71.63	-98.61	11.00	11.00	0.00	
Lower C Marker										
6,150.00	66.45	359.93	6,005.62	-95.57	71.63	-94.94	11.00	11.00	0.00	
6,158.63	67.40	359.93	6,009.00	-87.63	71.62	-87.00	11.00	11.00	0.00	
Top Ft. Hays										
6,200.00	71.95	359.93	6,023.37	-48.84	71.57	-48.22	11.00	11.00	0.00	
6,219.27	74.07	359.93	6,029.00	-30.41	71.55	-29.79	11.00	11.00	0.00	
Ft. Hays Marker										
6,250.00	77.45	359.93	6,036.56	-0.64	71.52	-0.01	11.00	11.00	0.00	
6,300.00	82.95	359.93	6,045.07	48.62	71.46	49.24	11.00	11.00	0.00	
6,350.00	88.45	359.93	6,048.81	98.46	71.40	99.08	11.00	11.00	0.00	
6,361.86	89.75	359.93	6,049.00	110.32	71.39	110.93	11.00	11.00	0.00	
Top Codell										
6,364.10	90.00	359.93	6,049.00	112.55	71.38	113.17	11.00	11.00	0.00	
LP @ 90° Inc, Hold - 7"										
6,400.00	90.00	359.93	6,049.00	148.45	71.34	149.07	0.00	0.00	0.00	
6,500.00	90.00	359.93	6,049.00	248.45	71.22	249.07	0.00	0.00	0.00	
6,600.00	90.00	359.93	6,049.00	348.45	71.10	349.06	0.00	0.00	0.00	
6,700.00	90.00	359.93	6,049.00	448.45	70.99	449.06	0.00	0.00	0.00	
6,800.00	90.00	359.93	6,049.00	548.45	70.87	549.05	0.00	0.00	0.00	
6,900.00	90.00	359.93	6,049.00	648.45	70.75	649.05	0.00	0.00	0.00	
7,000.00	90.00	359.93	6,049.00	748.45	70.63	749.04	0.00	0.00	0.00	
7,100.00	90.00	359.93	6,049.00	848.45	70.52	849.04	0.00	0.00	0.00	
7,200.00	90.00	359.93	6,049.00	948.45	70.40	949.03	0.00	0.00	0.00	
7,300.00	90.00	359.93	6,049.00	1,048.45	70.28	1,049.03	0.00	0.00	0.00	
7,400.00	90.00	359.93	6,049.00	1,148.45	70.16	1,149.02	0.00	0.00	0.00	
7,500.00	90.00	359.93	6,049.00	1,248.45	70.04	1,249.02	0.00	0.00	0.00	
7,600.00	90.00	359.93	6,049.00	1,348.45	69.93	1,349.01	0.00	0.00	0.00	
7,700.00	90.00	359.93	6,049.00	1,448.45	69.81	1,449.01	0.00	0.00	0.00	
7,800.00	90.00	359.93	6,049.00	1,548.45	69.69	1,549.00	0.00	0.00	0.00	
7,900.00	90.00	359.93	6,049.00	1,648.45	69.57	1,649.00	0.00	0.00	0.00	
8,000.00	90.00	359.93	6,049.00	1,748.45	69.45	1,748.99	0.00	0.00	0.00	
8,100.00	90.00	359.93	6,049.00	1,848.45	69.34	1,848.99	0.00	0.00	0.00	
8,200.00	90.00	359.93	6,049.00	1,948.45	69.22	1,948.98	0.00	0.00	0.00	
8,300.00	90.00	359.93	6,049.00	2,048.45	69.10	2,048.98	0.00	0.00	0.00	
8,400.00	90.00	359.93	6,049.00	2,148.45	68.98	2,148.97	0.00	0.00	0.00	
8,500.00	90.00	359.93	6,049.00	2,248.45	68.86	2,248.97	0.00	0.00	0.00	
8,600.00	90.00	359.93	6,049.00	2,348.45	68.75	2,348.96	0.00	0.00	0.00	
8,700.00	90.00	359.93	6,049.00	2,448.45	68.63	2,448.96	0.00	0.00	0.00	
8,800.00	90.00	359.93	6,049.00	2,548.45	68.51	2,548.95	0.00	0.00	0.00	



Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07E-0636D
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07E-0636D	Survey Calculation Method:	Minimum Curvature
Wellbore:	Hz		
Design:	Plan #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100ft)	Build Rate (°/100ft)	Turn Rate (°/100ft)
8,900.00	90.00	359.93	6,049.00	2,648.45	68.39	2,648.95	0.00	0.00	0.00
9,000.00	90.00	359.93	6,049.00	2,748.45	68.28	2,748.94	0.00	0.00	0.00
9,100.00	90.00	359.93	6,049.00	2,848.45	68.16	2,848.94	0.00	0.00	0.00
9,200.00	90.00	359.93	6,049.00	2,948.45	68.04	2,948.93	0.00	0.00	0.00
9,300.00	90.00	359.93	6,049.00	3,048.45	67.92	3,048.93	0.00	0.00	0.00
9,400.00	90.00	359.93	6,049.00	3,148.45	67.80	3,148.92	0.00	0.00	0.00
9,407.83	90.00	359.93	6,049.00	3,156.28	67.79	3,156.75	0.00	0.00	0.00
Beffie #1									
9,500.00	90.00	359.93	6,049.00	3,248.45	67.69	3,248.92	0.00	0.00	0.00
9,600.00	90.00	359.93	6,049.00	3,348.45	67.57	3,348.91	0.00	0.00	0.00
9,700.00	90.00	359.93	6,049.00	3,448.45	67.45	3,448.91	0.00	0.00	0.00
9,800.00	90.00	359.93	6,049.00	3,548.45	67.33	3,548.90	0.00	0.00	0.00
9,900.00	90.00	359.93	6,049.00	3,648.45	67.21	3,648.90	0.00	0.00	0.00
10,000.00	90.00	359.93	6,049.00	3,748.45	67.10	3,748.89	0.00	0.00	0.00
10,100.00	90.00	359.93	6,049.00	3,848.45	66.98	3,848.89	0.00	0.00	0.00
10,200.00	90.00	359.93	6,049.00	3,948.45	66.86	3,948.88	0.00	0.00	0.00
10,300.00	90.00	359.93	6,049.00	4,048.45	66.74	4,048.88	0.00	0.00	0.00
10,400.00	90.00	359.93	6,049.00	4,148.45	66.62	4,148.87	0.00	0.00	0.00
10,500.00	90.00	359.93	6,049.00	4,248.45	66.51	4,248.87	0.00	0.00	0.00
10,600.00	90.00	359.93	6,049.00	4,348.45	66.39	4,348.87	0.00	0.00	0.00
10,700.00	90.00	359.93	6,049.00	4,448.45	66.27	4,448.86	0.00	0.00	0.00
10,800.00	90.00	359.93	6,049.00	4,548.45	66.15	4,548.86	0.00	0.00	0.00
10,900.00	90.00	359.93	6,049.00	4,648.45	66.04	4,648.85	0.00	0.00	0.00
11,000.00	90.00	359.93	6,049.00	4,748.45	65.92	4,748.85	0.00	0.00	0.00
11,100.00	90.00	359.93	6,049.00	4,848.45	65.80	4,848.84	0.00	0.00	0.00
11,200.00	90.00	359.93	6,049.00	4,948.45	65.68	4,948.84	0.00	0.00	0.00
11,300.00	90.00	359.93	6,049.00	5,048.45	65.56	5,048.83	0.00	0.00	0.00
11,400.00	90.00	359.93	6,049.00	5,148.45	65.45	5,148.83	0.00	0.00	0.00
11,500.00	90.00	359.93	6,049.00	5,248.45	65.33	5,248.82	0.00	0.00	0.00
11,600.00	90.00	359.93	6,049.00	5,348.45	65.21	5,348.82	0.00	0.00	0.00
11,700.00	90.00	359.93	6,049.00	5,448.45	65.09	5,448.81	0.00	0.00	0.00
11,800.00	90.00	359.93	6,049.00	5,548.45	64.97	5,548.81	0.00	0.00	0.00
11,900.00	90.00	359.93	6,049.00	5,648.45	64.86	5,648.80	0.00	0.00	0.00
12,000.00	90.00	359.93	6,049.00	5,748.45	64.74	5,748.80	0.00	0.00	0.00
12,100.00	90.00	359.93	6,049.00	5,848.45	64.62	5,848.79	0.00	0.00	0.00
12,200.00	90.00	359.93	6,049.00	5,948.45	64.50	5,948.79	0.00	0.00	0.00
12,300.00	90.00	359.93	6,049.00	6,048.45	64.38	6,048.78	0.00	0.00	0.00
12,400.00	90.00	359.93	6,049.00	6,148.45	64.27	6,148.78	0.00	0.00	0.00
12,500.00	90.00	359.93	6,049.00	6,248.45	64.15	6,248.77	0.00	0.00	0.00
12,600.00	90.00	359.93	6,049.00	6,348.45	64.03	6,348.77	0.00	0.00	0.00
12,700.00	90.00	359.93	6,049.00	6,448.45	63.91	6,448.76	0.00	0.00	0.00
12,800.00	90.00	359.93	6,049.00	6,548.45	63.80	6,548.76	0.00	0.00	0.00
12,900.00	90.00	359.93	6,049.00	6,648.45	63.68	6,648.75	0.00	0.00	0.00
13,000.00	90.00	359.93	6,049.00	6,748.45	63.56	6,748.75	0.00	0.00	0.00
13,100.00	90.00	359.93	6,049.00	6,848.45	63.44	6,848.74	0.00	0.00	0.00
13,200.00	90.00	359.93	6,049.00	6,948.45	63.32	6,948.74	0.00	0.00	0.00
13,300.00	90.00	359.93	6,049.00	7,048.45	63.21	7,048.73	0.00	0.00	0.00
13,400.00	90.00	359.93	6,049.00	7,148.45	63.09	7,148.73	0.00	0.00	0.00
13,474.71	90.00	359.93	6,049.00	7,223.16	63.00	7,223.43	0.00	0.00	0.00
TD at 13474.71' MD									
13,474.72	90.00	359.93	6,049.00	7,223.17	63.00	7,223.44	0.00	0.00	0.00
PBHL 0636D									



Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07E-0636D
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07E-0636D	Survey Calculation Method:	Minimum Curvature
Wellbore:	Hz		
Design:	Plan #1		

Design Targets									
Target Name	Dip Angle	Dip Dir.	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
- hit/miss target	(°)	(°)	(usft)	(usft)	(usft)	(usft)	(usft)		
- Shape									
PBHL 0636D	0.00	0.00	6,049.00	7,223.17	63.00	1,565,622.37	3,469,934.10	40° 52' 25.130 N	103° 48' 2.559 W
- plan hits target center									
- Point									
Beffie #1	0.00	0.00	6,735.70	3,155.89	-264.56	1,561,549.56	3,469,684.53	40° 51' 44.942 N	103° 48' 6.822 W
- plan misses target center by 762.89usft at 9407.83usft MD (6049.00 TVD, 3156.28 N, 67.79 E)									
- Circle (radius 1,550.00)									

Casing Points					
Measured Depth	Vertical Depth	Name		Casing Diameter	Hole Diameter
(usft)	(usft)			(in)	(in)
6,364.10	6,049.00	7"		7.000	7.500

Formations						
Measured Depth	Vertical Depth	Name		Lithology	Dip	Dip Direction
(usft)	(usft)				(°)	(°)
1,553.76	1,550.00	Upper Pierre				
3,511.21	3,500.00	Hygiene				
3,661.78	3,650.00	Lower Pierre				
5,532.78	5,515.00	P200 Marker				
5,547.79	5,530.00	P300 Marker				
5,567.79	5,550.00	P350 Marker				
5,723.19	5,702.00	Sharon Springs				
5,728.50	5,707.00	Niobrara				
5,749.96	5,727.00	Top A Chalk				
5,790.70	5,764.00	Top A Marl				
5,812.24	5,783.00	A Marl				
5,822.62	5,792.00	Top Upper B				
5,855.73	5,820.00	Base Upper B				
5,876.54	5,837.00	Top Lower B				
5,901.84	5,857.00	Base Lower B				
5,910.94	5,864.00	Top B Marl				
5,980.47	5,914.00	Top C Chalk				
5,992.53	5,922.00	Middle C Chalk				
6,014.47	5,936.00	Middle C Marl				
6,046.26	5,955.00	Lower C Chalk				
6,079.18	5,973.00	Lower C Marl				
6,145.98	6,004.00	Lower C Marker				
6,158.63	6,009.00	Top Ft. Hays				
6,219.27	6,029.00	Ft. Hays Marker				
6,361.86	6,049.00	Top Codell				



Database:	LandmarkEDM	Local Co-ordinate Reference:	Well Horsetail #07E-0636D
Company:	Whiting Petroleum Corp.	TVD Reference:	KBE @ 4942.70usft (Original Well Elev)
Project:	Weld County, CO	MD Reference:	KBE @ 4942.70usft (Original Well Elev)
Site:	Sec 7-T10N-R57W	North Reference:	True
Well:	Horsetail #07E-0636D	Survey Calculation Method:	Minimum Curvature
Wellbore:	Hz		
Design:	Plan #1		

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
400.00	400.00	0.00	0.00	Build 2°/100'
650.00	649.68	-10.74	1.89	Hold 5° Inc
5,157.00	5,139.53	-397.58	70.10	Drop 2°/100'
5,407.00	5,389.21	-408.31	72.00	Hold Vertical
5,545.92	5,528.14	-408.31	72.00	KOP, Build 11°/100'
6,364.10	6,049.00	112.55	72.00	LP @ 90° Inc, Hold
13,474.71	6,049.00	7,223.17	72.00	TD at 13474.71' MD