

FORM  
5A

Rev  
06/12

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

400847012

Date Received:

06/15/2015

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: <u>5</u>	4. Contact Name: <u>collin androus</u>
2. Name of Operator: <u>COLORADO OIL &amp; GAS CONSERVATION</u>	Phone: <u>(303) 894-2100</u>
3. Address: <u>1120 LINCOLN ST SUITE 801</u>	Fax: _____
City: <u>DENVER</u> State: <u>CO</u> Zip: <u>80203</u>	Email: <u>collin.androus@state.co.us</u>

5. API Number <u>05-067-08801-00</u>	6. County: <u>LA PLATA</u>
7. Well Name: <u>MONITOR WELL</u>	Well Number: <u>35-7-8-1</u>
8. Location: QtrQtr: <u>NESE</u> Section: <u>8</u> Township: <u>35N</u> Range: <u>7W</u> Meridian: <u>N</u>	
9. Field Name: <u>IGNACIO BLANCO</u> Field Code: <u>38300</u>	

### Completed Interval

FORMATION: FRUITLAND COAL Status: SHUT IN Treatment Type: \_\_\_\_\_  
Treatment Date: \_\_\_\_\_ End Date: \_\_\_\_\_ Date of First Production this formation: \_\_\_\_\_  
Perforations Top: 403 Bottom: 416 No. Holes: 23 Hole size: 0.4  
Provide a brief summary of the formation treatment: \_\_\_\_\_ Open Hole: ☐

none.  
Upper transducer set at 5 feet below ground surface. Type and Rating is the LT 500 - 30 psia.  
Lower transducer set at 374 feet below ground surface. Type and Rating is the LT 500 - 300 psia  
Perforations 403 to 416, 2 holes per foot. 0.4 in

This formation is commingled with another formation: ☒ Yes ☐ No  
Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_  
Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_  
Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_  
Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_  
Recycled water used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_  
Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_  
Total proppant used (lbs): \_\_\_\_\_ Rule 805 green completion techniques were utilized: ☐  
Reason why green completion not utilized: \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

### Test Information:

Date: \_\_\_\_\_ Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_  
Calculated 24 hour rate: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_  
Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_  
Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_  
Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_

Reason for Non-Production: Observation Well

Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_

\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

Comment:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Collin Androus  
Title: Environmental Scientist Date: 6/15/2015 Email: collin.androus@state.co.us

### Attachment Check List

**Att Doc Num** **Name**

400847012 FORM 5A SUBMITTED

Total Attach: 1 Files

### General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Environmental	This is an observation well. Upper transducer set at 5 feet below ground surface. Type and Rating is the LT 500 - 30 psia. Lower transducer set at 374 feet below ground surface. Type and Rating is the LT 500 - 300 psia Perforations 403 to 416, 2 holes per foot. 0.4 in	6/15/2015 11:39:46 AM

Total: 1 comment(s)