

# CEMENT JOB REPORT



<b>CUSTOMER</b> BAYSWATER EXPLORATION &				<b>DATE</b> 06-JAN-15		<b>F.R. #</b> 10011129929		<b>SERV. SUPV.</b> JASON L SJOBERG						
<b>LEASE &amp; WELL NAME</b> MATRIX #L-29HC - API 05123407040000				<b>LOCATION</b> 29-6N-65W				<b>COUNTY-PARISH-BLOCK</b> Weld Colorado						
<b>DISTRICT</b> Brighton				<b>DRILLING CONTRACTOR RIG #</b>				<b>TYPE OF JOB</b> Surface						
<b>SIZE &amp; TYPE OF PLUGS</b>		<b>LIST-CSG-HARDWARE</b>		<b>MECHANICAL BARRIERS</b>		<b>MD</b>	<b>TVD</b>	<b>HANGER TYPES</b>		<b>MD</b>	<b>TVD</b>			
9-5/8" Top Cem Plug, Nitrile cvr, Phe		Float Shoe 9-5/8 - 8rd												
		Centralizer, with Pins, 9-5/8 in												
		Cement Basket, Slip On, 9-5/8 in												
		Alum Baffle Plate, Slip On, 9-5/8												
<b>MATERIALS FURNISHED BY BJ</b>				<b>LAB REPORT NO.</b>		<b>PHYSICAL SLURRY PROPERTIES</b>								
						<b>SACKS OF CEMENT</b>	<b>SLURRY WGT PPG</b>	<b>SLURRY YLD FT<sup>3</sup></b>	<b>WATER GPS</b>	<b>PUMP TIME HR:MIN</b>	<b>Bbl SLURRY</b>	<b>Bbl MIX WATER</b>		
Fresh Water							8.34				10			
Type III Cement + Adds						250	14.5	1.40	6.80		62.33	40.41		
Fresh Water							8.34				55			
Dye Water							8.34				10			
<b>Available Mix Water</b> 300 <b>Bbl.</b>				<b>Available Displ. Fluid</b> 300 <b>Bbl.</b>				<b>TOTAL</b>		137.33		40.41		
<b>HOLE</b>			<b>TBG-CSG-D.P.</b>						<b>COLLAR DEPTHS</b>					
<b>SIZE</b>	<b>% EXCESS</b>	<b>DEPTH</b>	<b>ID</b>	<b>OD</b>	<b>WGT.</b>	<b>TYPE</b>	<b>MD</b>	<b>TVD</b>	<b>GRADE</b>	<b>SHOE</b>	<b>FLOAT</b>	<b>STAGE</b>		
12.25	30	760	8.921	9.625	36	CSG	748	748	J-55	748	704	1		
<b>LAST CASING</b>			<b>PKR-CMT RET-BR PL-LINER</b>			<b>PERF. DEPTH</b>			<b>TOP CONN</b>		<b>WELL FLUID</b>			
<b>ID</b>	<b>OD</b>	<b>WGT</b>	<b>TYPE</b>	<b>MD</b>	<b>TVD</b>	<b>BRAND &amp; TYPE</b>		<b>DEPTH</b>	<b>TOP</b>	<b>BTM</b>	<b>SIZE</b>	<b>THREAD</b>	<b>TYPE</b>	<b>WGT.</b>
						No Packer		0			9.625	8 RND	WATER BASED	8.34
<b>DISPL. VOLUME</b>		<b>DISPL. FLUID</b>		<b>CAL. PSI</b>	<b>CAL. MAX PSI</b>	<b>OP. MAX</b>	<b>MAX TBG PSI</b>		<b>MAX CSG PSI</b>		<b>MIX WATER</b>			
<b>VOLUME</b>	<b>UOM</b>	<b>TYPE</b>	<b>WGT.</b>	<b>BUMP PLUG</b>	<b>TO REV.</b>	<b>SQ. PSI</b>	<b>RATED</b>	<b>Operator</b>	<b>RATED</b>	<b>Operator</b>				
55	BBLS	Fresh Water	8.34	239	0	0	0	0	2816	2000	Rig			
<b>Circulation Prior to Job</b>														
Circulated Well: Rig <input checked="" type="checkbox"/> BJ <input type="checkbox"/>						Circulation Time: 2			Circulation Rate: 4 BPM					
Mud Density In: 8.34 LBS/G Mud Density Out: 8.34 LBS/GAL						PV & YP Mud In:			PV & YP Mud Out:					
Gas Present: NO <input checked="" type="checkbox"/> YES <input type="checkbox"/> Units:						Solids Present at End of Circulation: NO <input checked="" type="checkbox"/> YES <input type="checkbox"/>								
<b>Displacement And Mud Removal</b>														
Displaced By: Rig <input type="checkbox"/> BJ <input checked="" type="checkbox"/>						Amount Bled Back After Job: .25 BBLS								
Returns During Job: <input type="checkbox"/> NONE <input type="checkbox"/> PARTIAL <input checked="" type="checkbox"/> FULL						Method Used to Verify Returns: Visual								
Cement Returns at Surface: <input checked="" type="checkbox"/> YES <input type="checkbox"/> NO						Were Returns Planned at Surface: <input type="checkbox"/> NO <input checked="" type="checkbox"/> YES								
Pipe Movement: <input type="checkbox"/> ROTATION <input type="checkbox"/> RECIPROCATION <input checked="" type="checkbox"/> NONE <input type="checkbox"/> UNABLE DUE TO STUCK PIPE														
Centralizers: <input type="checkbox"/> NO <input checked="" type="checkbox"/> YES						Quantity: 8			Type: <input type="checkbox"/> BOW <input type="checkbox"/> RIGID					
Job Pumped Through: <input type="checkbox"/> CHOKE MANIFOLD <input type="checkbox"/> SQUEEZE MANIFOLD <input checked="" type="checkbox"/> MANIFOLD <input type="checkbox"/> NO MANIFOLD														
<b>Plugs</b>														
Number of Attempts by BJ: 0 Competition: 0						Wiper Balls Used: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES Quantity:								
Plug Catcher Used: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES						Parabow Used: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES								
Was There a Bottom: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES						Top of Plug: 0 FT			Bottom of Plug: 0 FT					
<b>Squeezes (Update Original Treatment Report for Primary Job)</b>														
BLOCK SQUEEZE <input type="checkbox"/> SHOE SQUEEZE <input type="checkbox"/> TOP OF LINER SQUEEZE <input type="checkbox"/> PLANNED <input type="checkbox"/> UNPLANNED <input type="checkbox"/>														
Liner Packer: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES						Bond Log: <input checked="" type="checkbox"/> NO <input type="checkbox"/> YES			PSI Applied: 0 Fluid Weight: 0 LBS/GAL					
<b>Casing Test (Update Original Treatment Report for Primary Job)</b>														
Casing Test Pressure: 0 PSI With 0 LBS/GAL Mud						Time Held: 00 Hours 00 Minutes								
<b>EXPLANATION: TROUBLE SETTING TOOL, RUNNING CSG, ETC. PRIOR TO CEMENTING: None</b>														

# CEMENT JOB REPORT



## Shoe Test (Update Original Treatment Report for Primary Job)

Depth Drilled out of Shoe: 0 FT Target EMW: 0 LBS/GAL Actual EMW: 0 LBS/GAL  
 Number of Times Tests Conducted: 0 Mud Weight When Test was Conducted: 0 LBS/GAL

Problems Before Job (I.E. Running Casing, Circulating Well, ETC)  
 None

Problems During Job (I.E. Lost Returns, Equipment Failure, Bulk Delivery, Foaming, ETC)  
 None

Problems After Job (I.E. Gas at Surface, Float Equipment Failed, ETC)  
 None

### PRESSURE/RATE DETAIL

### EXPLANATION

TIME HR:MIN.	PRESSURE - PSI		RATE BPM	Bbl. FLUID PUMPED	FLUID TYPE	SAFETY MEETING: BJ CREW <input checked="" type="checkbox"/> CO. REP. <input checked="" type="checkbox"/>	
	PIPE	ANNULUS				TEST LINES	4903 PSI
						CIRCULATING WELL - RIG	<input checked="" type="checkbox"/> BJ <input type="checkbox"/>
02:30	0	0	0	0	N/A	Yard Call	
04:45	0	0	0	0	N/A	Leave Yard	
05:30	0	0	0	0	N/A	Arrive on Location	
05:40	0	0	0	0	N/A	Spot Trucks/Pre Rig-up Safety Meeting	
07:00	0	0	0	0	N/A	Safety Meeting	
07:42	4903	0	0	0	H2O	Pressure Test Pump and Lines	
07:46	285	0	5	10	H2O	Preflush Fresh Water	
07:49	281	0	5	10	H2O	Preflush Dye Water	
07:53	276	0	3.6	60	CMT	Batch, Weigh, Pump 14.5# Type III + .08 lbs/sack Static Free + 1% CaCl + .25 lbs/sack Cello Flake	
08:20	0	0	0	0	N/A	Drop Plug	
08:26	256	0	4.6	44	H2O	Displacement	
08:37	285	0	2.3	11	H2O	Drop Rate	
08:42	336	0	2.3	55	H2O	Bump Plug	
08:47	875	0	0	0	N/A	Check Floats	
08:52	0	0	0	0	N/A	Post Job Safety Meeting	

BUMPED PLUG	PSI TO BUMP PLUG	TEST FLOAT EQUIP.	BBL.CMT RETURNS/ REVERSED	TOTAL BBL. PUMPED	PSI LEFT ON CSG	SPOT TOP OUT CEMENT	Service Supervisor Signature:
<input checked="" type="checkbox"/> Y <input type="checkbox"/> N	336	<input checked="" type="checkbox"/> Y <input type="checkbox"/> N	10	135	0	<input checked="" type="checkbox"/> Y <input type="checkbox"/> N	

