



# Kerr-McGee Oil & Gas Onshore LP

A subsidiary of Anadarko Petroleum Corporation

1099 18<sup>th</sup> Street  
Denver, CO 80202  
720-929-6000

July 6, 2015

Matt Lepore  
Director, Colorado Oil and Gas Conservation Commission  
Department of Natural Resources  
The Chancery Building  
1120 Lincoln Street, Suite 801  
Denver, CO 80203

Re: Request for Exception to Rule 317.p  
SUNFLOWER 24N-17HZ Location  
SUNFLOWER 24N-17HZ (COGCC DOC# 400848008)  
SUNFLOWER 25G-17HZ (COGCC DOC# 400848019)  
SUNFLOWER 40C-17HZ (COGCC DOC# 400848020)  
SUNFLOWER 40N-17HZ (COGCC DOC# 400848023)  
SUNFLOWER 7C-17HZ (COGCC DOC# 400847547)  
SUNFLOWER 7N-17HZ (COGCC DOC# 400848003)  
SUNFLOWER 8N-17HZ (COGCC DOC# 400848006)  
Township 2 North, Range 65 West  
Section 8: SENE, SWSE, SWNE, NWSE  
Weld County, Colorado

Dear Director Lepore:

Kerr-McGee Oil & Gas Onshore LP (“KMG”) respectfully requests approval for an exception to Rule 317.p to only run a cased-hole pulsed neutron, gamma-ray, and cement bond log from the kickoff point into the surface casing on one of the first wells drilled on this multi-well location. A Cement Bond Log with cased-hole gamma-ray log will be run on production casing or on intermediate casing if production liner is run. The other wells on this multi-well location will be logged with only a cement bond log with cased-hole gamma-ray log from kickoff point into the surface casing. Rule 317.p of the Colorado Oil and Gas Commission's Rules and Regulations requires wells to be logged with a minimum of a resistivity log with gamma ray. The above-named wells are requested to be exempt from this requirement due to the proximity of existing well(s) with acceptable resistivity logs with gamma ray. The available log(s) meet the offsetting well requirements and have a surface location within seven hundred fifty (750) feet of the proposed well(s).

One of the first wells drilled will be logged with a cased-hole pulsed neutron, gamma-ray, and cement bond log. The other wells on this multi-well location will run a cement bond and gamma ray log from the kickoff point into the surface casing. The Drilling Completion Report (Form 5) submitted for each well will indicate that no open-hole logs were run.

The existing well(s) within seven hundred and fifty feet (750) with acceptable resistivity logs with gamma ray are listed in the table below:

<b>Well Name</b>	<b>Well Number</b>	<b>API Number</b>	<b>Distance From Well(s)</b>	<b>Azimuth (Degrees)</b>	<b>COGCC Well File Document Number</b>
NICHOLS	8-8	05-123-21194	794	50	1217375, 1217376
NICHOLS	7-8A	05-123-21938	935	305	1488698, 1488699
DECHANT	X08-09	05-123-31791	1075	150	2445400, 2445401
DECHANT	X08-10X	05-123-34289	938	210	1599514, 1599515

Should you have any questions, please contact our office. Thank you for your consideration.

Very truly yours,

Kerr-McGee Oil & Gas Onshore LP



Craig Richardson  
Regulatory Analyst II