Company STELBAR OIL CORP. INC.
Well STELBAR 1-12
Field DE NOVA
County WASHINGTON
State COLORADO

PIONEER

STELBAR OIL CORP. INC.
1-12
DE NOVA
WASHINGTON
COLORADO

CEMENT
WITH GAMMA RAY

All interpretations are opinions based on inferences from electrical or other measurements and Pioneer Wireline Services, LLC cannot and does not guarantee the accuracy or correctness of any interpretation, and Pioneer Wireline Services, LLC will not be liable or responsible for any loss, costs, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees.

NA DENOTES NOT AVAILABLE OR NON-APPLICABLE

THANK YOU FOR USING PIONEER Energy SERVICES

Your Pioneer Energy Services Crew	Tool Data – Services	Serial Number
Engineer: M. SMITH	CCL GAMMA RAY	
Operator: W DOLPH	CCL GAMMA RAY	
Operator: B GUZMAN		
Operator:		

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			ETHERO Standard Cable Head	1.00	1.69	10.00
			SONDEXT Centralizer for testing	3.00	3.25	20.00
WAP3	11.75		CBL Probe (CSG75) Probe 2.73" Over Rubber Bend	8.75	2.75	60.00
WAP5	10.75					
			SONDEXT Centralizer for testing	3.00	3.25	20.00
CCL	3.75					
GR	2.67		GR-Probe (1CGR) Probe 2.73" w Internal Plate	4.50	2.75	30.00

Dataset: stelbar_1-12_7262015_rst.dlis
Run Length: 1,570 ft
Log Interval: 1452.00 ft to 3.25 in

PIONEER
Pioneer Energy Services

MAIN LOG

0 PSI APPLIED AT SURFACE

Database File: stelbar_1-12_7262015_rst.dlis
Dataset Pathname: pass1
Presentation Format: cbl_gr
Dataset Creation: Wed Jul 29 16:30:30 2015 by Calc 7.0.81
Charted by: Depth in Feet scaled 1:240

0	Collar Locator	+/- 1.75	0	Amplified Amplitude (mV)	10,200
	Gamma Ray (GAPI)	250	(ft/240) 0	Amplitude (mV)	100

Variable Density 1200



0	Collar Locator	+/- 1.75	0	Amplified Amplitude (mV)	10,200
	Gamma Ray (GAPI)	250	(ft/240) 0	Amplitude (mV)	100

Variable Density 1200

PIONEER
Pioneer Energy Services

REPEAT LOG

0 PSI APPLIED AT SURFACE

Database File: stelbar_1-12_7262015_rst.dlis
Dataset Pathname: pass1
Dataset Creation: Wed Jul 29 16:30:30 2015 by Calc 7.0.81
Charted by: Depth in Feet scaled 1:240

0	Collar Locator	+/- 1.75	0	Amplified Amplitude (mV)	10,200
	Gamma Ray (GAPI)	250	(ft/240) 0	Amplitude (mV)	100

Variable Density 1200

Calibration Report

Dataset File: stelbar_1-12_7262015_rst.dlis
Dataset Pathname: pass1
Dataset Creation: Wed Jul 29 16:30:25 2015 by Calc 7.0.81

Gamma Ray Calibration Report

Serial Number	11226		
Calibrated By	Calc		
Performed	Wed Jul 29 14:27:36 2015		
Calibration Value	1.0	GAPI	
Background Reading	0.0	GR	
Calibration Reading	1.0	GR	
Sensitivity	1.0000	GAPI/cps	

Cement Bond Log Calibration Report

Serial Number	350275		
Calibrated By	Calc		
Performed	Wed Jul 29 15:56:16 2015		
Depth	414.6	ft	
Casing Diameter	4.5	in	
	Y Spacing	Y Spacing	
Signal Zero	5	5.4	mV
Calibrated Amplitude	91.1920	91.1920	mV
Reading in Free Pipe	91.1920	91.1920	mV
Reading in Free Pipe	1.7364	2.01199	V
Gain	47.2473	35.2507	
Offset	0.418617	-0.296619	

Company STELBAR OIL CORP. INC.
Well STELBAR 1-12
Field DE NOVA
County WASHINGTON
State COLORADO

PIONEER
Pioneer Energy Services