
Schlumberger
Array Induction Imager Tool
Gamma Ray and Spontaneous Potential
Gamma Ray (GAPI)
Spontaneous Potential (MV)
Deep Induction (OHMM)
Medium Induction (OHMM)
Shallow Induction (OHMM)
Bit Size (IN)
Caliper (IN)
Density Correction (G/C3)
Neutron Porosity (V/V)
Bulk Density (G/C3)
Photoelectric Factor (B/E)
Delta-T Compressional (US/F)
Delta-T Shear (US/F)
Array Induction Imager Tool
Gamma Ray and Spontaneous Potential
Gamma Ray (GAPI)
Spontaneous Potential (MV)
Deep Induction (OHMM)
Medium Induction (OHMM)
Shallow Induction (OHMM)
Bit Size (IN)
Caliper (IN)
Density Correction (G/C3)
Neutron Porosity (V/V)
Bulk Density (G/C3)
Photoelectric Factor (B/E)
Delta-T Compressional (US/F)
Delta-T Shear (US/F)
Array Induction Imager Tool
Gamma Ray and Spontaneous Potential
Gamma Ray (GAPI)
Spontaneous Potential (MV)
Deep Induction (OHMM)
Medium Induction (OHMM)
Shallow Induction (OHMM)
Bit Size (IN)
Caliper (IN)
Density Correction (G/C3)
Neutron Porosity (V/V)
Bulk Density (G/C3)
Photoelectric Factor (B/E)
Delta-T Compressional (US/F)
Delta-T Shear (US/F)

Distance
Total Length
Total Weight
Total Volume
Schematic not to Scale
107.00 ft
1,500 lb
20.00 ft3

Calibration Report

Calibration Facility
Calibration Performed
Calibration Interval

Antrim Calibration, Jackfield Rd
Wed Aug 31 16:36:12 2016 by Joe Bob Sweetfish, AIT

Gamma Ray Calibration Report

Tool - Serial
Probe/Tridec: ait0112

SHOP CALIBRATION
Run via 11.14.23.0 1500
Environment
Background
Difference
Counts/Sec
0.0
0.0
Date
Offset
Adj
Units
Min
Max
Min/Hour
PRIMARY VERIFICATION
Environment
Background
Difference
0.0
0.0
Adj
Min
Max
Counts
BEFORE SURVEY VERIFICATION
Environment
Background
Difference
0.0
0.0
0.0
Adj
Min
Max
Counts
AFTER SURVEY VERIFICATION
Environment
Background
Difference
0.0
0.0
0.0
Adj
Min
Max
Counts

Segmented Inched Bored Log Calibration Report

Serial Number
Tool Model
Probe
Calibration Casing Diameter
Calibration Depth
Run 11
Calibrated (ins)
Results
Zero
Cal
Zero
Cal
Gain
Offset
0.000
0.000
0.000