HALLIBURTON

CEMENT BOND LOG

Company	CARRIZO
Well	STATE 4-16-9-60
Field	WILDCAT
County	WELD
State	CO

Company CARRIZO
Well STATE 4-16-9-60
Field WILDCAT
County WELD State CO
API No.: 05-123-38453 Serv #: 901041785
Location: LAT: 40..75495° LONG: -104.10463°
Other Services
N/A

Sec: 16 Twp: 9N Rge: 60W

Permanent Datum	GL	Elevation	5012'	Elevation
Log Measured From	KB	17 Ft. above perm. datum		K.B. 5029'
Drilling Measured From	KB			D.F. 5028'
				G.L. 5012'

Date @ Time Logged	16-JAN-2014	Type Fluid in Hole	FRESH WATER
Run No.	ONE	Density of Fluid	8.33
Depth - Driller	10847'	Fluid Level	SURFACE
Depth - Logger	5996'	Cement Top Est. Logged	1440'
Bottom - Logged Interval	5984'	Equipment / Location	11874896 / BRIGHTON
Top - Log Interval	62'	Recorded by	JOSHUA MCDANIEL
Max. Recorded Temp.	202	Witnessed by	KIRK WILLIAMS

CEMENTING DATA	Surface	Protection	Production	Liner
	String	String	String	
Date / Time Cemented				
Primary / Squeeze				
Expected Compressive Strength	psi@ hrs	psi@ hrs	psi@ hrs	psi@ hrs
Cement Volume				
Cement Type / Weight	/	/	/	/
Formulation				
Mud Type / Mud Wgt.	/	/	/	/

Borehole Record			Casing & Tubing Record			
Run Number	Bit	From	To	Size	Weight	From	To
				7	23	0	5811'

<<< Fold Here >>>

HALLIBURTON DOES NOT GUARANTEE THE ACCURACY OF ANY INTERPRETATION OF THE LOG DATA, CONVERSION OF LOG DATA TO PHYSICAL ROCK PARAMETERS OR RECOMMENDATIONS WHICH MAY BE GIVEN BY HALLIBURTON PERSONNEL OR WHICH APPEAR ON THE LOG OR IN ANY OTHER FORM. ANY USER OF SUCH DATA, INTERPRETATIONS, CONVERSIONS, OR RECOMMENDATIONS AGREES THAT HALLIBURTON IS NOT RESPONSIBLE EXCEPT WHERE DUE TO GROSS NEGLIGENCE OR WILLFUL MISCONDUCT, FOR ANY LOSS, DAMAGES, OR EXPENSES RESULTING FROM THE USE THEREOF.

Comments

PRIMARY DEPTH REFERENCE

TOL @ 5811'

ESTIMATED TOP OF CEMENT @ 1440'

MAX TEMP = 202 DEG F

THANK YOU FOR CHOOSING HALLIBURTON ENERGY SERVICES!

HALLIBURTON

MAIN PASS 1000 PSI

SCALE: 5"=100'

Database File:	carizo.db
Dataset Pathname:	pass41
Presentation Format:	1cbl
Dataset Creation:	Sun Dec 15 08:42:21 2013 by Log Halliburton Casedho
Charted by:	Depth in Feet scaled 1:240

Collar Locator			Amplified Amplitude (mV)		MSG	
0	Gamma Ray (GAPI)	150	0 Amplified Amplitude (mV) 10	200	MSG	1200
0	LTEN (lb)	2500	0 Amplitude (mV) 100			
0	TEMP (degF)	300	200 TRAVEL TIME (usec) 300			

HALLIBURTON

MAIN PASS 1000 PSI

SCALE: 5"=100'

HALLIBURTON

REPEAT PASS

SCALE: 5"=100'

Database File: carizo.db
Dataset Pathname: pass39
Presentation Format: 1cbl
Dataset Creation: Sun Dec 15 08:22:54 2013 by Log Halliburton Casedho
Charted by: Depth in Feet scaled 1:240

Collar Locator			Amplified Amplitude (mV)		MSG	
0	Gamma Ray (GAPI)	150	0 Amplified Amplitude (mV) 10	200	MSG	1200
0	LTEN (lb)	2500	0 Amplitude (mV) 100			
0	TEMP (degF)	300	200 TRAVEL TIME (usec) 300			



Collar Locator			Amplified Amplitude (mV)		MSG	
0	Gamma Ray (GAPI)	150	0 Amplified Amplitude (mV) 10	200	MSG	1200
0	LTEN (lb)	2500	0 Amplitude (mV) 100			
0	TEMP (degF)	300	200 TRAVEL TIME (usec) 300			

HALLIBURTON

REPEAT PASS

SCALE: 5"=100'

Log Variables

Database:D:\Warrior_data\carizo.db
Dataset: field/well/run1/pass41

Top - Bottom

PPT usec	MAXAMPL mV	MINAMPL mV	MINATTN db/ft	CASEOD in	PERFS	TDEPTH ft	BOTTEMP degF
287	62	0	0.8	7	0	6500	200

BITSIZE in
7.875

Calibration Report

Database File: carizo.db
Dataset Pathname: pass41
Dataset Creation: Sun Dec 15 08:42:21 2013 by Log Halliburton Casedho

Temperature Calibration Report

Serial Number: Tit1.3_02
Tool Model: Titan
Performed: Fri Jan 04 06:55:24 2002

	Reference		Reading	
Low Reference:	0.00	degF	0.00	cps
High Reference:	1.00	degF	1.00	cps

Gain: 0.10
Offset: 0.00
Delta Spacing 2

Gamma Ray Calibration Report

Type / Serial: Probe / 275

	Counts/Sec.	Gain	Offset	Jig	Units
SHOP CALIBRATION	Sat Dec 14 14:28:27 2013				
Background	107.0				cps
Calibrator	454.8				cps
		0.6929			GAPI/cps
PRIMARY VERIFICATION	Sat Dec 14 14:33:15 2013				
Background	81.1				cps
Calibrator	313.9				cps
Difference				232.9	GAPI
BEFORE SURVEY VERIFICATION	Sun Dec 15 07:23:27 2013				
Background	54.9				cps
Calibrator	305.6				cps
Difference				250.7	GAPI
AFTER SURVEY VERIFICATION					
Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	GAPI

Cement Bond Log Calibration Report

Serial Number: 275
Tool Model: Probe
Performed: Tue Jan 14 10:13:31 2014

Depth: 322.018 ft
Casing Diameter: 5.5 in

	3' Spacing	5' Spacing	
Signal Zero:	0.25	0.25	mV
Calibrated Amplitude:	62	62	mV
Reading at Signal Zero:	-0.00131836	7.32422e-005	V
Reading in Free Pipe:	0.5104	0.505518	V
Gain:	120.672	122.17	
Offset:	0.409089	0.241052	

Sensor Report

Database File: carizo.db
Dataset Pathname: pass41
Dataset Creation: Sun Dec 15 08:42:21 2013 by Log Halliburton Casedho

Sensor Name	Offset (ft)
WVF3	12.65
WVF5	11.65
CCL	4.89
GR	2.15
TEMP	0.17
LLMTEN	0
Telemetry	0

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
STNDCH	21.25		STND_CH 1.4375 IN CABLE HEAD	1.00	1.44	1.00
CENT	20.25		Probe_275 Probe 2 3/4 Centralizer	2.88	2.75	10.00
WVF3	12.65		CBL-Probe (275) Probe 2.75" Dual Receiver Bond	8.92	2.75	60.00
WVF5	11.65					
CENT	8.46		Probe_275 Probe 2 3/4 Centralizer	2.88	2.75	10.00
GR	5.58					
CCL	4.89		GR-Probe (275) Probe 2.75" 4 Channel Pulse	4.33	2.75	30.00
GR	2.15					
TEMP	0.17		TEMP-Titan (Tit1.3_02) Titan Temp 1.3875	1.25	1.39	10.00
LLMTEN	0.00					

Dataset: carizo.db: field/well/run1/pass41
Total Length: 21.25 ft
Total Weight: 121.00 lb
O.D. 2.75 in

Company	CARRIZO		
Well	STATE 4-16-9-60		
Field	WILDCAT		
County	WELD	State	CO

HALLIBURTON

CEMENT BOND LOG