

PROJECT DATA PROCESSING

THE QUALITY

CONTRACTOR OF ENERGY @ 2024

MAY NOT CAN DO IT

THANK YOU FOR CHOOSING HALLIBURTON ENERGY SERVICES

HALLIBURTON

WHO PASS: 1000 PSI

Area: 4 1/8

Density: 9.2 ppg
Viscosity: 40 sec/qt
Fluid Loss: 6 cc/30 min
Solids: 5%
Oil/Water Ratio: 80/20
Electrical Stability: 600 V
Chlorides: 25,000 ppm
Calcium: 200 ppm
Rheology: 600 RPM: 60, 300 RPM: 40, 200 RPM: 30, 100 RPM: 20, 6 RPM: 10, 3 RPM: 8
Gels: 10 sec: 12, 10 min: 18
Filtrate: 4.5 cc/30 min
Cake Thickness: 2/32 in
pH: 9.5
Alkalinity: 1.2 cc
Excess Lime: 2 lb/bbl
Sand Content: 1%
Retort: Oil: 70%, Water: 25%, Solids: 5%
Low Gravity Solids: 4%
Barite: 1%
Weighting Material: Barite
Lost Circulation Material: None
Base Fluid: Diesel
Emulsifier: Primary: 5 lb/bbl, Secondary: 2 lb/bbl
Wetting Agent: 1 lb/bbl
Fluid Loss Additive: 3 lb/bbl
Viscosifier: 4 lb/bbl
Thinner: 1 lb/bbl
Shale Inhibitor: 2 lb/bbl
Corrosion Inhibitor: 0.5 lb/bbl
Biocide: 0.1 lb/bbl
Oxygen Scavenger: 0.2 lb/bbl
Caustic Soda: 0.5 lb/bbl
Lime: 2 lb/bbl
Calcium Chloride: 1 lb/bbl
Sodium Chloride: 2 lb/bbl
Potassium Chloride: 1 lb/bbl
Polymer: 1 lb/bbl
Starch: 1 lb/bbl
Lignite: 1 lb/bbl
Lignosulfonate: 1 lb/bbl
Asphalt: 1 lb/bbl
Gilsonite: 1 lb/bbl
Graphite: 1 lb/bbl
Mica: 1 lb/bbl
Nut Plug: Fine: 1 lb/bbl, Medium: 1 lb/bbl, Coarse: 1 lb/bbl
Fiber: 1 lb/bbl
Cellulose: 1 lb/bbl
Guar Gum: 1 lb/bbl
Xanthan Gum: 1 lb/bbl
Diesel: 1 lb/bbl
Mineral Oil: 1 lb/bbl
Synthetic Oil: 1 lb/bbl
Water: 1 lb/bbl
Seawater: 1 lb/bbl
Brine: 1 lb/bbl
Formate: 1 lb/bbl
Acetate: 1 lb/bbl
Bromide: 1 lb/bbl
Iodide: 1 lb/bbl
Nitrate: 1 lb/bbl
Phosphate: 1 lb/bbl
Silicate: 1 lb/bbl
Sulfate: 1 lb/bbl
Carbonate: 1 lb/bbl
Bicarbonate: 1 lb/bbl
Hydroxide: 1 lb/bbl
Oxide: 1 lb/bbl
Peroxide: 1 lb/bbl
Chloride: 1 lb/bbl
Fluoride: 1 lb/bbl
Iodide: 1 lb/bbl
Brom


HALLIBURTON
MAIN PASS 1000 PSI
SCALE 5" = 100'
REPEAT PASS
SCALE 5" = 100'
HALLIBURTON
REPEAT PASS
SCALE 5" = 100'