



Plugging Procedure

Well Name: Spaur 10-2

API 05123129140000	Surface Legal Location SESW 10 4N 67W			Field Name Wattenberg	State CO	Well Configuration Type Vertical
Ground Elevation (ft) 4,832.00	Original KB Elevation (ft) 4,844.00	KB-Ground Distance (ft) 12.00	Spud Date 12/30/1985 00:00	Rig Release Date 1/8/1985 00:00	On Production Date 1/31/1986	

Task Details

Type Well Abandonment	Sub Type Proposed Plugging Procedure	Completed Date
--------------------------	---	----------------

Action Details

Spaur #10-2 (05-123-12914)/Plugging Procedure (Intent)

Producing formation: Niobrara/Codell

Existing Perforations: Niobrara/Codell - 6,995'-7,225'

TD: 7,306' PBTD: 7,262'

Surface Casing: 8 5/8" 24# @ 300' w/ 250 sks cmt.

Production Casing: 4 1/2" 11.6# @ 7306' w/ 370 sks cmt (TOC at 5,776').

Proposed Procedure:

1. MIRU pulling unit.
2. Blow down to tanks. Load with fluid to kill well.
3. TOOH with 2 1/16" (Might be 2 3/8" – no recent tubing record) production tubing.
4. Rig up wireline. RIH with CIBP. Set CIBP at 6,940'.
5. Load dump bailer with 2sx of 15.8#/gal CL G cement. TIH with dump bailer and spot on top of CIBP.
6. RIH w/ casing cutter and cut casing above TOC at 5,776'. Pull casing out of hole.
7. TIH with workstring to 5,900'. Circulate and condition well in preparation to pump cement stub plug.
8. RU cementers. Mix and pump 250' of cement with 55 sks of 15.8#/gal CL G cement.
9. Pull up tbg to 450'. Mix and pump 450' of cement with 165 sks of 15.8#/gal CL G cement.
10. Cut surface casing 6' below ground level and weld on cap.