
MAIN PASS
Schlumberger
Gamma Ray (GAPI)
Resistivity (OHMM)
Density (G/C3)
Neutron Porosity (V/V)
Caliper (IN)
Delta Rho (G/C3)
PE (B/E)
Photoelectric Factor (B/E)



# REPEAT SECTION

PEAK WIRELINE SERVICES, INC.

Database File: gooddata11.db
Dataset Pathname: data01
Dataset Creation: Mon Nov 30 08:54:00 2015 by Log Dist Cancelbale 10071
Charted Depth: Mon Nov 30 08:54:00 2015 to 1

| WID | TT (mksec) | [WID] | AMP (volt) | WID_2 | AMPWID | [WID_2] | VOL | 12000 | Current Way | 4 |
|---|---|---|---|---|---|---|---|---|---|---|
| 0 | CCL | [0] | AMPCH (volt) | [0]_2 | AMPWIN | [0]2 | | | | |
| 0 | VIR (GAPH) | [WID] | Borid Index | 0 | AMPWIN | [WID] | | | | |

[WID_2=(VIR (GAPH) - WID)]



Database File: gooddata12.db
Dataset Pathname: data01
Dataset Creation: Mon Nov 30 08:56:48 2015 by Log Dist Cancelbale 10071

Gamma Ray Calibration Report

| | |
|---|---|
| Serial Number | 991329R |
| Test Model | PGGL |
| Test Date | Mon Nov 30 08:57:32 2015 |
| Calibrator Value | 1.0 GAPI |
| Background Reading | 0.0 cps |
| Calibrator Reading | 1.0 cps |
| Sensitivity | 1.000 GAPI/cps |

Segmented Contact Bond Log Calibration Report

| | |
|---|---|
| Serial Number | A-SAMBA |
| Test Date | 1-Jan |
| Calibration Casing Diameter | 5.500 in |
| Calibration Depth | 10.000 ft |

Master Calibration, performed Mon Nov 30 08:27:15 2015

| | Raw (v) | | Calibrated (mv) | | Results | |
|---|---|---|---|---|---|---|
| | Zero | Cal | Zero | Cal | Gain | Offset |
| 0 | 0.000 | 2.732 | 0.250 | 71.921 | 37.472 | 0.250 |
| CAL | 0.000 | 1.991 | 0.250 | 71.921 | 39.936 | 0.250 |
| ECHO | | | | | | |
| 0 | 0.000 | 1.991 | 0.250 | 100.000 | 52.534 | 0.250 |
| 01 | 0.000 | 1.991 | 0.250 | 100.000 | 52.534 | 0.250 |
| 02 | 0.000 | 1.991 | 0.250 | 100.000 | 52.534 | 0.250 |
| 03 | 0.000 | 1.991 | 0.250 | 100.000 | 52.534 | 0.250 |
| 04 | 0.000 | 1.991 | 0.250 | 100.000 | 52.534 | 0.250 |
| 05 | 0.000 | 1.991 | 0.250 | 100.000 | 52.534 | 0.250 |
| 06 | 0.000 | 1.991 | 0.250 | 100.000 | 52.534 | 0.250 |
| 07 | 0.000 | 1.991 | 0.250 | 100.000 | 52.527 | 0.250 |
| 08 | 0.000 | 1.991 | 0.250 | 100.000 | 52.527 | 0.250 |

Internal Reference Calibration, performed Wed Dec 31 17:00:00 1969

| | Raw (v) | | Calibrated (v) | | Results | |
|---|---|---|---|---|---|---|
| | Zero | Cal | Zero | Cal | Gain | Offset |
| CAL | 0.000 | 0.000 | 0.000 | 2.732 | 1.000 | 0.000 |

Air Zero Calibration, performed Mon Nov 30 08:27:34 2015

| | Raw (v) | | Calibrated (v) | | Results | |
|---|---|---|---|---|---|---|
| | Zero | | Zero | | Offset | |
| 0 | 0.000 | | 0.000 | | 0.000 | |
| CAL | 0.000 | | 0.000 | | 0.000 | |
| ECHO | | | | | | |
| 0 | 0.000 | | 0.000 | | 0.000 | |
| 01 | 0.000 | | 0.000 | | 0.000 | |
| 02 | 0.000 | | 0.000 | | 0.000 | |
| 03 | 0.000 | | 0.000 | | 0.000 | |
| 04 | 0.000 | | 0.000 | | 0.000 | |
| 05 | 0.000 | | 0.000 | | 0.000 | |
| 06 | 0.000 | | 0.000 | | 0.000 | |
| 07 | 0.000 | | 0.000 | | 0.000 | |
| 08 | 0.000 | | 0.000 | | 0.000 | |