

Company: Noble Energy Inc

Well: Wells Ranch AE32-675

Field: Wattenberg

County: Weld State: Colorado

Isolation Scanner

Cement Evaluation (Short)

Gamma Ray - CCL Log

County: Weld

Field: Wattenberg

Location: NWNW Sec. 32, T6N, R62W

Well: Wells Ranch AE32-675

Company: Noble Energy Inc

Location:

NWNW Sec. 32, T6N, R62W

SHL: 614' FNL x 650' FWL

Lat: 40.448750/ Long: -104.354230

Elev.:

K.B. 4771.00 ft

G.L. 4747.00 ft

D.F. 4770.00 ft

Permanent Datum:

Ground Level

Elev.: 4747.00 f

Log Measured From:

Kelly Bushing

24.00 ft

above Perm.Datum

Drilling Measured From:

Kelly Bushing

API Serial No.

05-123-41732

Section: 32

Township: 6N

Range: 62W

Logging Date 04-Nov-2015

Run Number	Run 1		
Depth Driller	6890.00 ft		
Schlumberger Depth	6890.00 ft		
Bottom Log Interval	6703.00 ft		
Top Log Interval	24.00 ft		
Casing Fluid Type	Brine		
Salinity			
Density	8.4 lbm/gal		
Fluid Level	0.00 ft		
BIT/CASING/TUBING STRING			
Bit Size	8.75 in		
From	638.00 ft		
To	6890.00 ft		
Casing/Tubing Size	7 in		
Weight	26 lbm/ft		
Grade	P110		
From	0.00 ft		
To	6880.20 ft		
Max Recorded Temperatures	218.9 degF		
Logger on Bottom	04-Nov-2015	14:40:00	
Unit Number	Location: 9115	Ft. Morgan, CO	
Recorded By	Aleksei Bekhterev		
Witnessed By	Bill Mansfield		

Disclaimer


THE USE OF AND RELIANCE UPON THIS RECORDED-DATA BY THE HEREIN NAMED COMPANY (AND ANY OF ITS AFFILIATES, PARTNERS, REPRESENTATIVES, AGENTS, CONSULTANTS AND EMPLOYEES) IS SUBJECT TO THE TERMS AND CONDITIONS AGREED UPON BETWEEN SCHLUMBERGER AND THE COMPANY, INCLUDING: (a) RESTRICTIONS ON USE OF THE RECORDED-DATA; (b) DISCLAIMERS AND WAIVERS OF WARRANTIES AND REPRESENTATIONS REGARDING COMPANY'S USE AND RELIANCE UPON THE RECORDED-DATA; AND (c) CUSTOMER'S FULL AND SOLE RESPONSIBILITY FOR ANY INFERENCE DRAWN OR DECISION MADE IN CONNECTION WITH THE USE OF THIS RECORDED-DATA.


Contents

1. Header	
2. Disclaimer	
3. Contents	
4. Well Sketch	
5. Borehole Size/Casing/Tubing Record	
6. Operational Run Summary	
7. Borehole Fluids	
8. Remarks and Equipment Summary	
9. Depth Summary	
10. USI IBC SLG	
10.1 USI Fluid Properties Measurement	
10.2 Software Version	
10.3 USI IBC SLG	
10.4 Parameter Listing	
11. USI Goodwin	
11.1 USI Goodwin	
12. XYZ ( USI Fluid Acoustic Slowness vs Depth 6.0 in )	

- 13. XYZ ( USI Acoustic Impedance of Mud vs Depth 6.0 in )
- 14. Calibration Report
- 15. Tail

Well Sketch





Borehole Size/Casing/Tubing Record

Bit						
Bit Size ( in )	13.5	8.75				
Top Driller ( ft )	0	638				
Top Logger ( ft )	0	638				
Bottom Driller ( ft )	638	6890				
Bottom Logger ( ft )	638	6890				
Casing						
Size ( in )	9.625	7				
Weight ( lbm/ft )	36	26				
Inner Diameter ( in )	8.921	6.276				
Grade	J55	P110				
Top Driller ( ft )	0	0				
Top Logger ( ft )	0	0				
Bottom Driller ( ft )	628.2	6880.2				
Bottom Logger ( ft )	628.2	6880.2				

Operational Run Summary

Parameter ( unit )	Run 1					
Date Log Started	04-Nov-2015					
Time Log Started	14:16:04					
Date Log Finished	04-Nov-2015					
Time Log Finished	18:52:53					
Top Log Interval ( ft )	24.00					
Bottom Log Interval ( ft )	6703.00					
Total Depth ( ft )						
Max Hole Deviation ( deg )	0.00					
Azimuth of Max Deviation ( deg )	0.00					
Bit Size ( in )	8.750					
Logging Unit Number	9115					
Logging Unit Location	Ft. Morgan, CO					
Recorded By	Aleksei Bekhterev					

Witnessed By	Bill Mansfield					
Service Order Number	CY37-00150					


## Borehole Fluids

Parameter( unit )	Run 1					
Fluid Type	Water					
Fluid Name	Brine					
Max Recorded Temperatures ( degF )	218.9					
Salinity ( ppm )	0					
Density ( lbm/gal )	8.4					
Date Logger on Bottom	04-Nov-2015					
Time Logger on Bottom	14:40:00					
Total Solid ( % )						
High Gravity Solids ( % )						

## Remarks and Equipment Summary

Run 1: Toolstring			Run 1: Remarks
<b>Equip name</b> <b>LEH-QT</b> LEH-QT	<b>length</b> <b>43.33</b>	<b>MP name</b> <b>Offset</b>	Toolstring ran as per tool sketch
			12 ppg Flex Seal, 15.8 ppg Tail cement
			Repeat pass is done with 0 psi
<b>EDTC-B</b> EDTH-B EDTG-A EDTC-B	<b>40.41</b>		Main pass is done with 2500 psi
			Temperature at the bottom: 218.9 degF
		<b>CTEM</b> 36.91 <b>ACCZ</b> 0.00 <b>HV</b> 0.00 <b>Gamm</b> 35.04 <b>a Ray</b> <b>TelSta</b> 33.91 <b>tus</b>	Top of cement: 760 ft
		<b>Tempe</b> 33.89 <b>rature</b>	Log started 30 ft above top of the liner (6703 ft)
<b>HGNS-H</b> <b>:3985</b> HGNH NPV-N NSR-F:51 38 HACCZ-H :4269 HMCA-H HGNS-H: 3985	<b>33.91</b>	<b>GR</b> 33.17	Data affected by high deviation at TD-6180 ft section
			Casing anomaly observed from 760' to 490'. Repeated at high resolution
			Crew: Jake Jump, Jay Musgrave
			Thank you for choosing Schlumberger Wireline!
		<b>CNL Po</b> 26.84 <b>rosity</b> <b>HMCA</b> 24.5 <b>HGNS</b> 24.5 <b>Accele</b> 0.00 <b>romete</b> <b>r</b>	
<b>AH-184</b> [2]	<b>24.5</b>		
<b>AH-184</b> [1]	<b>22.5</b>		
<b>CME-AF</b>	<b>20.5</b>		
<b>USIT-E</b> ECH-MFA :1964 USAC-A USIS-A:9	<b>16.71</b>		

USSC-B  
IBCS-B  
FAR-SEN  
SOR  
NEAR-SE  
NSOR  
USI-SEN  
SOR  
EMITTER  
-SENSOR



Lengths are in ft  
Maximum Outer Diameter = 4.472 in  
Line: Sensor Location, Value: Gating Offset  
All measurements are relative to TOOL\_ZERO

Depth Summary

	Run 1		
--	-------	--	--

Depth Measuring Device

Type	IDW-B		
Serial Number			
Calibration Date			
Calibrator Serial Number			
Calibration Cable Type			
Wheel Correction 1	0		
Wheel Correction 2	0		

Tension Device

Type	CMTD-B/A		
Serial Number			
Calibration Date			
Calibrator Serial Number			
Number of Calibration Points	0		

Logging Cable

Type	7-46A-XS		
Serial Number			
Length	12000.00 ft		
Conveyance Type	Wireline		
Rig Type	Crane		

Run 1:Depth Control Parameters	Depth Control Remarks
--------------------------------	-----------------------

Log Sequence	First Log In the Well	All Schlumberger depth policies followed
Rig Up Length At Surface		IDW used as primary depth device
Rig Up Length At Bottom		Z-chart used as secondary depth reference
Rig Up Length Correction		
Stretch Correction		
Tool Zero Check At Surface		

## USI IBC SLG

## USIT - Fluid Properties Measurement

Run Name	Pass Name	Start Depth(ft)	Stop Depth(ft)
Run 1	Main[3]:Up	6709.52	70.33

Fluid Velocity = "Automatic".  
CFVL equals DFSL channel

Start Depth(ft)	Stop Depth(ft)	Start Value(us/ft)	End Value(us/ft)
-----------------	----------------	--------------------	------------------

Mud Impedance = "FreePipe Norm."

Free Pipe normalization zone is : 119.02m(390.48ft) to 126.62m(415.43ft)

MUD\_N\_FRP = 1.15

DFD = 1.01g/cm3(8.40lbm/gal)

CZMD median computed in free pipe normalization interval = 1.68 MRayl

Start Depth(ft)	Stop Depth(ft)	Start Value(Mrayl)	End Value(Mrayl)
-----------------	----------------	--------------------	------------------

Run 1

IBC SLG

## Software Version

Acquisition System	Version
Maxwell 2016	6.0.52439.3100


## Log


Company:Noble Energy Inc Well:Wells Ranch AE32-675

Run 1: Main[3]:Up:S009


Description: USI IBC SLG Format: USI IBC SLG Index Scale: 2 in per 100 ft Index Unit: ft Index Type: Measured Depth Creation Date: 04-Nov-2015 19:18:56

TIME\_1900 - Time Marked every 60.00 (s)




















































IBC_FLEX_SEL	IBC Flexural Selection	USIT-E	Automatic	
IBC_OFFSET_SEL	IBC Flexural Offset Selector	USIT-E	IBC_FRP_OFFSET	
IBC_ZMUD_SEL	IBC Mud Impedance Selection	USIT-E	FreePipe Norm.	
ICE_PROCESS	ICE Processing	USIT-E	Yes	
IMAR	Image Rotation	USIT-E	Off	
MEAS_WLEN	Tcube Processing Window Length in Measurement Mode	USIT-E	22.5	us
MUD_N_FRP	Free Pipe Mud Normalization Factor	USIT-E	1.15	
MUD_N_THE	Theoretical Mud Normalization Factor	USIT-E	1	
U-USIT_OCDI	Outer Casing Diameter	USIT-E	0	in
U-USIT_OCSH	Outer Casing Shoe	USIT-E	0	ft
U-USIT_OCWE	Outer Casing Weight	USIT-E	0	lbm/ft
RCOD	Reference Calibrator Outer Diameter	USIT-E	7	in
RCSO	Reference Calibrator Standoff	USIT-E	1.181	in
RCTH	Reference Calibrator Thickness	USIT-E	0.295	in
SOCN	Standoff Distance	EDTC-B	0.125	in
SOCO	Standoff Correction Option	EDTC-B	No	
TCUB	T^3 Processing Level	USIT-E	Loop	
THDH	Maximum Search Thickness (percentage of nominal)	USIT-E	130	%
THDL	Minimum Search Thickness (percentage of nominal)	USIT-E	70	%
TPOS_EDTC	Tool Position: Centered or Eccentered	EDTC-B	Centered	
U-USIT_DFSZ	Drilling Fluid Specific Acoustic Impedance	USIT-E	2.07	Mrayl
U-USIT_UFAO	SIT Flexural Attenuation Offset	USIT-E	-15	dB/m
UFGDE	Fiberglass Density	USIT-E	16.27	lbm/gal
UFGPS	Fiberglass Processing Selection	USIT-E	No	
UFGVL	Fiberglass Velocity	USIT-E	9678.48	ft/s
U-USIT_UIAP	IBC Answer Product Enabled	USIT-E	SolidLiquidGasMap	
THDP	Thickness Detection Policy	USIT-E	Fundamental	
VCAS	Ultrasonic Transversal Velocity in Casing	USIT-E	51.4	us/ft
ZCAS	Acoustic Impedance of Casing	USIT-E	46.25	Mrayl
ZINI	Initial Estimate of Cement Impedance	USIT-E	-1	Mrayl
ZMUD	Acoustic Impedance of Mud	Borehole	1.48	Mrayl
ZTCM	Acoustic Impedance Threshold for Cement	USIT-E	2.6	Mrayl
ZTGS	Acoustic Impedance Threshold for Gas	USIT-E	0.3	Mrayl

Depth Zone Parameters			
Parameter	Value	Start ( ft )	Stop ( ft )
BS	13.5	35.5	638
BS	8.75	638	6709.5

All depth are actual.

Tool Control Parameters

Run 1: Parameters				
Parameter	Description	Tool	Value	Unit
AGMN	Minimum Gain of Cartridge	USIT-E	-12	dB
AGMX	Maximum Gain of Cartridge	USIT-E	18	dB
U-USIT_DDT5	USIC Downhole Decimation for T5 only	USIT-E	0_NONE	
DOT(DOS)	Distance between Opposite Transducer Faces	USIT-E	2.874	in
EMXV	EMEX Voltage	USIT-E	Time Zoned	V
HRES	Horizontal Resolution	USIT-E	10 deg	
MAX_LOG_SPEED	Toolstring Maximum Logging Speed	WLSESSION	2700	ft/h
MOTOR_PROTECT	Motor Protection	USIT-E	On	

IMUC	Type of Mud	USIT-E	BRI	
UACLV_PERM	Ultrasonic ACLV Permanent	USIT-E	No	
U-USIT_UFWB	Far Receiver Window Begin Time	USIT-E	Time Zoned	us
U-USIT_UFWE	Far Receiver Window End Time	USIT-E	Time Zoned	us
ULOG	Logging Objective	USIT-E	MEASUREMENT	
UMFR	Modulation Frequency	USIT-E	333333	Hz
U-USIT_UNWB	Near Receiver Window Begin Time	USIT-E	Time Zoned	us
U-USIT_UNWE	Near Receiver Window End Time	USIT-E	Time Zoned	us
USFR	Ultrasonic Sampling Frequency	USIT-E	500000	Hz
UPAT	USIT Emission Pattern	USIT-E	Pattern 375 KHz	
UWKM	USIT Working Mode	USIT-E	10 deg at 6.0 in LF	
USIT_DEPTHLOG	Starting Depth Log for Ultrasonics	USIT-E	6703.8	ft
USSP	Ultrasonic Service	USIT-E	IBC	
U-USIT_UTAN	Transducer Angles	USIT-E	33_DEG	
VRES	Vertical Resolution	USIT-E	6.0 in	
WINB	Window Begin Time	USIT-E	Time Zoned	us
WINE	Window End Time	USIT-E	Time Zoned	us

Time Zone Parameters					
Parameter	Value	Start Time	Stop Time	Start Depth ( ft )	Stop Depth ( ft )
EMXV	100	04-Nov-2015 15:29:07	04-Nov-2015 15:50:20	6709.52	6304.7
EMXV	95	04-Nov-2015 15:50:20	04-Nov-2015 15:50:23	6304.7	6301.88
EMXV	90	04-Nov-2015 15:50:23	04-Nov-2015 15:52:13	6301.88	6223.76
EMXV	95	04-Nov-2015 15:52:13	04-Nov-2015 15:52:17	6223.76	6221.22
EMXV	100	04-Nov-2015 15:52:17	04-Nov-2015 15:52:20	6221.22	6218.96
EMXV	105	04-Nov-2015 15:52:20	04-Nov-2015 15:52:22	6218.96	6217.08
EMXV	110	04-Nov-2015 15:52:22	04-Nov-2015 15:52:26	6217.08	6214.92
EMXV	115	04-Nov-2015 15:52:26	04-Nov-2015 15:54:13	6214.92	6137.62
EMXV	110	04-Nov-2015 15:54:13	04-Nov-2015 15:54:16	6137.62	6134.91
EMXV	105	04-Nov-2015 15:54:16	04-Nov-2015 15:54:22	6134.91	6131.04
EMXV	100	04-Nov-2015 15:54:22	04-Nov-2015 15:54:25	6131.04	6128.34
EMXV	95	04-Nov-2015 15:54:25	04-Nov-2015 15:54:29	6128.34	6125.38
EMXV	90	04-Nov-2015 15:54:29	04-Nov-2015 15:54:33	6125.38	6122.53
EMXV	85	04-Nov-2015 15:54:33	04-Nov-2015 15:54:39	6122.53	6118.62
EMXV	80	04-Nov-2015 15:54:39	04-Nov-2015 16:19:16	6118.62	5066.61
EMXV	75	04-Nov-2015 16:19:16	04-Nov-2015 16:19:19	5066.61	5064.39
EMXV	70	04-Nov-2015 16:19:19	04-Nov-2015 16:19:22	5064.39	5061.93
EMXV	65	04-Nov-2015 16:19:22	04-Nov-2015 16:19:25	5061.93	5059.68
EMXV	60	04-Nov-2015 16:19:25	04-Nov-2015 16:19:29	5059.68	5057.18
EMXV	55	04-Nov-2015 16:19:29	04-Nov-2015 18:16:32	5057.18	70.33
U-USIT_UFWB	133	04-Nov-2015 15:29:07	04-Nov-2015 15:39:08	6709.52	6709.02
U-USIT_UFWB	80.28	04-Nov-2015 15:39:08	04-Nov-2015 15:40:28	6709.02	6687.75
U-USIT_UFWB	82.32	04-Nov-2015 15:40:28	04-Nov-2015 15:41:56	6687.75	6662.55
U-USIT_UFWB	70.81	04-Nov-2015 15:41:56	04-Nov-2015 15:55:28	6662.55	6083.27
U-USIT_UFWB	88.6	04-Nov-2015 15:55:28	04-Nov-2015 15:55:44	6083.27	6071.17
U-USIT_UFWB	103.25	04-Nov-2015 15:55:44	04-Nov-2015 16:01:05	6071.17	5841.44
U-USIT_UFWB	110.57	04-Nov-2015 16:01:05	04-Nov-2015 16:18:22	5841.44	5105.48

U-USIT_UFWB	124.18	04-Nov-2015 16:18:22	04-Nov-2015 18:16:32	5105.48	70.33
U-USIT_UFWE	173	04-Nov-2015 15:29:07	04-Nov-2015 15:39:10	6709.52	6708.52
U-USIT_UFWE	225.08	04-Nov-2015 15:39:10	04-Nov-2015 15:39:51	6708.52	6697.78
U-USIT_UFWE	199.52	04-Nov-2015 15:39:51	04-Nov-2015 15:55:31	6697.78	6080.62
U-USIT_UFWE	197.43	04-Nov-2015 15:55:31	04-Nov-2015 16:01:07	6080.62	5840.02
U-USIT_UFWE	191.15	04-Nov-2015 16:01:07	04-Nov-2015 16:01:23	5840.02	5828.08
U-USIT_UFWE	179.64	04-Nov-2015 16:01:23	04-Nov-2015 16:18:23	5828.08	5104.48
U-USIT_UFWE	174.41	04-Nov-2015 16:18:23	04-Nov-2015 18:16:32	5104.48	70.33
U-USIT_UNWB	102	04-Nov-2015 15:29:07	04-Nov-2015 15:39:15	6709.52	6707.31
U-USIT_UNWB	48.1	04-Nov-2015 15:39:15	04-Nov-2015 15:40:16	6707.31	6690.98
U-USIT_UNWB	51.97	04-Nov-2015 15:40:16	04-Nov-2015 15:55:20	6690.98	6088.52
U-USIT_UNWB	64.53	04-Nov-2015 15:55:20	04-Nov-2015 15:55:52	6088.52	6065.82
U-USIT_UNWB	76.04	04-Nov-2015 15:55:52	04-Nov-2015 15:56:57	6065.82	6018.6
U-USIT_UNWB	58.25	04-Nov-2015 15:56:57	04-Nov-2015 15:57:02	6018.6	6014.78
U-USIT_UNWB	77.08	04-Nov-2015 15:57:02	04-Nov-2015 16:01:10	6014.78	5837.64
U-USIT_UNWB	82.32	04-Nov-2015 16:01:10	04-Nov-2015 16:18:15	5837.64	5110.44
U-USIT_UNWB	91.74	04-Nov-2015 16:18:15	04-Nov-2015 18:16:32	5110.44	70.33
U-USIT_UNWE	142	04-Nov-2015 15:29:07	04-Nov-2015 15:39:16	6709.52	6707
U-USIT_UNWE	147.15	04-Nov-2015 15:39:16	04-Nov-2015 15:39:17	6707	6706.84
U-USIT_UNWE	175.8	04-Nov-2015 15:39:17	04-Nov-2015 15:40:15	6706.84	6691.48
U-USIT_UNWE	159.76	04-Nov-2015 15:40:15	04-Nov-2015 15:41:53	6691.48	6664.24
U-USIT_UNWE	171.27	04-Nov-2015 15:41:53	04-Nov-2015 15:55:22	6664.24	6087.07
U-USIT_UNWE	160.8	04-Nov-2015 15:55:22	04-Nov-2015 16:01:09	6087.07	5838.53
U-USIT_UNWE	152.43	04-Nov-2015 16:01:09	04-Nov-2015 16:18:17	5838.53	5109.12
U-USIT_UNWE	139.87	04-Nov-2015 16:18:17	04-Nov-2015 17:50:59	5109.12	1129.98
U-USIT_UNWE	144.06	04-Nov-2015 17:50:59	04-Nov-2015 18:16:32	1129.98	70.33
WINB	37.61	04-Nov-2015 15:29:07	04-Nov-2015 15:39:12	6709.52	6708.1
WINB	14.62	04-Nov-2015 15:39:12	04-Nov-2015 15:40:53	6708.1	6681.18
WINB	44.25	04-Nov-2015 15:40:53	04-Nov-2015 15:40:59	6681.18	6679.44
WINB	18.93	04-Nov-2015 15:40:59	04-Nov-2015 15:41:06	6679.44	6677.57
WINB	51.92	04-Nov-2015 15:41:06	04-Nov-2015 15:41:14	6677.57	6675.33
WINB	19.69	04-Nov-2015 15:41:14	04-Nov-2015 15:55:24	6675.33	6085.92
WINB	28.13	04-Nov-2015 15:55:24	04-Nov-2015 15:57:38	6085.92	5989.41
WINB	17.39	04-Nov-2015 15:57:38	04-Nov-2015 16:01:03	5989.41	5843.08
WINB	28.13	04-Nov-2015 16:01:03	04-Nov-2015 16:18:19	5843.08	5107.68
WINB	35.81	04-Nov-2015 16:18:19	04-Nov-2015 18:16:32	5107.68	70.33
WINE	77.61	04-Nov-2015 15:29:07	04-Nov-2015 15:39:13	6709.52	6707.73
WINE	90.58	04-Nov-2015 15:39:13	04-Nov-2015 15:44:09	6707.73	6572.32
WINE	68.81	04-Nov-2015 15:44:09	04-Nov-2015 15:44:14	6572.32	6568.97
WINE	89.53	04-Nov-2015 15:44:14	04-Nov-2015 15:48:47	6568.97	6372.58
WINE	101.81	04-Nov-2015 15:48:47	04-Nov-2015 15:55:26	6372.58	6084.67
WINE	91.06	04-Nov-2015 15:55:26	04-Nov-2015 16:18:20	6084.67	5106.77
WINE	78.78	04-Nov-2015 16:18:20	04-Nov-2015 17:50:51	5106.77	1135.72
WINE	83.39	04-Nov-2015 17:50:51	04-Nov-2015 17:50:58	1135.72	1130.86



WINE	78.02	04-Nov-2015 17:50:58	04-Nov-2015 18:16:32	1130.86	70.33
------	-------	----------------------	----------------------	---------	-------

All depth are at tool zero.

USI Goodwin

Run 1

IBC Goodwin Compressed

Log


Company:Noble Energy Inc


Well:Wells Ranch AE32-675

Run 1: Main[3]:Up:S009

Description: USI Goodwin    Format: USI Goodwin    Index Scale: 0.1 in per 100 ft    Index Unit: ft    Index Type: Measured Depth    Creation Date: 04-Nov-2015 19:19:03

TIME\_1900 - Time Marked every 60.00 (s)








Gamma Ray  
(ECGR\_EDT  
C) EDTC-B  
0 gAPI 150

Amplitude of  
Eccentering  
(ECCE)  
USIT-E  
0 in 0.5

Minimum Acoustic Impedance 1 (MIN_AI1) USIT-E	Minimum Acoustic Impedance 3 (MIN_AI3) USIT-E	Minimum Acoustic Impedance 5 (MIN_AI5) USIT-E	Minimum Acoustic Impedance 7 (MIN_AI7) USIT-E	Minimum Acoustic Impedance 9 (MIN_AI9) USIT-E	Acoustic Impedance Minimum (AIMN) USIT-E	Minimum Flexural Attenuation (U-USIT_UF AX) USIT-E
0 Mrayl 15	0 Mrayl 15	0 Mrayl 15	0 Mrayl 15	0 Mrayl 15	0 Mrayl 7.5	40 dB/m 140
Maximum Acoustic Impedance 1 (MAX_AI1) USIT-E	Maximum Acoustic Impedance 3 (MAX_AI3) USIT-E	Maximum Acoustic Impedance 5 (MAX_AI5) USIT-E	Maximum Acoustic Impedance 7 (MAX_AI7) USIT-E	Maximum Acoustic Impedance 9 (MAX_AI9) USIT-E	Acoustic Impedance Maximum (AIMX) USIT-E	Maximum Flexural Attenuation (U-USIT_UF AX) USIT-E
0 Mrayl 15	0 Mrayl 15	0 Mrayl 15	0 Mrayl 15	0 Mrayl 15	0 Mrayl 7.5	40 dB/m 140
Average Acoustic Impedance 1 (AV_AI1) USIT-E	Average Acoustic Impedance 3 (AV_AI3) USIT-E	Average Acoustic Impedance 5 (AV_AI5) USIT-E	Average Acoustic Impedance 7 (AV_AI7) USIT-E	Average Acoustic Impedance 9 (AV_AI9) USIT-E	Acoustic Impedance Average (AIAV) USIT-E	Average Flexural Attenuation (U-USIT_UF AV) USIT-E
0 Mrayl 15	0 Mrayl 15	0 Mrayl 15	0 Mrayl 15	0 Mrayl 15	0 Mrayl 7.5	40 dB/m 140
Minimum Acoustic Impedance 2 (MIN_AI2) USIT-E	Minimum Acoustic Impedance 4 (MIN_AI4) USIT-E	Minimum Acoustic Impedance 6 (MIN_AI6) USIT-E	Minimum Acoustic Impedance 8 (MIN_AI8) USIT-E			
-7.5Mrayl 7.5	-7.5Mrayl 7.5	-7.5Mrayl 7.5	-7.5Mrayl 7.5			
Maximum Acoustic Impedance 2 (MAX_AI2) USIT-E	Maximum Acoustic Impedance 4 (MAX_AI4) USIT-E	Maximum Acoustic Impedance 6 (MAX_AI6) USIT-E	Maximum Acoustic Impedance 8 (MAX_AI8) USIT-E			
-7.5Mrayl 7.5	-7.5Mrayl 7.5	-7.5Mrayl 7.5	-7.5Mrayl 7.5			
Average Acoustic	Average Acoustic	Average Acoustic	Average Acoustic			



Acoustic Impedance 2 (AV_AI2) USIT-E	Acoustic Impedance 4 (AV_AI4) USIT-E	Acoustic Impedance 6 (AV_AI6) USIT-E	Acoustic Impedance 8 (AV_AI8) USIT-E
-7.5Mrayl 7.5	-7.5Mrayl 7.5	-7.5Mrayl 7.5	-7.5Mrayl 7.5


TIME\_1900 - Time Marked every 60.00 (s)

Description: USI Goodwin    Format: USI Goodwin    Index Scale: 0.1 in per 100 ft    Index Unit: ft    Index Type: Measured Depth    Creation Date: 04-Nov-2015 19:19:03


# Fluid Acoustic Slowness vs Depth

2D Cross Plot

Index Range: From 6708.50 to 69.50 ft



# Acoustic Impedance of Mud vs Depth



Calibration Report							
EDTC-B (Enhanced Digital Telemetry Cartridge - Version B) Calibration - Run 1							
Primary Equipment :							
EDTC-B				EDTC-B			
Calibration Parameter :							
Plus Reference (Jig minus background reference)				160			
EDTC-B Accelerometer Calibration - EDTC-B Accelerometer Calibration							
Before (Measured):		14:16:55 04-Nov-2015					
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div></div>
AZ Vertical Measurement	ft/s2	Before	32.19	31.53	32.09	32.84	<div><div></div><div></div><div></div><div></div><div></div><div></div></div>
EDTC-B Memory Data - EDTC-B Memory Data							
Master (EEPROM):		14:16:38 04-Nov-2015					
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div><div></div><div></div></div>
Initial PMT HV	V	Master			1482.000		<div><div></div><div></div></div>

Accelerometer Serial Number		Master	-----	-----	696	-----	<div></div>
Accelerometer Coefficients - 0		Master	-----	-----	2.987	-----	<div></div>
Accelerometer Coefficients - 1		Master	-----	-----	0.000	-----	<div></div>
Accelerometer Coefficients - 2		Master	-----	-----	0.000	-----	<div></div>
Accelerometer Coefficients - 3		Master	-----	-----	0.000	-----	<div></div>
Accelerometer Coefficients - 4		Master	-----	-----	0.000	-----	<div></div>
Accelerometer Coefficients - 5		Master	-----	-----	0.000	-----	<div></div>
Accelerometer Coefficients - 6		Master	-----	-----	0.000	-----	<div></div>
Accelerometer Coefficients - 7		Master	-----	-----	-0.007	-----	<div></div>
Accelerometer Coefficients - 8		Master	-----	-----	0.000	-----	<div></div>
Accelerometer Coefficients - 9		Master	-----	-----	0.000	-----	<div></div>
Accelerometer Coefficients - 10		Master	-----	-----	0.000	-----	<div></div>
Accelerometer Coefficients - 11		Master	-----	-----	0.000	-----	<div></div>
Gamma-Ray Detector Serial Number		Master			7792		<div></div>
EDTC-B Gamma-Ray Calibration - Gamma Ray Coefficients							

Before (Measured):		20:41:14 01-Nov-2015					
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div></div>
Gamma Ray Gain		Before	1.000	0.900	1.066	1.100	<div></div>

EDTC-B Gamma-Ray Calibration - Gamma Ray Accumulations							
Before (Measured):		20:41:14 01-Nov-2015					
Measurement	Unit	Phase	Nominal	Low Limit	Actual	High Limit	<div></div>
RGR Zero Measurement	gAPI	Before		0	70.943	120.000	<div></div>
RGR Plus Measurement	gAPI	Before	160.000	145.000	150.150	175.000	<div></div>

Well: Wells Ranch AE32-675  
Field: Wattenberg  
County: Weld  
State: Colorado

Isolation Scanner

Cement Evaluation (Short)

Gamma Ray - CCL Log