

1625 Broadway
Suite 2000
Denver, CO 80202

Tel: 303.228.4000
Fax: 303.228.4280
www.nobleenergyinc.com



January 5, 2016

Colorado Oil and Gas Conservation Commission
The Chancery Building
1120 Lincoln Street, Suite 801
Denver, CO 80203
Attn: Mr. Matt Lepore, Director

RE: **Letter to the Director, Rule 317.p Requirement to Log Well Exception**
Lapp A15-655 Pad (400921790), Lapp A15-635 (400921784), Lapp A15-645 (400921785), Lapp A15-648
(400921786), Lapp A15-651 (400921789)
Section 13: NW/4SW/4 Township 6 North, Range 64 West, 6th P.M.
Weld County, Colorado

Dear Director:

Noble Energy, Inc. ("Noble") intends to drill and produce the above referenced horizontal oil and gas well(s), to be located as described above. Noble respectfully requests the Director to approve an exception to Rule 317.p for the referenced proposed wells, as suitable gamma ray and resistivity logs exist in the records from prior wells drilled in the vicinity of the surface-hole location of the proposed new well(s).

The logs from the following prior-drilled well are proposed to provide adequate log coverage to characterize the geology of the area are located within 750' of the subject well(s).

Well name(s) with Log	API Number	Distance to well	Direction to well	Log Document Number(s)	Type of Log
Lapp 13-32	05-123-24136	439'	SE	1360938	Resistivity

One of the first wells drilled on the multi-well location will be logged with cased-hole pulsed neutron, gamma-ray, and cement bond logs from kick-off point into the surface casing. The other wells on the multi-well location will be logged with only a cement bond log with cased-hole gamma-ray log from kick-off point into the surface casing. The stratigraphy in the well logged with cased-hole pulsed neutron and gamma-ray can be described by correlating the cased-hole logs with existing open-hole resistivity and gamma-ray well log control in offsetting wells. The stratigraphy in the wells logged with only a cement bond log with cased-hole gamma-ray log can be described by correlating the cased-hole gamma-ray log with the cased-hole pulsed neutron and gamma-ray logs run in the one well. The depth of the surface casing in all the wells can be verified by the attenuation of either or both the gamma-ray and the cement bond log at the surface casing shoe. The coverage of aquifers in all the wells can be verified through the combination of the description of the stratigraphy and the verification of the depth of surface casing. Logging program description provided as a Drilling/Completion Operations BMP on every Form 2 on the multi-well location, including a description of the Form 5 requirements. Rule 317.p Exception Request Letter attached to the Form 2 (letter requirements below). The Form 5 for each well will list all logs run in that well and have those logs attached. The Form 5 for each well shall clearly state "No open-hole logs were run." Noble hereby requests the Director to grant an exception to Rule 317.p.

If you should have any questions or concerns regarding this permit, please contact the undersigned at 303-228-4000.

Respectfully,

Jan Kajiwar

Jan Kajiwar
Regulatory Analyst III