



May 17, 2016

Matt Lepore
 Director, Colorado Oil and Gas Conservation Commission
 Department of Natural Resources
 The Chancery Building
 1120 Lincoln Street, Suite 801
 Denver, CO 80203

Re: Request for Exception to Rule 317.p
 Evans 7-26 Pad

Evans 7-26 (West)		
API	New Name	COGCC Document #
05-123-41473	Evans 25C-14-L	400697485
05-123-41476	Evans 11N-14C-L	400695437
05-123-41459	Evans 3N-14B-XR	400695462
05-123-41477	Evans 29N-14A-XR	400695493
05-123-41466	Evans 29C-14-XR	400695572
05-123-41470	Evans 29N-14C-XR	400695627
05-123-41471	Evans 4N-14B-XR	400695709
05-123-41460	Evans 4N-14A-XR	400695747
05-123-41474	Evans 4C-14-XR	400695775
05-123-41468	Evans 4N-14C-XR	400697462
05-123-41479	Evans 30N-14B-XR	400697442

Evans 7-26 (East)		
API	New Name	COGCC Document #
05-123-41461	Evans 25N-14B-L	400697421
05-123-41463	Evans 10N-14C-L	400695784
05-123-41458	Evans 10C-14-L	400697334
05-123-41472	Evans 10N-14A-L	400697207

05-123-41478	Evans 10N-14B-L	400697324
05-123-41475	Evans 24N-14C-L	400697216
05-123-41464	Evans 24C-14-L	400697234
05-123-41467	Evans 24N-14A-L	400697317
05-123-41465	Evans 24N-14B-L	400697384
05-123-41462	Evans 9N-14C-L	400697366
05-123-41469	Evans 9C-14-L	400697352

SWNE Section 26, Township 5 North, Range 66 West
Weld County, Colorado

Dear Director Lepore:

Synergy Resources Corporation (SRC) respectfully requests approval for an Open Hole Logging Exception to Rule 317.p. The above-named wells are requested to be exempt from this requirement due to the proximity of existing well(s) with acceptable petrophysical logs that adequately describes the stratigraphy of the wellbore, adequately verifies surface casing setting depth, and adequately verifies any aquifer coverage. The existing wells listed in the table below have log(s) which meet the offsetting well surface-hole distance and bearing requirements.

Well Name	Well Number	API Number	Distance From Well(s)	Azimuth (Degrees)	Log Type/Types	Log Type Document Number
Rhoadarmer	#1-26B	05.123.24888	215'	211°	Triple Combo Logs	1406592/1405844

One of the first wells drilled on this multi-well location will be logged with a cased-hole pulsed neutron, gamma ray, and cement bond log from kick-off point into the surface casing. The other wells on this multi-well location will be logged with only a cement bond and cased-hole gamma ray log from the kick-off point into the surface casing. The Drilling Completion Report (Form 5) submitted for each well will indicate that no open-hole logs were run.

Should you have any question, please feel to contact me at (720) 616-4319.

Sincerely,



Synergy Resources Corporation

Erin Ekblad

Manager of Regulatory Affairs