

Operator: Synergy Resources Corporation
Well Name: Wolfson 26-1
Legal: NWNW, Section 24, Township 6N, Range 68W
Location: Larimer, CO
API: 05-123-14573
Surface: 8.625" 24# @ 225' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7,335' **Hole Size:** 7.875" **TOC:** 6,100' (COGCC site)
Perforations: 6,876'-7,041' (Nio) 7,178'-7,190' (Codell)
TD: 7,335'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and check surface annulus for pressure
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2", 11.6# retainer, set at 6,876' and squeeze perfs, TOOH
 - a. Pump 14 sks to squeeze perfs and on top of retainer to create 100' plug
 - b. Wait 4 hours and tag plug
6. Pressure test csg to 500 psi for 15 minutes
7. Cut 4.5" @ 450', and POOH
8. TIH to 500' and pump a 500' shoe plug (0' – 500')
 - a. 200 sx of 15.8# class G neat 1.15 cu./ft. yield cement, (500' – 0')
 - b. 50' in, 50' out of surface casing
 - c. Wait 4 hours and tag plug
9. RDMO WO unit
10. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
11. Weld on cap with ID plate, inscribed with well location, and identity
12. Backfill, clean location
13. P&A complete