

FORM  
5A

Rev  
06/12

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

401061774

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 47120

2. Name of Operator: KERR MCGEE OIL & GAS ONSHORE LP

3. Address: P O BOX 173779

City: DENVER State: CO Zip: 80217-

4. Contact Name: ILA BEALE

Phone: (720) 929-6408

Fax:

Email: ila.beale@anadarko.com

5. API Number 05-123-41347-00

7. Well Name: JESTER

8. Location: QtrQtr: SWNW Section: 15 Township: 3N Range: 67W Meridian: 6

9. Field Name: WATTENBERG Field Code: 90750

6. County: WELD

Well Number: 40N-14HZ

## Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: FRACTURE STIMULATION  
Treatment Date: 05/15/2016 End Date: 05/23/2016 Date of First Production this formation: 05/28/2016  
Perforations Top: 7470 Bottom: 16451 No. Holes: 1044 Hole size: 0.42  
Provide a brief summary of the formation treatment: Open Hole: ☐

"PERF AND FRAC FROM 7470-16,451.  
400 BBL ACID, 9,009 BBL PUMP DOWN, 184,592 BBL SLICKWATER, - 194,000 BBL TOTAL FLUID  
780,400# 100 MESH GENOA/SAND HILLS, 4,396,600# 40/70 OTTAWA/ST. PETERS, - 5,177,000# TOTAL SAND."

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 194000 Max pressure during treatment (psi): 7376  
Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): 8.30  
Type of gas used in treatment: Min frac gradient (psi/ft): 0.93  
Total acid used in treatment (bbl): 400 Number of staged intervals: 45  
Recycled water used in treatment (bbl): 2710 Flowback volume recovered (bbl): 2817  
Fresh water used in treatment (bbl): 190890 Disposition method for flowback: RECYCLE  
Total proppant used (lbs): 5177000 Rule 805 green completion techniques were utilized: ☒  
Reason why green completion not utilized:

Fracture stimulations must be reported on FracFocus.org

### Test Information:

Date: 06/08/2016 Hours: 24 Bbl oil: 377 Mcf Gas: 518 Bbl H2O: 460  
Calculated 24 hour rate: Bbl oil: 377 Mcf Gas: 518 Bbl H2O: 460 GOR: 1374  
Test Method: FLOWING Casing PSI: 1850 Tubing PSI: Choke Size: 14/64  
Gas Disposition: SOLD Gas Type: WET Btu Gas: 1382 API Gravity Oil: 54  
Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:  
Reason for Non-Production:  
Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt  
\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

Comment:

7.5% HCL acid was used in a plug and perf operation for this well.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: ILA BEALE  
Title: STAFF REG. SPECIALIST Date: Email: ila.beale@anadarko.com

## Attachment Check List

Att Doc Num Name

Total Attach: 0 Files

### General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>

Total: 0 comment(s)