Schlumberger

Client: BHP BILLITON WP
Well: 6406/3-2 ANTARES
Field: ANTARES
Rig: SEDCO 704

Country: Norway
Province: Norwegian Sea
County: Offshore
Location: Block 6406/3

Permanent Datum: MEAN SEA LEVEL
Elevation: 0 m
Log Measured From: RT
Drilling Measured From: RT
Elevation: 25 m
Above Permanent Datum

Date: 20-Oct-2009
Run Number: ONE
Depth Driller: 3470 m
Depth Logger: 3470 m
Bottom Logged Interval: 3470 m
Top Logged Interval: 3000 m
Casing Driller: 3000 m @ 3000 m
Casing Logger: 3000 m @ 3000 m
Bit Size: 8.5 in
Type Fluid in Hole: WBM
Density: 1.25 g/cm³
Viscosity: 0.0 s
PH: 0.0
Fluid Loss: 0.0 cm³
Source of Sample: FLOWLINE
Rm @ Measured Temp: 0.0 ohmm @ 0 °C
Rmf @ Measured Temp: 0.0 ohmm @ 0 °C
Rmc @ Measured Temp: 0.0 ohmm @ 0 °C
Source of Rmf / Rmc: MEASURED / CALCULATED
Rm @ BHT: 0.0 ohmm @ 0 °C
Time Since Circulation: 0.0 hr
Max Rec Temp: 0 °C
Equipment / Base: 0704
Recorded By: SCHLUMBERGER
Witnessed By: BHP BILLITON

Gamma Ray (GR) (GAPI) 0 150
Caliper (CALI) (in) 6 16
Bit Size (BS) (in) 6 16
Deep Resistivity (RDEP) (ohmm) 0.2 2000
Medium Resistivity (RMED) (ohmm) 0.2 2000
Shallow Resistivity (RSHA) (ohmm) 0.2 2000
Density Correction (DRHO) (g/cm³) -0.25 0.25
Neutron Porosity (NPHI) (m³/m³) 0.45 -0.15
Photoelectric Factor (PEF) (b/e) 0 10
Bulk Density (RHOB) (g/cm³) 1.95 2.95
Delta-T (DT) (µs/ft) 140 40

Run 1 - 3000 - 3470 m - 20-Oct-2009

Gamma Ray (GR) (GAPI) 0 150
Caliper (CALI) (in) 6 16
Bit Size (BS) (in) 6 16

Run 1 - 3000 - 3470 m - 20-Oct-2009

All measurements are recorded in relation to the Kelly Bushing (KB) unless otherwise noted. Logging speed will be adjusted for optimum data acquisition conditions. Data is recorded at a sampling interval of 0.1524 m. Data is recorded at a sampling interval of 0.1524 m. Data is recorded at a sampling interval of 0.1524 m