



# Kerr-McGee Oil & Gas Onshore LP

A subsidiary of Anadarko Petroleum Corporation

1099 18<sup>th</sup> Street  
Denver, CO 80202  
720-929-6000

December 27, 2016

Matt Lepore  
Director, Colorado Oil and Gas Conservation Commission  
Department of Natural Resources  
The Chancery Building  
1120 Lincoln Street, Suite 801  
Denver, CO 80203

Re: Request for Exception to Rule 317.p  
NEWBY 27N-33HZ PAD – DOC # 401162609  
NEWBY 28N-33HZ – DOC # 401162587  
NEWBY STATE 36N-4HZ - DOC # 401162588  
NEWBY 2N-33HZ – DOC # 401162590  
NEWBY STATE 15N-4HZ – DOC # 401162591  
NEWBY 27N-33HZ – DOC # 401162593  
NEWBY STATE 37N-4HZ – DOC # 401162595  
NEWBY STATE 16N-4HZ – DOC # 401162598  
NEWBY 1N-33HZ – DOC # 401162599  
NEWBY STATE 26N-33HZ – DOC # 401162601  
NEWBY STATE 38N-4HZ – DOC # 401162602  
NEWBY STATE 30N-34HZ – DOC # 401162604  
NEWBY STATE 34N-3HZ – DOC # 401162606  
Township 3 North, Range 68 West  
Section 33: S2SE  
Weld County, Colorado

Dear Director Lepore:

Kerr-McGee Oil & Gas Onshore LP (“KMG”) respectfully requests approval for an exception to Rule 317.p to only run a cased-hole pulsed neutron, gamma-ray, and cement bond log from the kickoff point into the surface casing on one of the first wells drilled on this multi-well location. A Cement Bond Log with cased-hole gamma-ray log will be run on production casing or on intermediate casing if production liner is run. The other wells on this multi-well location will be logged with only a cement bond log with cased-hole gamma-ray log from kickoff point into the surface casing. Rule 317.p of the Colorado Oil and Gas Commission's Rules and Regulations requires wells to be logged with a minimum of a resistivity log with gamma ray. The above-named wells are requested to be exempt from this requirement due to the proximity of existing well(s) with acceptable resistivity logs with gamma ray. The available log(s) meet the offsetting well requirements and have a surface location within seven hundred fifty (750) feet of the proposed well(s).

One of the first wells drilled will be logged with a cased-hole pulsed neutron, gamma-ray, and cement bond log. The other wells on this multi-well location will run a cement bond and gamma ray log from the kickoff point into the surface casing. The Drilling Completion Report (Form 5) submitted for each well will indicate that no open-hole logs were run.

The existing well(s) within seven hundred and fifty feet (750) with acceptable resistivity logs with gamma ray are listed in the table below:

Well Name	Well Number	API Number	Distance From Well(s)	Azimuth (Degrees)	COGCC Well File Document Number	Type of Log
ADLER	15-33	05-123-30374	598	64	1542919, 1542920	DUAL INDUCTION GUARD LOG GAMMA RAY, COMPENSATED DENSITY COMPENSATED NEUTRON MICROLOG

Should you have any questions, please contact our office. Thank you for your consideration.

Sincerely,

**Kerr-McGee Oil & Gas Onshore LP**



Shayelyn Marshall  
Regulatory Analyst