



SRC ENERGY

Operator: SRC Energy
Well Name: Dupper #3
Legal: SENE, Section 27, Township 4N, Range 65W
Location: Weld County, CO
API: 05-123-12338
Surface: 8.625" 24# @ 311' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7183' **Hole Size:** 7.875" **TOC:** 6072 (CALC)
Perforations: 6,781' – 6,983' (Niobrara), 7,070' – 7,077' (Codell)
TD: 7,183'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and check surface annulus for pressure
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2", 11.6# retainer, set at 6,706' and squeeze perfs (50 sxs)
 - a. Release off of retainer and pump 5 sx on top to create 50' plug
 - b. TOOH
6. Pressure test csg to 500 psi for 15 minutes
7. TIH to 4275' and perforate casing. Establish injection
8. Circulate 30 sacks cement on the backside followed by 10 sacks of a balance plug over the perfs.
9. Cut 4.5" @ 321', and POOH
10. TIH to 371' and pump a 371' shoe plug (0' – 371')
 - a. 150 sx of 15.8# class G neat 1.15 cu./ft. yield cement, (371' – 0')
 - b. 60' out of surface casing
 - c. Wait 4 hours and tag plug
11. RDMO WO unit
12. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
13. Weld on cap with ID plate, inscribed with well location, and identity
14. Backfill, clean location
15. P&A complete