

LEGEND:

- └─┘ = 90° SYMBOL
- = PROPOSED WELLHEAD.
- = TARGET BOTTOM HOLE.
- ▲ = SECTION CORNERS LOCATED. (NAD 83)
- △ = SECTION CORNERS RE-ESTABLISHED. (Not Set on Ground.) (NAD 83)

T6S, R97W, 6th P.M.

1917 Brass Cap,
1.6' High, Steel
Post
Lat: 39.515732°
Long: 108.196743°

S89°58'04"E - 2635.63' (Meas.)

S89°47'16"E - 2635.29' (Meas.)

1917 Brass Cap,
1.0' High, Fence Corner
Lat: 39.515714°
Long: 108.178067°

1917 Brass Cap,
0.6' High
Lat: 39.515733°
Long: 108.187403°

23

1917 Brass Cap,
2.5' High
Lat: 39.508481°
Long: 108.178067°

1917 Brass Cap,
1.0' High
Lat: 39.501243°
Long: 108.196735°

S89°54'51"E - 2633.48' (Meas.)

Target Bottom Hole

1917 Brass Cap,
1.3' High, Steel
Post
Lat: 39.501239°
Long: 108.187406°

S89°56'54"E - 2638.99' (Meas.)

1917 Brass Cap,
0.6' High, Steel Post
Lat: 39.501239°
Long: 108.178056°

PUCKETT 21A-26-697

Elev. Graded Ground = 8396.3'

26

1917 Brass Cap,
2.0' High
Lat: 39.494008°
Long: 108.178056°

LINE TABLE

LINE	DIRECTION	LENGTH
L1	N89°38'09"W	2640.48'
L2	S89°56'16"W	2528.26'

S89°56'16"W
2633.86'
(Meas.)

N 1/4 Cor. Sec. 34,
True Position
Lat: 39.486769°
Long: 108.206092°

Section Corner
Re-Established
Using Double
Proportion Method
Lat: 39.486731°
Long: 108.196739°

N89°43'57"E - 2640.45' (Meas.)

N89°53'43"W - 2638.32' (Meas.)

S 1/4 Cor. Sec. 25,
1920 Brass Cap,
2.0' High
Lat: 39.486778°
Long: 108.168697°

S89°55'12"W
2638.32' (Meas.)

NW Cor. Sec. 34,
Section Corner
Re-Established
Using Double
Proportion Method
Lat: 39.486753°
Long: 108.215422°

105.60'
(G.L.O.)
N 1/4 Cor. Sec. 34,
W.C.
1917 Brass Cap,
2.2' High
Lat: 39.486769°
Long: 108.206467°

N00°05'12"W
1807.07' (Meas.)

SW Cor. Sec. 35,
1920 Brass Cap,
1.5' High
Lat: 39.481792°
Long: 108.196089°

1917 Brass Cap,
1.3' High
Lat: 39.486769°
Long: 108.187389°

Section Corner
Re-Established
Using Double
Proportion Method
Lat: 39.486764°
Long: 108.178042°

SW Cor. Sec. 36,
1920 Brass Cap,
0.9' High
Lat: 39.481786°
Long: 108.178033°

S00°01'47"E
1813.28' (Meas.)



NAD 83 (SURFACE LOCATION)	NAD 83 (TARGET BOTTOM HOLE)
LATITUDE = 39°29'56.09" (39.498914)	LATITUDE = 39°30'04.52" (39.501256)
LONGITUDE = 108°10'59.12" (108.183089)	LONGITUDE = 108°11'18.69" (108.188525)
NAD 27 (SURFACE LOCATION)	NAD 27 (TARGET BOTTOM HOLE)
LATITUDE = 39°29'56.16" (39.498933)	LATITUDE = 39°30'04.60" (39.501278)
LONGITUDE = 108°10'56.83" (108.182453)	LONGITUDE = 108°11'16.40" (108.187889)
UTM NAD 27 (ZONE 12)	UTM NAD 27 (ZONE 12)
N: 14356034.37 E: 2435293.00	N: 14356839.30 E: 2433732.70

PDOP = 1.2

CERTIFICATE

THIS IS TO CERTIFY THAT THE ABOVE PLAT WAS PREPARED FROM FIELD NOTES OF ACTUAL SURVEYS MADE BY ME OR UNDER MY SUPERVISION, AND THAT THE SAME ARE TRUE AND CORRECT TO THE BEST OF MY KNOWLEDGE AND BELIEF.

REGISTERED LAND SURVEYOR
REGISTRATION NO. 109130
STATE OF COLORADO

REV: 1 04-24-17 C.D.L. (BHL CHANGE)

BASIS OF BEARINGS

BASIS OF BEARINGS IS A G.P.S. OBSERVATION

BASIS OF ELEVATION

SPOT ELEVATION AT THE NORTHWEST CORNER OF SECTION 30, T5S, R95W, 6th P.M. TAKEN FROM THE FORKED GULCH QUADRANGLE, COLORADO, GARFIELD COUNTY, 7.5 MINUTE SERIES (TOPOGRAPHICAL MAP) PUBLISHED BY THE UNITED STATES DEPARTMENT OF THE INTERIOR, GEOLOGICAL SURVEY. SAID ELEVATION IS MARKED AS BEING 5966 FEET.



UELS, LLC
Corporate Office * 85 South 200 East
Vernal, UT 84078 * (435) 789-1017



Caerus Oil & Gas LLC

PUCKETT 21A-26-697
NW 1/4 NE 1/4, SECTION 26, T6S, R97W, 6th P.M.
GARFIELD COUNTY, COLORADO

SURVEYED BY	BART HUNTING, C.R.	08-29-16	SCALE
DRAWN BY	C.D.L.	08-30-16	1" = 1000'

WELL LOCATION PLAT