



SRC ENERGY

**Operator:** SRC Energy  
**Well Name:** Howard 15-27  
**Legal:** SWNE Section 27, Township 6N, Range 64W  
**Location:** Weld County, CO  
**API:** 05-123-14592  
**Surface:** 8.625" 24# @ 338'      **Hole Size:** 12.25"      **TOC:** Surface  
**Production:** 3.5" 9.3# @ 7033'      **Hole Size:** 7.875"      **TOC:** 6150' (CBL)  
**Perforations:** 6579' – 6870' (Nio-Codell)  
**TD:** 7042'

### P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and check surface annulus for pressure
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 3-1/2", 9.3# CIBP, set at 6,504', TOOH
6. Pressure test csg to 500psi for 15 minutes
7. Pump 8 sx on top of CIBP to create 150' plug
8. Cut 4.5" @ 850'
9. TIH to 900' and pump a 900' shoe plug (0' – 900')
  - a. 380 sx of 15.8# class G neat 1.15 cu./ft. yield cement, (900' – 0')
  - b. 562' out of surface casing
  - c. Wait 4 hours and tag plug
10. RDMO WO unit
11. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
12. Weld on cap with ID plate, inscribed with well location, and identity
13. Backfill, clean location
14. P&A complete