



SRC ENERGY

**Operator:** SRC Energy  
**Well Name:** State M 36-25  
**Legal:** NWSW, Section 36, Township 6N, Range 67W  
**Location:** Weld County, CO  
**API:** 05-123-23212  
**Surface:** 8.625" 24# @ 545' **Hole Size:** 12.25" **TOC:** Surface  
**Production:** 4.5" 11.6# @ 7,227' **Hole Size:** 7.875" **TOC:** 2,860' (CBL)  
**Perforations:** 6,768' – 6,918' (Niobrara), 7,088' – 7,106' (Codell)  
**TD:** 7,255'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH and tag existing CIBP w/ 2 sx on top (approximately 6692')
6. Pressure test casing to 500 psi for 15 minutes
7. Set 14 sx on top of existing CIBP (cover 200' above Niobrara top)
8. Cut 4.5" @ 900', and POOH
9. TIH to 950' and pump stub plug (0' – 950')
  - a. 362 sx of 15.8# class G neat 1.15 cu./ft. yield cement
  - b. 400' out of surface casing
  - c. Wait 4 hours and tag plug
10. RDMO WO unit
11. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
12. Weld on cap with ID plate, inscribed with well location, and identity
13. Backfill, clean location
14. P&A complete