



SRC ENERGY

Operator: SRC Energy
Well Name: Goetzel 20-34
Legal: SESW, Section 20, Township 6N, Range 66W
Location: Weld County, CO
API: 05-123-24964
Surface: 8.625" 24# @ 414' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7,265' **Hole Size:** 7.875" **TOC:** 80' (CBL)
Perforations: 7,122' – 7,141' (Codell)
TD: 7,270'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 11.6# CIBP, set at 7047'
6. Pressure test csg to 500 psi for 15 minutes
7. Set 43 sx on top of CIBP (cover 200' above Niobrara top)
8. TIH to 614' and pump casing plug (0' – 614')
 - a. 59 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. 200' out of surface casing
 - c. Wait 4 hours and tag plug
9. RDMO WO unit
10. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
11. Weld on cap with ID plate, inscribed with well location, and identity
12. Backfill, clean location
13. P&A complete