



SRC ENERGY

**Operator:** SRC Energy  
**Well Name:** Sena 15-24  
**Legal:** SENW, Section 15, Township 6N, Range 66W  
**Location:** Weld County, CO  
**API:** 05-123-26846  
**Surface:** 8.625" 24# @ 738'                      **Hole Size:** 12.25"                      **TOC:** Surface  
**Production:** 4.5" 11.6# @ 7,388'                      **Hole Size:** 7.875"                      **TOC:** 750' (CBL)  
**Perforations:** 6,944' – 7,090' (Niobrara), 7,237' – 7,254' (Codell)  
**TD:** 7,440'

#### P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2 11.6# CIBP, set at 6869'
6. Pressure test casing to 500 psi for 15 minutes
7. Set 16 sx on top of CIBP (cover 200' above Niobrara top)
8. TIH to 3,000' and set 48 sx creating balance plug (2,500'-3,000')
9. TIH to 725' and perforate casing
10. TIH w/ 4-1/2 11.6# CICR, set at 675'
  - a. Circulate 200 sx through CICR (725' annulus plug & 50' casing plug)
  - b. Sting out of CICR and pump 65 sx creating casing plug from 675' to surface
11. RDMO WO unit
12. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
13. Weld on cap with ID plate, inscribed with well location, and identity
14. Backfill, clean location
15. P&A complete