

Colorado Oil and Gas Conservation Commission  
 1136 Speer Blvd.  
 Denver 4, Colorado  
 OFFICE OF STATE OIL INSPECTOR  
 SUNDRY NOTICES AND REPORTS OF WELLS  
 LOCATED ON PRIVATE LANDS

2 approved copies  
 Returned 11-7-51  
 185-10

(Indicate nature of data by checking below)



- Notice of intention to drill X
- Notice of intention to change plans \_\_\_\_\_
- Notice of date for test of water shut-off \_\_\_\_\_
- Report on result of test of water shut-off \_\_\_\_\_
- Notice of intention to re-drill or repair well \_\_\_\_\_
- Notice of intention to clean out well \_\_\_\_\_
- Statement of shooting \_\_\_\_\_
- Statement of perforating \_\_\_\_\_
- Notice to pull or otherwise alter casing \_\_\_\_\_
- Notice of intention to abandon well \_\_\_\_\_
- Report of work done on well since previous report \_\_\_\_\_

Following is a (notice of intention to do work) (On land) November 2 19 51  
 (~~report of work done~~) (patented) described as follows:

Colorado Logan Yenter Pool  
State County Field

13 Yenter "B" NW/4 Sec. 3 T. 8 N. R. 54 W.  
 (Well No.) (Lease) (Sec. and 1/4 Sec.) (Twp.) (Range) (Meridian)

The well is located 990 ft. (N) of South Line and 330 ft. (E) of West Line  
Lot 9, Sec. 3

The elevation above sea level is 4406 ft. K.B. Estimated

Details of Plan of Work: (State names of and expected depths to objective sands: Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

To drill and test subject well to the "J" Sand of the Graneros Series.  
 SURFACE CASING: 9-5/8" Armco spiral weld to be set at approximately 200' and cemented with 160 sax. Cement to be circulated to ground surface.  
 PRODUCTION STRING CASING: 5 1/2" O.D., 15.5#, J-55 casing to be set through the oil producing section of the "J" Sand. Cement with 250 sax.  
 TESTING: 1.-No coring planned. 2.-DST "D" Sand if as high as Yenter #2 (-713').  
 3.-No DST planned for "J" Sand.  
 LOGGING: One-run Schlumberger electric log from under surface casing point to T.D. Run Micro-log on any indicated gas or oil zones.  
 DRIFT SURVEYS: At 50' intervals in surface hole and to a point 100' below surface casing, thereafter at 250' intervals.  
 DRILLING TIME: Use Geolograph.  
 SAMPLES: 10' intervals from 4200' to 5050' - 5' intervals from 5050' to T.D.  
 DEPTH MEASUREMENTS: S.L.M. of drill pipe at approximately 4000' and prior to DST and at T.D.  
 COMPLETION PROGRAM: Drill "J" Sand to a minus T.D. of 885'. Set and cement the oil string casing on bottom. Perforate for production.  
 ANTICIPATED FORMATION TOPS: Niobrara @ 4376' - Ft. Hays @ 4668' - Greenhorn @ 4891' - "D" Sand at 5149' - "J" Sand @ 5248'.

Approved: NOV 7 1951

Company British-American Oil Producing Company

[Signature]  
 State Oil Inspector  
 Director

Address P. O. Box 620 - Casper, Wyoming

By [Signature]  
 G. Wm. Evelyn, Jr.  
 Title District Superintendent

Submit reports of proposed work, for approval, on this form in Duplicate.