



SRC ENERGY

Operator: SRC Energy
Well Name: LHI 14-12
Legal: NWNE, Section 14, Township 4N, Range 67W
Location: Weld County, CO
API: 05-123-19971
Surface: 8.625" 24# @ 391' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7,330' **Hole Size:** 7.875" **TOC:** 260' (CBL)
Perforations: 7,155' – 7,175' (Codell)
TD: 7,340'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2 11.6# CIBP, set at 7,080'
6. Pressure test casing to 500 psi for 15 minutes
7. Run CBL, verify existing cement coverage
8. Set 41 sx on top of CIBP (cover 200' above Niobrara top)
9. TIH w/ 4-1/2 11.6# CIBP, set at 5,500'
 - a. Dump bail 2 sx on top of CIBP
10. TIH w/ 4-1/2 11.6# CIBP, set at 4,000'
 - a. Dump bail 2 sx on top of CIBP
11. TIH w/ 4-1/2 11.6# CIBP, set at 2,000'
 - a. Dump bail 2 sx on top of CIBP
12. Cut 4.5" @ 250', and POOH
13. TIH to 791' and pump stub plug (0' – 791')
 - a. 150 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. 400' out of surface casing
 - c. Wait 4 hours and tag plug
14. RDMO WO unit
15. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
16. Weld on cap with ID plate, inscribed with well location, and identity
17. Backfill, clean location



SRC ENERGY

18. P&A complete