



SRC ENERGY

Operator: Chandler & Associates LLC
Well Name: Yancey 1
Legal: NENE, Section 13, Township 6N, Range 67W
Location: Weld County, CO
API: 05-123-05227
Surface: 10.75" 40# @ 360' **Hole Size:** 13.75" **TOC:** Surface
Production: N/A **Hole Size:** 8.75" (360'-7,731'), 7.875" (7,731'-9,151')
TD: 9,151'

P&A Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Dig out to find wellhead and check pressure
3. Cut cap off, extend surface pipe to achieve ground level
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe to be ran in well
5. Mill cement, cement btm is approximately 360' according to historical well data
6. Wash run to depth that well allows
7. TOOH, remove BHA for milling
8. TIH to 4,000' based off of pipe tally and pump a 500' open hole plug
 - a. 227 sx of 15.8# class G neat 1.15 cu/ft yield cement (3,500'-4,000')
 - b. Wait 4 hours and tag plug
9. TIH to 2,250' based off of pipe tally and pump a 250' open hole plug
 - a. 114 sx of 15.8# class G neat 1.15 cu/ft yield cement (2,000'-2,250')
 - b. Wait 4 hours and tag plug
10. TIH to 860' based off of pipe tally and pump a 860' surface plug
 - a. 417 sx of 15.8# class G neat 1.15 cu/ft yield cement (0'-860')
 - b. Wait 4 hours and tag plug
11. RDMO WO unit
12. Remove extension of surface pipe. Top off if necessary.
13. Weld on cap with ID plate, inscribed with well location, and identity
14. Backfill, clean location
15. P&A complete

*Assumed Data