










































gyrodata
REPEAT RUN - Run with X PP
Survey Date: 8-Jul-2021
Survey Type: Repeat
Survey Company: Gyrodata
Job Number: 21GYR0001
Client: Chevron
Well Name: Jack 3
Field Name: Jack
Rig Name: Transocean Development Driller III
Rig Type: Semi-Submersible
Surface Coordinates: 28° 11' 31.5" N 95° 58' 23.5" W
Declination: 6.50° E
Grid Convention: True North
Vertical Section Azimuth: 0.00°
Vertical Section Origin: 0.00 ft, 0.00 ft
Survey Depth Range: 0.00 ft to 30,000.00 ft
Survey Interval: 30.00 ft
Survey Tool Type: Gyro
Survey Direction: Outward
Survey Tool Name: GyroSphere HDGM
Survey Tool Number: 5-1/2" 1.75 ID
Survey Tool Error Model: ISCWSA Rev 4
Survey Tool Error Profile: Gyro
Survey Tool Error Coefficients: Standard
Survey Tool Error Coefficients: Standard
Survey Tool Error Coefficients: Standard



Calibration Report

Database File	d:\warrior\data\20180116_extraction_jesser 3e-10-11n_cbl\20180116_extraction_jesser 3e-10-11n_cbl.db
Dataset Pathname	Main.2
Dataset Creation	Tue Jan 16 12:14:54 2018

Gamma Ray Calibration Report

Serial Number:	ISHV2-03	
Tool Model:	2 3/4" TekCo	
Performed:	Tue Dec 13 00:23:06 2016	
Calibrator Value:	194.0	GAPI
Background Reading:	58.9	cps
Calibrator Reading:	300.8	cps
Sensitivity:	0.8020	GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	IPPO2-01	
Tool Model:	2 3/4" RIB Analog	
Calibration Casing Diameter:	5.500	in
Calibration Depth:	0.000	ft

Master Calibration, performed (Derived):

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.003	1.247	0.000	72.000	57.854	-0.153
CAL	0.000	0.750				
5'	-0.005	1.775	0.000	72.000	40.431	0.216
SUM						
S1	0.027	1.166	0.000	72.000	63.228	-1.707
S2	0.027	1.132	0.000	72.000	65.142	-1.759
S3	0.031	1.167	0.000	72.000	63.345	-1.947
S4	0.034	1.082	0.000	72.000	68.750	-2.370
S5	0.029	1.067	0.000	72.000	69.383	-2.004
S6	0.027	1.064	0.000	72.000	69.441	-1.891
S7	0.027	1.145	0.000	72.000	64.435	-1.750
S8	0.027	1.158	0.000	72.000	63.615	-1.694

Internal Reference Calibration, performed Fri Aug 25 16:15:12 2017:

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.750	0.000	0.750	1.000	0.000

Air Zero Calibration, performed Fri Aug 25 16:15:12 2017:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Temperature Calibration Report

Serial Number:	IPPO2-01			
Tool Model:	2 3/4" RIB Analog			
Performed:	Fri Aug 26 11:07:15 2016			
	Reference		Reading	
Low Reference:	0.00	degF	0.00	usec
High Reference:	1.00	degF	1.00	usec
Gain:	0.33			
Offset:	0.00			
Delta Spacing	1			

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb
			CableHead-TitanConeType2	1.03	1.44	3.60
CCL	13.50		CCL_Log-2 3/4" TekCo (IS2T1-09)	1.83	2.75	33.00
			Antelope-Overbody	1.25	2.75	
TEMP	10.05					
WVFS8	8.76					
WVFS7	8.76					
WVFS6	8.76					
WVFS5	8.76					
WVFS4	8.76					
WVFS3	8.76					
WVFS2	8.76					
WVFS1	8.76					
WVF3FT	8.01					
WVF5FT	7.01		RBTA-2 3/4" RIB Analog (IPPO2-01)	9.13	2.75	102.00
WVFSYNC	3.68					
WVFTEMP	3.68					
WVFCAL	3.68					
			Antelope-Overbody	1.25	2.75	
			GR_Log-2 3/4" TekCo (ISHV2-03)	3.68	2.75	47.00
GR	1.04					
LOCTIM	0.00					
UTCTIM	0.00					

Dataset:	20180116_extraction_jesser 3e-10-11n_cbl.db: field/well/run1/Main.2
Total length:	15.67 ft
Total weight:	185.60 lb
O.D.:	2.75 in

gyrodata

Company	Extraction Oil and Gas		
Well	Jesser 3E-10-11N		
Field	Wattenberg		
County	Weld		
State	Colorado	Country	U.S.A.