



Service Order #: 70204

Date: 07-Apr-18

| Well Name | Location | County | St | API# | | |
|---------------|------------|-----------------|-----------|-----------------|------|-----|
| WEYERMAN 6-18 | | YUMA | CO | 05-125-09027-00 | | |
| Formation | Cement Via | Type Of Service | Well Type | Age | AFE# | PO# |
| | CASING | PLUG | | REWORK | | |

Customer: PRIME OPERATING CO.

Remarks: SAFETY MEETING
64 SKS, 13 BBLS
ANNULUS 331'- 0'
CASING 340' -0'

Customer Rep: TOM

PH:

| WELLBORE DATA | | | | |
|--------------------|-------|--------|-------|--------|
| Type | Size | Weight | Depth | Volume |
| Surface Casing: | 7.000 | 17.0 | 281.0 | |
| Production Casing: | 4.500 | 10.5 | 340.0 | |
| Intermediate: | | | | |
| Drill Pipe: | | | | |
| Tubing: | | | | |

| Type | Size | Depth (Top) | Depth (Bot) | Volume |
|------------|-------|-------------|-------------|--------|
| Liner: | | | | |
| Open Hole: | 6.250 | 281.0 | 331.0 | |

| OTHER DATA | | |
|------------|---------|-------------|
| BHT | Max PSI | Total Depth |
| | | |

Packer or RetainerType / Depth:

| | |
|------|-------|
| CIBP | 340.0 |
|------|-------|

| Perf Depths: | | # | Total |
|--------------|-------|---|-------|
| 330.0 | 331.0 | 0 | 0 |
| | | 0 | |
| | | 0 | |

| TIME | PUMP RATES | | DENSITY | PRESS | STG TOT | TOTAL | REMARKS |
|------|-------------|------------|----------|-------|---------|--------|------------------------|
| | WATER (gpm) | PUMP (bpm) | (lb/gal) | (psi) | (bbls) | (bbls) | |
| 9:07 | 0 | 0.0 | 6.88 | 0 | 0.0 | 0.0 | PSI TEST |
| 9:07 | 0 | 0.0 | 6.88 | 13 | 0.0 | 0.0 | H2O SPACER |
| 9:13 | 0 | 0.5 | 16.01 | 19 | 2.8 | 2.8 | START CMT |
| 9:22 | 0 | 0.0 | 16.08 | 57 | 13.0 | 15.8 | CMT TO SURFACE OFFLINE |
| 9:22 | 109 | 0.0 | 13.76 | 25 | 13.0 | 15.8 | Paused 09:22:37 |

Summary

| | | | |
|--------------|--------------|---------|---------|
| Max Fl. Rate | Avg Fl. Rate | Max Psi | Avg Psi |
| 0.5 | 0.7 | 1,615 | 30 |

Customer Acknowledgement:

Service Rating:

- ☐ Satisfactory
☐ Unsatisfactory

Cementer:

S. BOHLEN

PRODUCTS USED

CLASS G CMT, 1.15 YEILD, 15.8 LBS/GAL