



DAILY DRILLING REPORT

RECEIVED

MAR 3 1978

COLO. OIL & GAS CONS. COMM.

NAME OF WELL: KISSINGER - ROSE 11-12X
LOCATION: NW/4 SW/4 SECTION 12-T 20S-R 50W, KIOWA CO., COLORADO
OPERATOR: KISSINGER PETROLEUM CORPORATION
CONTRACTOR: SNYDER DRILLING COMPANY
ELEVATIONS: GL 4356' KB TD 5550'
-2-

1-27-78 3446', Drilling, Mud: 9.4, Visc 44, LCM 10#/bbl
1-28-78 3560', Drilling, Mud: 9.0, Visc 33, LCM 6#/bbl
1-29-78 3820', Drilling, Mud: 9.2, Visc 36, LCM 8#/bbl
1-30-78 4036', Drilling, Mud: 9.2, Visc 41, LCM 8#/bbl
1-31-78 4285', Drilling, Circ up and had drlg break from 4201-4208.
Mud: 9.2, Visc 42, WL 14, LCM 7#/bbl
2-1-78 4560', Drilling, Mud: 9.3, Visc 43, WL 13, LCM 8#/bbl
2-2-78 4850', Drilling, Mud: 9.3, Visc 42, WL 10, LCM 6#/bbl
2-3-78 5138', Drilling, Survey: 1° at 5100', Mud: 9.3, Visc 43, WL
10, LCM 8#/bbl
2-4-78 5410', Drilling, Mud: 9.3, Visc 43, WL 10, LCM 8#/bbl
2-5-78 TD 5550', Logging.
2-6-78 TD 5550', Prep to P & A well. Ran logs as follows: I-ES,
GRN w/cal.
2-7-78 TD 5550', WELL PLUGGED AND ABANDONED.
LOG TOPS: KB 4363
DAKOTA 800 CHEROKEE 4495
BLAINE 2057 ATOKA 4690
STONE CORRAL 2320 MORROW SHALE 5082 (-719)
TOPEKA 3670 KEYES 5275
LANSING 3860 MISS 5350
MARMATON 4350 LOGGERS TD 5550
The Morrow-McClave sand was not present. Logs calculate
100% SW throughout.
Plugged well as follows: 25 sx Btm of Sfc
10 sx Top of Sfc
(Release date of rig to be reported later)

RECEIVED

MAR 3 1978

DAILY DRILLING REPORT

COLD. OIL & GAS CONS. COMM.

NAME OF WELL: KISSINGER - ROSE 11-12X
LOCATION: NW/4 SW/4 SECTION 12-T 20S-R 50W, KIOWA CO., COLORADO
OPERATOR: KISSINGER PETROLEUM CORPORATION
CONTRACTOR: SNYDER DRILLING COMPANY
ELEVATIONS: GL 4356' KB 4363' TD 5550'

2-8-78

TD 5550'. WELL PLUGGED AND ABANDONED.
Rig released 10 PM 2-5-78. P & A Complete.
FINAL REPORT.

RECEIVED

MAR 3 1978

DAILY DRILLING REPORT

COLO. OIL & GAS CONS. COMM.

NAME OF WELL: KISSINGER - ROSE 11-12X
LOCATION: NW/4 SW/4 SECTION 12-T 20S-R 50W, KIOWA CO., COLORADO
OPERATOR: KISSINGER PETROLEUM CORPORATION
CONTRACTOR: SNYDER DRILLING COMPANY
ELEVATIONS: GL 4356' KB TD 5550'

1-14-78 Moving rig to this loc; replacement well for Rose 11-12.

1-15-78 68', Spudded 1-14-78. Drld 68' 17-1/4" hole. Ran and cem 2 jts (62') 13-3/8" csg at 68' w/85 sx Class "H", 3% CaCl₂. Plug down 10 PM 1-14-78.

1-16-78 781', Drilling.

1-17-78 1158', Tripping, Survey: 1^O at 1158'. Spud time 3:45 PM 1-14. Mud: Visc 38, LCM 10#

1-18-78 1320', Losing circ. Lost circ at 1320' at 11 AM. Hole stdg full at this time; prep to try and drill ahead. Mud: Visc 36, LCM 20#

1-19-78 1630', Drilling, Mud: 9.0, Visc 40, 16# LCM

1-20-78 1940', Drilling, Mud: 9, Visc 39, 16# LCM

1-21-78 2206', Drilling, Drld ahead while WO cement trucks to set sfc csg. Mud: 9.1, Visc 36

1-22-78 2300', Down for repairs. Ran and cem 317' 24# 8-5/8" csg at 327' KB w/325 sx Class "H" containing 3% CaCl₂. Plug down 4:45 PM 1-21-78. Mud: 9.0, Visc 36, LCM 10#

1-23-78 2325', Drilling, Changed drawworks motor. Mud: 8.9, Visc 30, LCM 3#

1-24-78 2660', Drilling. Mud: 9.0, Visc 35, LCM 8#/bbl

1-25-78 2924', Drilling, Mud: 9.0, Visc 38, LCM 8#/bbl

1-26-78 3227', Drilling, Mud: 9, Visc 33, LCM 6#/bbl

RECEIVED

MAR 3 1978

DAILY DRILLING REPORT

COLO. OIL & GAS CONS. COMM.

NAME OF WELL: KISSINGER - ROSE 11-12X
LOCATION: NW/4 SW/4 SECTION 12-T 20S-R 50W, KIOWA CO., COLORADO
OPERATOR: KISSINGER PETROLEUM CORPORATION
CONTRACTOR: SNYDER DRILLING COMPANY
ELEVATIONS: GL 4356' KB TD 5550'

1-14-78 Moving rig to this loc; replacement well for Rose 11-12.

1-15-78 68', Spudded 1-14-78. Drld 68' 17-1/4" hole. Ran and cem 2 jts (62') 13-3/8" csg at 68' w/85 sx Class "H", 3% CaCl₂. Plug down 10 PM 1-14-78.

1-16-78 781', Drilling.

1-17-78 1158', Tripping, Survey: 1⁰ at 1158'. Spud time 3:45 PM 1-14. Mud: Visc 38, LCM 10#

1-18-78 1320', Losing circ. Lost circ at 1320' at 11 AM. Hole stdg full at this time; prep to try and drill ahead. Mud: Visc 36, LCM 20#

1-19-78 1630', Drilling, Mud: 9.0, Visc 40, 16# LCM

1-20-78 1940', Drilling, Mud: 9, Visc 39, 16# LCM

1-21-78 2206', Drilling, Drld ahead while WO cement trucks to set sfc csg. Mud: 9.1, Visc 36

1-22-78 2300', Down for repairs. Ran and cem 317' 24# 8-5/8" csg at 327' KB w/325 sx Class "H" containing 3% CaCl₂. Plug down 4:45 PM 1-21-78. Mud: 9.0, Visc 36, LCM 10#

1-23-78 2325', Drilling, Changed drawworks motor. Mud: 8.9, Visc 30, LCM 3#

1-24-78 2660', Drilling. Mud: 9.0, Visc 35, LCM 8#/bbl

1-25-78 2924', Drilling, Mud: 9.0, Visc 38, LCM 8#/bbl

1-26-78 3227', Drilling, Mud: 9, Visc 33, LCM 6#/bbl

RECEIVED

MAR 3 1978

DAILY DRILLING REPORT

GOLD. OIL & GAS CONS. COMM.

NAME OF WELL: KISSINGER - ROSE 11-12X
 LOCATION: NW/4 SW/4 SECTION 12-T 20S-R 50W, KIOWA CO., COLORADO
 OPERATOR: KISSINGER PETROLEUM CORPORATION
 CONTRACTOR: SNYDER DRILLING COMPANY
 ELEVATIONS: GL 4356' KB TD 5550'

-2-

1-27-78 3446', Drilling, Mud: 9.4, Visc 44, LCM 10#/bbl
 1-28-78 3560', Drilling, Mud: 9.0, Visc 33, LCM 6#/bbl
 1-29-78 3820', Drilling, Mud: 9.2, Visc 36, LCM 8#/bbl
 1-30-78 4036', Drilling, Mud: 9.2, Visc 41, LCM 8#/bbl
 1-31-78 4285', Drilling, Circ up and had drlg break from 4201-4208.
 Mud: 9.2, Visc 42, WL 14, LCM 7#/bbl
 2-1-78 4560', Drilling, Mud: 9.3, Visc 43, WL 13, LCM 8#/bbl
 2-2-78 4850', Drilling, Mud: 9.3, Visc 42, WL 10, LCM 6#/bbl
 2-3-78 5138', Drilling, Survey: 1° at 5100', Mud: 9.3, Visc 43, WL
 10, LCM 8#/bbl
 2-4-78 5410', Drilling, Mud: 9.3, Visc 43, WL 10, LCM 8#/bbl
 2-5-78 TD 5550', Logging.
 2-6-78 TD 5550', Prep to P & A well. Ran logs as follows: I-ES,
 GRN w/cal.
 2-7-78 TD 5550', WELL PLUGGED AND ABANDONED.
 LOG TOPS: KB 4363

DAKOTA	800	CHEROKEE	4495
BLAINE	2057	ATOKA	4690
STONE CORRAL	2320	MORROW SHALE	5082 (-719)
TOPEKA	3670	KEYES	5275
LANSING	3860	MISS	5350
MARMATON	4350	LOGGERS TD	5550

The Morrow-McClave sand was not present. Logs calculate
 100% SW throughout.
 Plugged well as follows: 25 sx Btm of Sfc
 10 sx Top of Sfc
 (Release date of rig to be reported later)

RECEIVED

MAR 3 1978

DAILY DRILLING REPORT

COLORADO OIL & GAS CONS. COMM.

NAME OF WELL: KISSINGER - ROSE 11-12X
LOCATION: NW/4 SW/4 SECTION 12-T 20S-R 50W, KIOWA CO., COLORADO
OPERATOR: KISSINGER PETROLEUM CORPORATION
CONTRACTOR: SNYDER DRILLING COMPANY
ELEVATIONS: GL 4356' KB 4363' TD 5550'

2-8-78

TD 5550'. WELL PLUGGED AND ABANDONED.
Rig released 10 PM 2-5-78. P & A Complete.
FINAL REPORT.