

COLORADO OIL AND GAS CONSERVATION COMMISSION
SUNDRY NOTICES AND REPORTS OF WELLS



00251999

RECEIVED
SEP 26 1952

OIL & GAS
CONSERVATION COMMISSION

333-1

(Indicate nature of data by checking below)

- Notice of intention to drill X
- Notice of intention to change plans _____
- Notice of date for test of water shut-off _____
- Report on result of test of water shut-off _____
- Notice of intention to re-drill or repair well _____
- Notice of intention to clean out well _____
- Statement of shooting _____
- Statement of perforating _____
- Notice to pull or otherwise alter casing _____
- Notice of intention to abandon well _____
- Report of work done on well since previous report _____

Following is a (notice of intention to do work) September 25, 19 52
(~~report of work done~~) (On land)
(~~patented~~) described as follows:

<u>Colorado</u>	<u>Logan</u>	<u>Dale</u>	<u>Field</u>
State	County		
<u>2A</u>	<u>J. Knifton "A"</u>	<u>NW/4 23</u>	<u>8N</u>
(Well No.)	(Lease)	(Sec. and $\frac{1}{4}$ Sec.)	(Twp.)
			<u>53W</u>
			(Range)
			(Meridian)

The well is located 950 ft. (N) of N. Line and 987 ft. (E) of W Line
(S) of NW/4 Section 23-8N-53W.

The elevation above sea level is * ft. *To be reported later.

Details of Plan of Work: (State names of and expected depths to objective sands: Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cementing points, and all other important proposed work.)

We propose to drill the captioned well to an approximate depth of 4900 feet to further evaluate the 'Muddy' and Dakota sandstone underlying the Dale Field.

6 5/8" casing will be set at approximately 600 feet and cemented to the surface.

4 1/2" casing will be cemented at approximately 4900 and perforated the 'Muddy' and/or Dakota sandstone if commercial production is encountered. We will acid treat and/or hydrafrac the productive interval if necessary.

Estimated formation tops:
'Muddy' 4645
Dakota 4755