



| | | | |
|--|----|--|--|
| | | | |
| | | | |
| | 28 | | |
| | | | |

Locate
Well
CorrectlyOIL & GAS
CONSERVATION COMMISSIONFile in _____ on Fee and Patented lands and in
quadr. _____ on State and School lands, with

OFFICE OF DIRECTOR

OIL AND GAS CONSERVATION COMMISSION,
STATE OF COLORADO

00217133

LOG OF OIL AND GAS WELL

Field South Springdale Company Ginther, Warren & Ginther
County Logan Address Box 769, Sterling, Colorado
Lease Dollerschell
Well No. 1 Sec. 28 Twp. 8 N Rge. 53W Meridian 6th State or Pat. Pat.

Location 335 Ft. (N) of N Line and 1016 Ft. (E) of W line of SW 1/4 Elevation 4159
2310-5 990-W (Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Signed

RA WarrenDate Nov. 25, 1953Title Superintendent

The summary on this page is for the condition of the well as above date.

Commenced drilling Sept. 24, 1953 Finished drilling Oct. 2 1953

OIL AND GAS SANDS OR ZONES

"D" No. 1, from 4770 to 4807 Barren No. 4, from _____ to _____
"J" No. 2, from 4867 to 4886 Oil No. 5, from _____ to _____
No. 3, from _____ to _____ No. 6, from _____ to _____

IMPORTANT WATER BANDS

No. 1, from _____ to _____ No. 3, from _____ to _____
No. 2, from _____ to _____ No. 4, from _____ to _____

CASING RECORD

| SIZE | WT. PER FOOT | MAKE | WHERE LANDED | NO. OF SKS. CEMENT | STOOD HOURS | PRESSURE TEST PSI |
|---------|--------------|----------|--------------|--------------------|-------------|-------------------|
| 10-3/4" | 32.75 | Spang | 324 | 160 | 24 | |
| 7" O.D. | 20 | National | 4880 | 175 | 72 | |
| | | | | | | |
| | | | | | | |

COMPLETION DATA

Total Depth 4886 ft. Cable Tools from _____ to _____ Rotary Tools from 0 to T.D.
Casing Perforations (prod. depth) from _____ to _____ ft. No. of holes None
Acidized with _____ gallons. Other physical or chemical treatment of well to induce flow None
Shooting Record Open hole completion 4880-86

Prod. began Nov. 1, 1953 Making 70 bbls./day of 40.8 A. P. I. Gravity Fluid on _____ Pump ☒
Tub. Pres. 20 lbs./sq. in. Csg. Pres. 160 lbs./sq. in. Gas Vol. 25 Mcf. Gas Oil Ratio 360
Length Stroke 44 in. Strokes per Min. 13 Diam. Pump 1 1/2 in.
B. S. & W. 3 % Gas Gravity Not known BTU's/Mcf. Not known Gals. Gasoline/Mcf. Not known

WELL DATA

Indicate (yes or no) whether or not the following information was obtained.

Electrical Log Yes Date Oct. 2, 1953 Straight Hole Survey Yes Type Totco
Date _____ 19____ Other Types of Hole Survey Temp Type Amerada
Time Drilling Record Geolograph
Core Analysis Yes Depth 4877 to 4879
4882 to 4886 (Note—Any additional data can be shown on reverse side.)

FORMATION RECORD

Show all formations, especially all sands and character and contents thereof.

| FORMATION | TOP | BOTTOM | REMARKS |
|----------------|------|---------------------------------|---------|
| Pierre Sh. | 335 | 3965 | |
| Niobrara Sh. | 3965 | | |
| Greenhorn L.S. | 4417 | | |
| "D" Sand | 4770 | 4807 | |
| "J" Sand | 4876 | T.D. (Continue on reverse side) | |