



SRC ENERGY

Operator: SRC Energy
Well Name: LHI 14-43
Legal: SWSE, Section 14, Township 4N, Range 67W
Location: Weld County, CO
API: 05-123-19810
Surface: 8.625" 24# @ 392' **Hole Size:** 12.25" **TOC:** Surface
Production: 4.5" 11.6# @ 7,435' **Hole Size:** 7.875" **TOC:** 392' (Reported-CBL)
Perforations: 7,225' – 7,245' (Codell)
TD: 7,436'

P&R Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 11.6# CIBP, set at 7,150'
6. Pressure test casing to 500 psi for 15 minutes
7. Set 33 sx on top of existing CIBP (cover 200' above Niobrara top)
8. Run CBL in thru surface pipe. Perf 4.5" casing at approx. 385' (post CBL Review)
9. TIH to 385' and pump balance plug (0' – 385')
 - a. 112 sx of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. trip out of surface casing
 - c. Wait 4 hours and tag plug
10. RDMO WO unit
11. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
12. Weld on cap with ID plate, inscribed with well location, and identity
13. Backfill, clean location
14. P&A complete