Log Variables





























































REPEAT PASS - Ran with 0 PSI

6 in / 100 ft

Database File 20190110_extraction_duck club 12w-20-6n_cbl20190110_extraction_duck club 12w-20-6n_cbl.db
Dataset Pathname pass2
Presentation Format rdx_9x
Dataset Creation Thu Jan 10 14:15:19 2019
Charted by Depth in Feet scaled 1:240



Calibration Report

Database File d:\warrior\data\20190110_extraction_duck club 12w-20-6n_cbl\20190110_extraction_duck club 12w-20-6n_c
Dataset Pathname pass3
Dataset Creation Thu Jan 10 14:23:26 2019

Gamma Ray Calibration Report

Serial Number:	ISHV2-02
Tool Model:	2 3/4" TeleCo
Performed:	Wed-Aug-22 11:07:35 2018
Calibrator Value:	194.0 GAPI
Background Reading:	53.6 cps
Calibrator Reading:	293.4 cps
Sensitivity:	0.8092 GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	ISF06-04
Tool Model:	2 3/4" RIB Analog
Calibration Casing Diameter:	5.500 in
Calibration Depth:	1125 ft

Master Calibration, performed (Derived)

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.003	1.499	0.000	72.000	48.126	-0.124
CAL	0.054	0.749				
5'	0.006	1.576	0.000	72.000	45.867	-0.269
SUM						
S1	0.024	1.591	0.000	72.000	45.951	-1.093
S2	0.027	1.585	0.000	72.000	46.076	-1.306
S3	0.027	1.520	0.000	72.000	48.018	-1.338
S4	0.023	1.494	0.000	72.000	48.927	-1.124
S5	0.016	1.443	0.000	72.000	50.453	-0.827
S6	0.015	1.467	0.000	72.000	49.603	-0.755
S7	0.022	1.498	0.000	72.000	48.771	-1.070
S8	0.023	1.498	0.000	72.000	48.784	-1.101

Internal Reference Calibration, performed (Not Performed)

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	-0.004	0.749	1.000	0.000

Air Zero Calibration, performed (Not Performed)

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Temperature Calibration Report

Serial Number:	ISF06-04
Tool Model:	2 3/4" RIB Analog
Performed:	Tue Jan 08 11:48:09 2019

	Reference	Reading	
Low Reference:	0.00	degF	0.00 usec
High Reference:	1.00	degF	1.00 usec
Gain:	0.33		
Offset:	0.00		
Delta Spacing	1		

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb)
			CableHead-TitanConeType2	1.03	1.44	3.60
CCL	13.50		CCL_Log-2 3/4" TeleCo (IPSN7-03)	1.83	2.75	33.00
			Antetype-Overbody	1.25	2.75	
TEMP	10.05					
WVF58	8.76					
WVF57	8.76		RBTA-2 3/4" RIB Analog (ISF06-04)	9.13	2.75	102.00
WVF56	8.76					
WVF55	8.76					
WVF54	8.76					
WVF53	8.76					
WVF52	8.76					
WVF51	8.76					
WVF5FT	8.01					
WVF5FT	7.01					
WVF3YNC	3.68					
WVFTEMP	3.68					
WVFCAL	3.68					
			Antetype-Overbody	1.25	2.75	
			GR_Log-2 3/4" TeleCo (ISHV2-02)	3.68	2.75	47.00
GR	1.04					
LOCTIM	0.00					
UTCTIM	0.00					
PMON	0.00					

Dataset 20190110_extraction_duck club 12w-20-6n_cbl.db: field/well/run1/pass3
Total length: 15.67 ft
Total weight: 185.60 lb
O.D.: 2.75 in

Company	Extraction Oil and Gas, Inc.
Well	12W-20-6N
Field	Wattenberg
County	Adams
State	Colorado
Country	U.S.A.