Schlumberger

Schlumberger, Platform Express, HRA - Quad Combo (TNPH-GR-DSI)

Well: 15/9-19 A
Field: Sleipner Vest
Structure: Utsira High
Location: Block 15/9
County: Norway
State: Offshore
Country: Norway
API Number: 15/9-19 A
Permanent Datum: Mean Sea Level
Elevation: 0 m
Log Measured From: Rotary Table
Drilling Measured From: Rotary Table

Run 1
Service Order: 7000000
Run Number: 1
Logging Date: 10-Jul-2008
Max Recorded Temperature: 0 degC
Bottom Driller's Depth: 1,250.0 m
Bottom Logger's Depth: 1,250.0 m
Casing Driller's Depth: 0.0 m
Casing Logger's Depth: 0.0 m
Bit Size: 8.5 in
Type Fluid in Hole: WBM
Density: 1.03 g/cm3
Viscosity: 0.0 s
PH: 0.0
Fluid Loss: 0.0 cm3
Source of Sample: Flowline
Rm @ Meas Temp: 0.0 ohmm @ 0 degC
Rmf @ Meas Temp: 0.0 ohmm @ 0 degC
Rmc @ Meas Temp: 0.0 ohmm @ 0 degC
Source of Rmf/Rmc: Measured
Rm @ BHT: 0.0 ohmm @ 0 degC
Time Since Circulation: 0.0 hr
Time on Bottom: 10-Jul-2008 00:00
Max Recorded Temperature: 0 degC
Equipment: 1302
Location: Sleipner

Run	Service Order	Bit Size (in)	Depth Driller (m)	Depth Logger (m)	Bottom Logged Interval (m)	Top Logged Interval (m)	Casing Driller (m)	Casing Logger (m)	Bottom Logged Interval (m)	Top Logged Interval (m)
1	7000000	8.5	1,250.0	1,250.0	1,250.0	0.0	0.0	0.0	0.0	0.0
2										
3										
4										
5										
6										
7										
8										

Gamma Ray (GR) 0 gAPI 150
Caliper (HCAL) 6 in 16
Bit Size (BS) 6 in 16
Deep Resistivity (HRDD) 0.2 ohmm 2000
Medium Resistivity (HRMD) 0.2 ohmm 2000
Shallow Resistivity (HRMS) 0.2 ohmm 2000
Neutron Porosity (HNPO) 0.45 v/v -0.15
Density Porosity (HDPO) 0.45 v/v -0.15
Bulk Density (HRHO) 1.95 g/cm3 2.95
Photoelectric Factor (HPEF) 0 b/e 10
Delta Rho (HDRH) -0.25 g/cm3 0.25






Gamma
0
150
ROP
0
100
Bottom Hole Temp
0
300
4600
4650
4700
4750
4800
4850
4900
4950
5000
5050
5100
5150
5200
5250
5300
5350
5400
5450
5500
5550
5600
5650
5700
5750
5800
5850
5900
5950
6000
6050
6100
6150
6200
6250
6300
6350
6400
6450
6500
6550