

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-21494.



01342179

NOTICE AND REPORTS ON WELLS

Use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	5. LEASE DESIGNATION AND SERIAL NO. Sec. 20-9N-78W
2. NAME OF OPERATOR Willis C. Walker	6. INDIAN, ALLOTTEE, OR TRIBE NAME
3. ADDRESS OF OPERATOR P. O. Box 681, Walden, Colorado	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' S/N & 660' W/ E line (NE/4 NE/4) Sec. 20-9N-78W	8. NAME OR LEASE NAME Angler Grant Hoge
14. PERMIT NO.	9. WELL NO. 2
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 8333' KB & 8323' G.L.	10. FIELD AND POOL, OR WILDCAT So. McCallum
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 20-9N-78W
	12. COUNTY OR PARISH Jackson
	13. STATE Colorado

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

X

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Plug and Abandon Well As Follows:

1. Place cement plug across perfs. from 5420' to 5700'.
2. Place 50' cement inside casing and 50' above casing.
3. Fill hole with mud.
4. Place 10 sack cement plug at top of surface pipe and erect proper marker.
5. 100' at base of surface casing, 50' in and 50' out.
6. Clean and level location.

DVR	
FJP	
HHM	✓
JAM	✓
JJD	✓

RECEIVED

FEB 11 1969

COLO. OIL & GAS CONS. COMM.

18. I hereby certify that the foregoing is true and correct

SIGNED

Willis C. Walker

(This space for Federal or State office use)

TITLE **Lessee**

DATE **8-30-67**

APPROVED BY

APPROVED

SEP 5 1967

RUDOLPH C. BAIER, JR.
ACTING DISTRICT ENGINEER

TITLE

DATE

*See Instructions on Reverse Side