



CONSERVATION COMMISSION OF NATURAL RESOURCES STATE OF COLORADO FEB 19 1987

File in duplicate for Patented and Federal lands. File in triplicate for State lands.

COLO. OIL & GAS COMMISSION

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL [] GAS WELL [X] OTHER []
2. NAME OF OPERATOR Powell Properties, Inc.
3. ADDRESS OF OPERATOR 95 Main St. Suite 10 Los Altos, California 94022
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 600' from South Line & 750' from West Line At proposed prod. zone Tract 38
14. PERMIT NO.
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3663 RKB

5. LEASE DESIGNATION AND SERIAL NO.
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME Holt B
9. WELL NO. 5R
10. FIELD AND POOL, OR WILDCAT Verde
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 1-35S-43W
12. COUNTY Baca
13. STATE Colorado

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF [] PULL OR ALTER CASING [] WATER SHUT-OFF [] REPAIRING WELL []
FRACTURE TREAT [] MULTIPLE COMPLETE [X] FRACTURE TREATMENT [] ALTERING CASING []
SHOOT OR ACIDIZE [] ABANDON [] SHOOTING OR ACIDIZING [] ABANDONMENT []
REPAIR WELL [] CHANGE PLANS [] (Other) []
(Other) [] (NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Date of work As soon as possible

Table with 6 columns: Casing, Weight, Depth Set, Hole size, Cement, Casing to pull. Row 1: 20", 48#, 47', 30", 100 sxs, None: Cemented top to bottom. Row 2: 4 1/2", 9.5#, 2982', 7 7/8", 800 sxs, None: Circulated cement top to bottom.

RECOMMENDED PLUGGING PROCEDURE:

PBTD: 2944' Perforations: 2756' to 2930'

Pump 30 sack cement plug with five sacks into perforations. Fill hole with 9# mud and put 10 sack plug in top. Cut off pipe 30" below ground and weld on plate. Fill hole and smooth location.

NOTE:

Baker R-3 tension packer hung at 2740'. We can pump thru this packer.

18. I hereby certify that the foregoing is true and correct

SIGNED William R. Braley TITLE Engineer DATE 2-16-87

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE SUPR. PETROLEUM ENGINEER DATE FEB 24 1987

CONDITIONS OF APPROVAL, IF ANY:

BEST IMAGE AVAILABLE

