

OIL AND GAS CONSERVATION COMMISSION
OF THE STATE OF COLORADO

PLUGGING RECORD

INSTRUCTIONS

Within thirty (30) days after the plugging of any well, the owner or operator thereof shall file this form in duplicate for wells on Patented or Federal lands, and in triplicate for wells on State lands, give a detailed account of the manner in which the abandonment or plugging work was carried out, including the nature and quantities of materials used in plugging and the location and extent (by depths) of the plugs of different materials; records of the amount, size and location (by depths) of casings and junk left in the well; and a detailed statement of the volume and weight of mud fluid used.

Operator HLM DRILLING COMPANY Field _____ Wildcat X
Lease Name Fluharty Well No. 1 County Logan
Location C SE NE Section 31 Township 10N Range 52W Meridian 6th
(Quarter Quarter)
1980 feet from N Section line and 660 feet from E Section Line
N or S E or W

TOTAL DEPTH 4930DATE OF PLUGGING Dec. 10, 1959*NO Prior approval*

DETAILS OF WORK

A. Halliburton wiper plug was placed at 180' and cemented with 15 sacks of cement. A second plug was placed at 20' and cemented with 10 sacks. The remainder of the surface pipe and hole below was filled with heavy drilling mud.

AJJ	
DVR	
WRS	
HHM	
JAM	
FJP	
JJD	<input checked="" type="checkbox"/>
FILE	

*Visited 6/1/60
appears OK*

I/we hereby swear (or affirm) that the statements herein made are a full and correct report:

Approved:

Date

DEC 17 1959Company HLM DRILLING COMPANYDate 12-16-59Address 504 Colorado BuildingPhone No. AM 6-3454

Director

By

D.C. Winslow

(Signature)

Title AGENT**VIOLATION****REMARKS.**