

Operator:	SRC Energy				
Well Name:	BOULTER #15-21				
Legal:	NENW 15 4N 66W				
Location:	Weld County, CO				
API:	05-123-16273				
Surface:	8.625" 23# @	390'	Hole Size: 12.25"	TOC: Surface	
Production:	4.5" 11.6# @	7312'	Hole Size: 7.875"	TOC: 3900' (CBL)	
Perforations:	7223 - 7236 CODELL		6913 - 7343 NIOBRARA		
TD:	7350				

P&R Procedure

1. Conduct pre-job safety meeting and complete daily JSA
2. Blow down well if necessary, circulate hole with treated water
3. Dig out around wellhead and perform bradenhead test
4. MIRU WO unit, ND wellhead, NU BOP, tally all pipe
5. TIH w/ 4-1/2" 11.6# CIBP on tubing, set at 6838'
6. Run CBL
7. Pressure test casing to 500 psi for 15 minutes
8. Set 15 sx on top of existing CIBP (200')
9. Spot 16 sx (200') plug with from 4057 - 4257
10. TIH w/perf gun to 2500' and perforate casing
11. TIH w/ 4-1/2" 11.6# CICR, set at 2400'
 - a. pump 84 sks of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. Release off of CICR and pump 9 sx (120' casing plug)
12. Cut 4.5" casing @ 809'
13. TIH with tubing to 859' and pump stub plug from 0 - 859'
 - a. pump 268 sks of 15.8# class G neat 1.15 cu./ft. yield cement
 - b. trip out of surface casing
 - c. Wait 4 hours and tag plug
14. RDMO WO unit
15. Dig up wellhead and cut off 10' below restored ground level, top off if necessary
16. Weld on cap with ID plate, inscribed with well location, and identity
17. Backfill, clean location
18. P&R complete