



UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
2. NAME OF OPERATOR
Quality Exploration, Inc.
3. ADDRESS OF OPERATOR
3545 E. 51st Street, Ste. 24 Tulsa, OK 74135
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL and 660' FSL Sec. 7
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Change Rigs

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED

NOV 8 1983

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

COLO. OIL & GAS CONS. COMM.

WRS	
FJP	
HRM	
JAM	
RCC	
LAR	
SCM	
ED	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface location measured and true vertical depths for all markers and zones pertinent to this work.)*

Well was spudded March 23, 1981. 8 5/8" surface casing was set at 320' with 150 sx Class G cement + 2% CaCl. Well now drilling at 620' in shale.

Request permission to release current rig and obtain larger rig (Denton Brothers) to finish hole. Larger rig available approximately May 15, 1981.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John McCatharn TITLE Agent DATE April 28, 1981
John McCatharn

(This space for Federal or State office use)

APPROVED BY Carl A. Barwick TITLE Acting Supervisor DATE 5-4-81
CONDITIONS OF APPROVAL, IF ANY:

Larger drilling rig, capable of drilling to TD. Must be drilling by midnight 5-15-81, or lease C-12014 will terminate.
*See Instructions on Reverse Side
Strand Junction