















































REPEAT PASS - Ran with Zero PSI

6 in / 100 ft

Database File	20190719_oop_prosper farms 4-65 11-12 3ah_ctk20190719_oop_prosper farms 4-65 11-12 3ah_ctd.db
Dataset Pathname	pass2.1
Presentation Format	ctd_8in
Dataset Creation	Fri Jul 19 15:21:42 2019
Charted by	Depth in Feet scaled 1:240



Calibration Report

Database File	d:\wamon\data\20190719_oop_prosper farms 4-65 11-12 3ah_ctd\20190719_oop_prosper farms 4-65 11-12
Dataset Pathname	pass3.1
Dataset Creation	Fri Jul 19 15:21:05 2019

Gamma Ray Calibration Report

Serial Number:	0XEM9-01
Tool Model:	2 3/4" TeleCo
Performed:	Thu Apr 25 11:23:51 2019
Calibrator Value:	194.0 GAPI
Background Reading:	52.3 cps
Calibrator Reading:	314.5 cps
Sensitivity:	0.7398 GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	IRB34-03
Tool Model:	2 3/4" RIB Analog
Calibration Casing Diameter:	5.500 in
Calibration Depth:	122.740 ft

Master Calibration, performed (Derived):

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	-0.002	1.240	0.000	71.921	57.908	0.118
CAL	-0.004	0.746				
5'	0.000	1.313	0.000	71.921	54.796	-0.007
SUM						
S1	0.007	1.301	0.000	72.000	55.631	-0.370
S2	0.006	1.371	0.000	72.000	52.511	-0.236
S3	0.006	1.378	0.000	72.000	52.466	-0.336
S4	0.005	1.426	0.000	72.000	50.618	-0.263
S5	0.006	1.472	0.000	72.000	49.106	-0.296
S6	0.006	1.469	0.000	72.000	49.209	-0.284
S7	0.006	1.447	0.000	72.000	49.953	-0.322
S8	0.007	1.395	0.000	72.000	51.872	-0.357

Internal Reference Calibration, performed (Not Performed):

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	-0.004	0.746	1.000	0.000

Air Zero Calibration, performed (Not Performed):

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Temperature Calibration Report

Serial Number:	IRB34-03
Tool Model:	2 3/4" RIB Analog
Performed:	Wed Jan 30 14:36:18 2019

	Reference	Reading	
Low Reference:	0.00	degF 0.00	usec
High Reference:	1.00	degF 1.00	usec
Gain:	0.33		
Offset:	0.00		
Delta Spacing	1		

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb)
			CableHead-TitanConeType2	1.03	1.44	3.60
CCL	13.50		CCL_Log-2 3/4" TeleCo (IS271-09)	1.83	2.75	33.00
			Antelope-Overbody	1.25	2.75	
TEMP	10.05					
WVFS8	8.76					
WVFS7	8.76					
WVFS6	8.76					
WVFS5	8.76		RBTA-2 3/4" RIB Analog (IRB34-03)	9.13	2.75	102.00
WVFS4	8.76					
WVFS3	8.76					
WVFS2	8.76					
WVFS1	8.76					
WVF3FT	8.01					
WVFSF1	7.01					
WVFSYNC	3.68					
WVFTEMP	3.68					
WVFCAL	3.68					
			Antelope-Overbody	1.25	2.75	
			GR_Log-2 3/4" TeleCo (IXEM9-01)	3.68	2.75	47.00
GR	1.04					
LOCTIM	0.00					
UTCTIM	0.00					

Dataset:	20190719_oop_prosper farms 4-65 11-12 3ah_ctd.db: field/well/run1/pass3.1
Total length:	15.67 ft
Total weight:	185.60 lb
O.D.:	2.75 in

Company	ConocoPhillips, Inc.
Well	Prosper Farms 4-65 11-12 3AH
Field	—
County	Arapahoe
State	Colorado
Country	U.S.A.