

KOLOA PAD
MULTI-WELL PLAN

NOTES:

1. THIS FIELD SURVEY CONFORMS TO THE MINIMUM STANDARDS SET BY THE COGCC, RULE NO. 215
2. ALL DISTANCES AND BEARINGS SHOWN HEREON ARE GROUND VALUES AS GPS MEASURED IN THE FIELD, WITH TIES TO WELLS MEASURED PERPENDICULAR TO LINES SHOWN HEREON. THIS LOW DISTORTION PROJECTION (LDP) IS BASED ON THE NORTH AMERICAN DATUM OF 1983, U.S. SURVEY FOOT WITH A LATITUDE ORIGIN OF 40.655085°N, A CENTRAL MERIDIAN LONGITUDE OF 104.086861°W, AND A SCALE FACTOR ON THE CENTRAL MERIDIAN OF 1.000232 (EXACT). THE LDP BASIS OF BEARINGS IS GEODETIC NORTH.
3. FIELD VERIFICATION OF MONUMENTS COMPLETED WITHIN 1 YEAR OF SIGNATURE DATE, UNLESS OTHERWISE NOTED.

NOTES:

- KL-1 TO BE AT 500' FNL & 2541' FWL.
BOTTOM HOLE AT 300' FSL & 2345' FWL, SEC. 22.
KOLOA 15-22-1HC TO BE AT 500' FNL & 2561' FWL.
BOTTOM HOLE AT 785' FNL & 305' FWL, SEC. 22.
KOLOA 15-22-2HN TO BE AT 500' FNL & 2581' FWL.
BOTTOM HOLE AT 300' FSL & 1330' FWL, SEC. 22.
KOLOA 15-22-3HN TO BE AT 500' FNL & 2601' FWL.
BOTTOM HOLE AT 300' FSL & 1990' FWL, SEC. 22.
KOLOA 15-22-4HN TO BE AT 500' FNL & 2621' FWL.
BOTTOM HOLE AT 300' FSL & 2630' FEL, SEC. 22.
KOLOA 15-22-5HN TO BE AT 500' FNL & 2641' FWL.
BOTTOM HOLE AT 300' FSL & 1990' FEL, SEC. 22.
KOLOA 15-22-6HC TO BE AT 500' FNL & 2661' FWL.
BOTTOM HOLE AT 300' FSL & 1475' FEL, SEC. 22.
KOLOA 15-22-7HN TO BE AT 500' FNL & 2681' FWL.
BOTTOM HOLE AT 300' FSL & 960' FEL, SEC. 22.
KOLOA 15-22-8HN TO BE AT 500' FNL & 2582' FEL.
BOTTOM HOLE AT 300' FSL & 305' FEL, SEC. 22.
KL-2 TO BE AT 500' FNL & 2562' FEL.
BOTTOM HOLE AT 300' FSL & 630' FEL, SEC. 22.

LEGEND

- = EXISTING MONUMENT ▲ = LANDING POINT
○ = CALCULATED POSITION ◆ = EXISTING WELL
● = PROPOSED WELL LP = LANDING POINT
◆ = BOTTOM HOLE BHL = BOTTOM HOLE

