
gyrodata
Log Variables
BOND INDEX
Variable Strength Curves
Log Variables
gyrodata
Log Variables
gyrodata
Log Variables


gyrodata
DEPARTURE - Rel with Inc Hz
0 to 180 E
Client: Chevron
Field: Gulf of Mexico
Well: Jack #2 Wellbore
Rig: Walter Deepwater Jack/St. Malo
Survey Date: 2014-Jan-01
Survey Type: Gyrodata Gyrocompassing Surface Survey
Survey Interval: 0 to 10,000 ft
Survey Method: Gyrocompassing
Survey Tool: Gyrocompassing
Survey Tool Type: Gyrocompassing
Survey Tool Serial Number: 1234
Survey Tool Calibration Date: 2013-Dec-01
Survey Tool Calibration Due Date: 2014-Dec-01
Survey Tool Calibration Status: Calibrated
Survey Tool Calibration Certificate: Yes
Survey Tool Calibration Certificate Number: 1234
Survey Tool Calibration Certificate Date: 2013-Dec-01
Survey Tool Calibration Certificate Due Date: 2014-Dec-01
Survey Tool Calibration Certificate Status: Calibrated
Survey Tool Calibration Certificate Issued By: Gyrodata
Survey Tool Calibration Certificate Issued To: Chevron
Survey Tool Calibration Certificate Issued For: Jack #2 Wellbore
Survey Tool Calibration Certificate Issued On: 2013-Dec-01
Survey Tool Calibration Certificate Due On



Calibration Report

Database File	d:\warrior\data\20200226_extraction_gp cody fed 20e-15-1n_cbl\20200226_extraction_gp cody fed 20e-15-1
Dataset Pathname	pass3.1
Dataset Creation	Wed Feb 26 13:11:41 2020

Gamma Ray Calibration Report

Serial Number:	ISHV2-03	
Tool Model:	2 3/4" TekCo	
Performed:	Fri Sep 13 16:47:28 2019	
Calibrator Value:	194.0	GAPI
Background Reading:	58.0	cps
Calibrator Reading:	329.7	cps
Sensitivity:	0.7141	GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	ISF06-04
Tool Model:	2 3/4" RIB Analog

Master Calibration, performed (Derived):

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.009	1.512	0.000	72.000	47.929	-0.446
CAL	-0.004	0.749				
5'	-0.001	1.996	0.000	72.000	36.048	0.031
SUM						
S1	0.033	1.728	0.000	72.000	42.470	-1.398
S2	0.029	1.522	0.000	72.000	48.225	-1.388
S3	0.032	1.457	0.000	72.000	50.542	-1.625
S4	0.042	1.474	0.000	72.000	50.301	-2.119
S5	0.050	1.536	0.000	72.000	48.441	-2.414
S6	0.050	1.680	0.000	72.000	44.171	-2.216
S7	0.045	1.909	0.000	72.000	38.635	-1.737
S8	0.037	1.864	0.000	72.000	39.410	-1.461

Temperature Calibration Report

Serial Number:	ISF06-04			
Tool Model:	2 3/4" RIB Analog			
Performed:	Tue Jan 08 14:48:09 2019			
	Reference		Reading	
Low Reference:	0.00	degF	0.00	usec
High Reference:	1.00	degF	1.00	usec
Gain:	0.33			
Offset:	0.00			
Delta Spacing	1			

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb
			CableHead-TitanConeType2	1.03	1.44	3.60
CCL	13.50		CCL_Log-2 3/4" TekCo (IPSN7-002)	1.83	2.75	33.00
			Antelope-Overbody	1.25	2.75	
TEMP	10.05					
WVFS8	8.76					
WVFS7	8.76					
WVFS6	8.76		RBTA-2 3/4" RIB Analog (ISF06-04)	9.13	2.75	102.00
WVFS5	8.76					
WVFS4	8.76					
WVFS3	8.76					
WVFS2	8.76					
WVFS1	8.76					
WVF3FT	8.01					
WVF5FT	7.01					
WVFSYNC	3.68					
WVFTEMP	3.68					
WVFCAL	3.68					
			Antelope-Overbody	1.25	2.75	
			GR_Log-2 3/4" TekCo (ISHV2-03)	3.68	2.75	47.00
GR	1.04					
LOCTIM	0.00					
UTCTIM	0.00					

Dataset:	20200226_extraction_gp cody fed 20e-15-1n_cbl.db: field/well/run1/pass3.1
Total length:	15.67 ft
Total weight:	185.60 lb
O.D.:	2.75 in

gyrodata

Company	Extraction Oil and Gas Inc.
Well	GP Cody Fed 20E-15-1N
Field	Wattenberg
County	Weld
State	Colorado
Country	U.S.A.