





# Bison Oil Well Cementing Single Cement Surface Pipe

Date: 2/23/2020

Invoice # 200573

API# \_\_\_\_\_

Foreman: Kirk Kallhoff

**Customer:** Anadarko Petroleum Corporation

**Well Name:** damore 18-3hz

County: Weld

State: Colorado

Sec: 18

Twp: 5n

Range: 67w

Consultant: joe

Rig Name & Number: Cartel 88

Distance To Location: 15

Units On Location: 4028/4034/4039

Time Requested: 100 am

Time Arrived On Location: 1130 pm

Time Left Location: 5:30 am

WELL DATA	Cement Data
Casing Size OD (in) : <u>9.625</u>	Cement Name: <u>BFN III</u>
Casing Weight (lb) : <u>36.00</u>	Cement Density (lb/gal) : <u>14.2</u>
Casing Depth (ft.) : <u>1,850</u>	Cement Yield (cuft) : <u>1.48</u>
Total Depth (ft) : <u>1860</u>	Gallons Per Sack: <u>7.40</u>
Open Hole Diameter (in.) : <u>13.50</u>	% Excess: <u>10%</u>
Conductor Length (ft) : <u>80</u>	Displacement Fluid lb/gal: <u>8.3</u>
Conductor ID : <u>15.25</u>	BBL to Pit:
Shoe Joint Length (ft) : <u>41</u>	Fluid Ahead (bbls): <u>30.0</u>
Landing Joint (ft) : <u>8</u>	H2O Wash Up (bbls): <u>10.0</u>
Max Rate: <u>8</u>	Spacer Ahead Makeup
Max Pressure: <u>2000</u>	30 bbl with Die in 2nd 10

Casing ID

8.921

Casing Grade

J-55 only used

Calculated Results	Displacement: <u>140.47 bbls</u>
<b>cuft of Shoe</b> <u>17.80</u> <b>cuft</b> (Casing ID Squared) X (.005454) X (Shoe Joint ft)	(Casing ID Squared) X (.0009714) X (Casing Depth + Landing Joint - Shoe Joint)
<b>cuft of Conductor</b> <u>61.05</u> <b>cuft</b> (Conductor Width Squared) -(Casing Size OD Squared) X (.005454) X (Conductor Length ft)	<b>Pressure of cement in annulus</b>
<b>cuft of Casing</b> <u>951.56</u> <b>cuft</b> (Open Hole Squared)-(Casing Size Squared) X (.005454) X (Casing Depth - Conductor Length )	<b>Hydrostatic Pressure:</b> <u>1364.75 PSI</u>
<b>Total Slurry Volume</b> <u>1030.40</u> <b>cuft</b> (cuft of Shoe) + (cuft of Conductor) + (cuft of Casing)	<b>Pressure of the fluids inside casing</b>
<b>bbls of Slurry</b> <u>183.51</u> <b>bbls</b> (Total Slurry Volume) X (.1781)	<b>Displacement:</b> <u>780.01 psi</u>
<b>Sacks Needed</b> <u>696</u> <b>sk</b> (Total Slurry Volume) ÷ (Cement Yield) X (% Excess Cement)	<b>Shoe Joint:</b> <u>30.25 PSI</u>
<b>Mix Water</b> <u>122.67</u> <b>bbls</b> (Sacks Needed) X (Gallons Per Sack) ÷ 42	<b>Total</b> <u>810.25 psi</u>
	<b>Differential Pressure:</b> <u>554.49 psi</u>
	<b>Collapse PSI:</b> <u>2020.00 psi</u>
	<b>Burst PSI:</b> <u>3520.00 psi</u>
	<b>Total Water Needed:</b> <u>303.14 bbls</u>

*X Joe Walker*  
Authorization To Proceed

### SERIES 2000

