RELIANCE
OILFIELD SERVICES

Radial Cement Bond
Gamma Ray
Casing Collar Log

Company	TEP Rocky Mountain LLC
Well	Strait Bottom Ranch SG 13-22
Field	Grand Valley
County	Garfield
State	Colorado

Company TEP Rocky Mountain LLC
Well Strait Bottom Ranch SG 13-22
Field Grand Valley
County Garfield State Colorado
Location: API # : 05-045-24014
SEC 22 TWP 7S RGE 96W
Other Services --

			Elevation
Permanent Datum	Ground Level	Elevation 5665'	K.B. 5689'
Log Measured From	Kelly Bushing	24 FT	D.F. 5688'
Drilling Measured From	Kelly Bushing		G.L. 5665'

Date	21-APR-2020
Run Number	One
Depth Driller	6150 FT
Depth Logger	6082 FT
Bottom Logged Interval	6067 FT
Top Log Interval	Surface
Open Hole Size	8.750"
Type Fluid	Water
Density / Viscosity	8.34 lb/gal
Max. Recorded Temp.	187°F
Estimated Cement Top	See Log
Time Well Ready	ROA
Time Logger on Bottom	8:25
Equipment Number	HD-0331
Location	Grand Junction, CO
Recorded By	Z. Fisher
Witnessed By	--

Borehole Record				Tubing Record			
Run Number	Bit	From	To	Size	Weight	From	To

Casing Record	Size (in)	Wgt (lbs/Ft)	Grade	Top	Bottom
Surface Casing	9 5/8	32.3	H-40	Surface	1042 FT
Intermediate #1	4 1/2	11.6	P-110	Surface	6110 FT
Intermediate #2					
Liner					

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

Comments

Log ran as per customer request
Depth referenced to Kelly Bushing at 24 FT
Marker Joint logged from 3540 - 3562 FT
Recorded with 0 PSI Surface Induced Pressure

Thank you for choosing Reliance Oilfield Services, LLC!

RELIANCE
OILFIELD SERVICES

Main Pass

Recorded With 0 PSI Surface Induced Pressure

Database File	tep\tep_straight bottom ranch sg 13-22_rbl_04-21-20\processed_tep_straight bottom ranch sg 13-22_rbl_0
Dataset Pathname	main.1
Presentation Format	ros_radii_tep
Dataset Creation	Wed Apr 22 09:47:06 2020
Charted by	Depth in Feet scaled 1:240

Gamma Ray		3' Amplitude	5' Variable Density Log	Sector Map	Average Amplitude
0 (GAPI) 200		0 (mV) 100	200 (usec) 1200		0 150
Casing Collar Locator		3' Amplitude x 5			Mimimum Amplitude
Line Speed		0 (mV) 20			0 150
-150 (ft/min) 150		3' Travel Time			Maximum Amplitude
Line Tension		300 (usec) 200			0 150
0 (lb) 2000					
Differential Temperature					
-2 (degF) 2					
Temperature					
0 (degF) 20					

Gamma Ray		3' Amplitude	5' Variable Density Log	Sector Map	Average Amplitude
0 (GAPI) 200		0 (mV) 100	200 (usec) 1200		0 150
Casing Collar Locator		3' Amplitude x 5			Mimimum Amplitude
Line Speed		0 (mV) 20			0 150
-150 (ft/min) 150		3' Travel Time			Maximum Amplitude
Line Tension		300 (usec) 200			0 150
0 (lb) 2000					
Differential Temperature					
-2 (degF) 2					
Temperature					
0 (degF) 20					

Repeat Pass

Recorded With 0 PSI Surface Induced Pressure

Database File tep\tep_straight bottom ranch sg 13-22_rbl_04-21-20\processed_tep_straight bottom ranch sg 13-22_rbl_0
Dataset Pathname repeat.2
Presentation Format ros_radii_tep
Dataset Creation Wed Apr 22 09:58:34 2020
Charted by Depth in Feet scaled 1:240

Gamma Ray		3' Amplitude	5' Variable Density Log	Sector Map	Average Amplitude
0 (GAPI) 200		0 (mV) 100	200 (usec) 1200		0 150
Line Speed		3' Amplitude x 5			Mimimum Amplitude
-150 (ft/min) 150		0 (mV) 20			0 150
Line Tension		3' Travel Time			Maximum Amplitude
0 (lb) 2000		300 (usec) 200			0 150
Differential Temperature					
-2 (degF) 2					
Temperature					
0 (degF) 20					



Gamma Ray		3' Amplitude	5' Variable Density Log	Sector Map	Average Amplitude
0 (GAPI) 200		0 (mV) 100	200 (usec) 1200		0 150
Line Speed		3' Amplitude x 5			Mimimum Amplitude
-150 (ft/min) 150		0 (mV) 20			0 150
Line Tension		3' Travel Time			Maximum Amplitude
0 (lb) 2000		300 (usec) 200			0 150
Differential Temperature					
-2 (degF) 2					
Temperature					
0 (degF) 20					



Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb)
			Titan CHD-14375 GO Titan 1-7/16" Assembled Electric Cable Head with 1" Fishing Neck	1.03	1.44	3.60
			DSS RAC-2750 5A GO DSS 2-3/4" Roller 5 Arm Centralizer with GO Ends	2.55	2.75	32.00
TEMP	17.11					
			Probe Radii-2750 RBT (FW1311-021) Probe 2-3/4" Radial Cement Bond Tool with Integral Temperature Sub	9.39	2.75	105.00
WVFS8	14.88					
WVFS7	14.88					
WVFS6	14.88					
WVFS5	14.88					
WVFS4	14.88					
WVFS3	14.88					
WVFS2	14.88					
WVFS1	14.88					
WVFCAL	14.88					
WVF3FT	14.88					
WVF5FT	13.88					
			BTA-MUD BTA 2-3/4" Roller 6 Arm Centralizer with Reversible Ends	2.92	2.72	25.00
CCL	6.80					
			Probe GR-CCL ANL-2750 A (051217) Probe 2.75" Analog 4 Channel Pulse Gamma Ray/CCL Combined	4.54	2.75	55.00
GR	4.06					
			BTA-MUD BTA 2-3/4" Roller 6 Arm Centralizer with Reversible Ends	2.92	2.72	25.00
			GO BN-14375 GO 1-7/16" Bull Nose with Go Box Top	0.25	1.44	1.00

Dataset: processed_tep_straight bottom ranch sg 13-22_rbl_04-21-20.db: field/well/run1/main.1
Total length: 23.60 ft
Total weight: 246.60 lb
O.D.: 2.75 in

Calibration Report

Database File c:\programdata\warrior\data\tep\tep_straight bottom ranch sg 13-22_rbl_04-21-20\processed_tep_straight bo
Dataset Pathname main.1
Dataset Creation Wed Apr 22 09:47:06 2020

Gamma Ray Calibration Report

Serial Number: 051217
Tool Model: 2750 A
Performed: Mon Oct 01 11:32:35 2018

Calibrator Value: 637.0 GAPI

Background Reading: 115.3 cps
Calibrator Reading: 1027.7 cps

Sensitivity: 0.6982 GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number: FW1311-021
Tool Model: 2750 RBT

Calibration Casing Diameter: 4.500 in
Calibration Depth: 28.002 ft

Master Calibration, performed (Derived):

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.005	0.709	0.800	81.196	114.224	0.242
CAL	0.003	0.756				
5'	0.005	0.650	0.800	81.196	124.605	0.204
SUM						
S1	0.001	0.706	0.000	100.000	141.776	-0.113
S2	0.004	0.692	0.000	100.000	145.322	-0.586
S3	0.005	0.719	0.000	100.000	140.108	-0.743
S4	0.007	0.766	0.000	100.000	131.622	-0.872
S5	0.006	0.752	0.000	100.000	134.129	-0.855
S6	0.006	0.715	0.000	100.000	141.117	-0.830
S7	0.007	0.698	0.000	100.000	144.808	-1.068
S8	0.010	0.719	0.000	100.000	141.042	-1.384

Air Zero Calibration, performed Tue Apr 21 06:45:14 2020:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Temperature Calibration Report

Serial Number: FW1311-021
Tool Model: 2750 RBT
Performed: Mon Oct 01 11:32:11 2018

	Reference	Reading
Low Reference:	100.00 degF	112.12 degF
High Reference:	350.00 degF	415.62 degF

Gain: 0.82
Offset: 7.65
Delta Spacing 1

RELIANCE OILFIELD SERVICES

Company	TEP Rocky Mountain LLC
Well	Strait Bottom Ranch SG 13-22
Field	Grand Valley
County	Garfield
State	Colorado