
NEXTIER
MAIN PASS (PPE)
LOG INTERPRETATION
Gamma Ray (GR)
Resistivity (RES)
Density (RHOB)
Neutron (NPHI)
Sonic (DT)
Caliper (CALI)
Spectral Gamma Ray (SGR)
Thorium (TH)
Potassium (K)
Uranium (U)
Photoelectric Factor (PEF)
Volume of Clay (VCL)
Porosity (PHIE)
Water Saturation (SW)
Permeability (PERM)
Hydrocarbon Pore Volume (HCPV)
Bulk Volume Water (BVW)
Irreducible Water Saturation (SWI)
Movable Hydrocarbon (MOVH)
Net Pay (NETP)
Net Reservoir (NETR)
Net Gross (NETG)
Pay Flag (PAYF)
Reservoir Flag (RESF)
Lithology (LITH)
Fluid Type (FLUID)
Depth (DEPTH)
Time (TIME)
Speed (SPEED)
Tension (TENS)
Temperature (TEMP)
Pressure (PRES)
Flow Rate (FLOW)
Volume (VOL)
Mass (MASS)
Density (DENS)
Viscosity (VISC)
Velocity (VEL)
Acceleration (ACCEL)
Force (FORCE)
Energy (ENERGY)
Power (POWER)
Torque (TORQUE)
Angle (ANGLE)
Rotation (ROT)
Vibration (VIB)
Shock (SHOCK)
Strain (STRAIN)
Stress (STRESS)
Modulus (MOD)
Poisson's Ratio (POIS)
Young's Modulus (YOUNG)
Shear Modulus (SHEAR)
Bulk Modulus (BULK)
Compressibility (COMP)
Permeability (PERM)
Porosity (PHIE)
Water Saturation (SW



Log Variables

Database:C:\Warrior\Data\yuma well.db
Dataset: field/well/run1/pass9

Top - Bottom

PPT usec	CASEWGHT lb/ft	MAXAMPL mV	MINAMPL mV	MINATTN db/ft	SRFTEMP degF	CASEOD in	PERFS
357	11.6	81	0.7	0.8	0	4.5	0

TDEPTH ft	BOTTEMP degF	BOREID in
0	200	8.625

Calibration Report

Database File: yuma well.db
Dataset Pathname: pass9
Dataset Creation: Wed Jul 08 10:07:21 2020 by Log 7.0 B1

Gamma Ray Calibration Report

Type / Serial: Probe275dig / 110785

SHOP CALIBRATION — Wed Mar 18 07:21:11 2020

	Counts/Sec.	Gain	Offset	Jig	Units
Background	0.0				cps
Calibrator	1.0				cps
		0.5200			GAPI/cps

PRIMARY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	GAPI

BEFORE SURVEY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	GAPI

AFTER SURVEY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference				0.0	GAPI

Segmented Cement Bond Log Calibration Report

Serial Number: 101020
Tool Model: Probe

Calibration Casing Diameter: 4.500 in
Calibration Depth: 1541.800 ft

Master Calibration, performed Wed Jul 08 09:52:58 2020:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.008	1.914	0.800	81.196	42.180	0.482
CAL	0.008	0.734				
5'	0.008	1.565	0.800	81.196	51.622	0.394
SUM						
S1	0.008	1.820	0.000	81.000	44.693	-0.354
S2	0.008	1.933	0.000	81.000	42.081	-0.326
S3	0.008	2.040	0.000	81.000	39.873	-0.325
S4	0.008	2.036	0.000	81.000	39.932	-0.308
S5	0.008	1.977	0.000	81.000	41.142	-0.333
S6	0.007	1.890	0.000	81.000	43.029	-0.321
S7	0.008	1.846	0.000	81.000	44.077	-0.353
S8	0.008	1.832	0.000	81.000	44.409	-0.342

Internal Reference Calibration, performed Fri Jan 13 14:30:16 2012:

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.008	0.734	1.000	0.000

Air Zero Calibration, performed Mon Dec 30 15:19:04 2019:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Sensor	Offset (ft)	Schematic	Description	Len (ft)	OD (in)	Wt (lb)
			STNDRD Standard Cable Head	1.00	1.69	10.00
			Probe Probe 2 3/4 Centralizer	2.88	2.75	20.00
HEADVOLT	16.33					
IntTemp	14.92					
			RBT-Probe (101020) Probe Radii Bond Tool with Digital Telemetry	8.75	2.75	90.00
WVF3FT	11.67					
WVFCAL	11.67					
WVFS1	11.67					
WVFS2	11.67					
WVFS3	11.67					
WVFS4	11.67					
WVFS5	11.67					
WVFS6	11.67					
WVFS7	11.67					
WVFS8	11.67					
WVF5FT	10.67					
			Probe Probe 2 3/4 Centralizer	2.88	2.75	20.00
CCL	3.63					
			GR-Probe275dig (110785) Probe Gamma CCL	4.54	2.75	57.00
GR	0.90					

Dataset: yuma well.db: field/well/run1/pass9
Total Length: 20.04 ft
Total Weight: 197.00 lb
O.D. 2.75 in