

FORM

6

Rev  
02/20

## State of Colorado

## Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE ET OE ES

Document Number:

402503720

Date Received:

10/05/2020

## WELL ABANDONMENT REPORT

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set.

A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

OGCC Operator Number: 69175

Contact Name: Valerie Danson

Name of Operator: PDC ENERGY INC

Phone: (970) 506-9272

Address: 1775 SHERMAN STREET - STE 3000

Fax:

City: DENVER State: CO Zip: 80203

Email: valerie.danson@pdce.com

For "Intent" 24 hour notice required,

Name: Evins, Bret

Tel: (970) 420-6699

COGCC contact:

Email: bret.evins@state.co.us

Type of Well Abandonment Report: ☒ Notice of Intent to Abandon ☐ Subsequent Report of Abandonment

API Number 05-123-27309-00

Well Name: D DYER

Well Number: 41-34

Location: QtrQtr: NENE Section: 34 Township: 7N Range: 64W Meridian: 6

County: WELD

Federal, Indian or State Lease Number:

Field Name: WATTENBERG

Field Number: 90750

## Only Complete the Following Background Information for Intent to Abandon

Latitude: 40.534670 Longitude: -104.528440

GPS Data: GPS Quality Value: 2.9 Type of GPS Quality Value: Date of Measurement: 02/18/2007

GPS Instrument Operator's Name: HOLLY L TRACY

Reason for Abandonment: ☐ Dry ☒ Production Sub-economic ☐ Mechanical Problems☐ OtherCasing to be pulled: ☐ Yes ☒ No Estimated Depth:Fish in Hole: ☐ Yes ☒ No If yes, explain details belowWellbore has Uncemented Casing leaks: ☐ Yes ☒ No If yes, explain details below

Details:

## Current and Previously Abandoned Zones

| Formation | Perf. Top | Perf. Btm | Abandoned Date | Method of Isolation | Plug Depth |
|-----------|-----------|-----------|----------------|---------------------|------------|
| CODELL    | 7092      | 7102      |                |                     |            |

Total: 1 zone(s)

## Casing History

| Casing Type | Size of Hole | Size of Casing | Weight Per Foot | Setting Depth | Sacks Cement | Cement Bot | Cement Top | Status |
|-------------|--------------|----------------|-----------------|---------------|--------------|------------|------------|--------|
| SURF        | 12+1/4       | 8+5/8          | 24              | 624           | 345          | 624        | 0          | VISU   |
| 1ST         | 7+7/8        | 4+1/2          | 10.5            | 7,287         | 175          | 7,287      | 6,250      | CBL    |
| S.C. 1.1    |              |                |                 | 6,250         | 540          | 6,250      | 310        | CBL    |

## Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth 7042 with 2 sacks cmt on top. CIBP #2: Depth 6740 with 2 sacks cmt on top.  
CIBP #3: Depth 2600 with 2 sacks cmt on top. CIBP #4: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.  
CIBP #5: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged: ☐  
Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged: ☐  
Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged: ☐  
Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged: ☐  
Set \_\_\_\_\_ sks cmt from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Plug Type: \_\_\_\_\_ Plug Tagged: ☐

Perforate and squeeze at 310 ft. with 80 sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth

Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth

Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth

(Cast Iron Cement Retainer Depth)

Set 175 sacks half in. half out surface casing from 1882 ft. to 0 ft. Plug Tagged: ☒

Set \_\_\_\_\_ sacks at surface

Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker: ☐ Yes ☐ No

Set \_\_\_\_\_ sacks in rat hole Set \_\_\_\_\_ sacks in mouse hole

### Additional Plugging Information for Subsequent Report Only

Casing Recovered: \_\_\_\_\_ ft. \_\_\_\_\_ inch casing Cut and Cap Date: \_\_\_\_\_  
of \_\_\_\_\_

\*Wireline Contractor: \_\_\_\_\_ \*Cementing Contractor: \_\_\_\_\_

Type of Cement and Additives Used: \_\_\_\_\_

Flowline/Pipeline has been abandoned per Rule 1105 ☐ Yes ☐ No

Technical Detail/Comments:

D Dyer 41-34 (05-123-27309)/Plugging Procedure (Intent)  
Producing Formation: Codell: 7092'-7102'  
Upper Pierre Aquifer: 660'-1732'  
TD: 7294' PBTD: 7145' (3/27/2014)  
Surface Casing: 8 5/8" 24# @ 624' w/ 345 sxs cmt  
Production Casing: 4 1/2" 10.5# @ 7287' w/ 715 sxs cmt (TOC @ 310')

Tubing: 2 3/8" tubing set @ 7079' (3/28/2014)

Proposed Procedure:

1. MIRU pulling unit. Pull 2 3/8" tubing.
2. RU wireline company.
3. TIH with CIBP. Set BP at 7042'. Top with 2 sxs 15.8#/gal CI G cement. (Top of Codell perms @ 7092')
4. TIH with CIBP. Set BP at 6740'. Top with 2 sxs 15.8#/gal CI G cement. (Top of Niobrara @ 6790')
5. TIH with CIBP. Set BP at 2600'. Top with 2 sxs 15.8#/gal CI G cement.
6. TIH with perf gun. Shoot squeeze holes @ 310'.
7. TIH with tubing to 1882'. RU cementing company. Mix and pump 175 sxs 15.8#/gal CI G cement down tubing. Cement should circulate to surface.
8. Close off casing returns. Hook up cement line to cement flange and pump 80 sxs 15.8#/gal CI G cement downhole and squeeze through perforations @ 310' into annular space. Cement should circulate to surface.
9. Cut surface casing 6' below ground level and weld on cap.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Valerie Danson

Title: Reg Tech Date: 10/5/2020 Email: valerie.danson@pdce.com

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: JENKINS, STEVE

Date: 10/7/2020

**CONDITIONS OF APPROVAL, IF ANY:**

Expiration Date: 4/6/2021

**COA Type**

**Description**

|  |  |
|--|--|
|  | <p>1) Provide 48 hour notice of plugging MIRU via electronic Form 42.</p> <p>2) Prior to placing the 1882' plug: verify that all fluid migration (liquid or gas) has been eliminated. If evidence of fluid migration or pressure remains, contact COGCC Engineer for an update to plugging orders.</p> <p>3) After isolation has been verified, pump plug and displace. If cement is not circulated to surface, shut-in, WOC 4 hours then tag plug – must be at 574' or shallower and provide 10 sx plug at the surface.</p> <p>4) Leave at least 100' of cement in the wellbore for each plug.</p> <p>5) Properly abandon flowlines per Rule 1105. File electronic Form 42 once abandonment of on-location flowlines is complete. Within 90 days of an operator completing abandonment requirements for an off-location flowline or crude oil transfer line the operator must submit a Flowline Report, Form 44.</p> <p>6) With the Form 6 SRA operator must provide written documentation which positively affirms each COA has been addressed.</p> <p>7) After placing the shallowest hydrocarbon isolating plug (2600'), operator must wait a sufficient time to confirm static conditions. If at any time after placing this plug there is evidence of pressure or fluid migration, contact COGCC engineering before continuing operations.</p> |
|  | <p>Operator shall implement measures to control venting, to protect health and safety, and to ensure that vapors and odors from well plugging operations do not constitute a nuisance or hazard to public welfare.</p>   |
|  | <p>Prior to starting plugging operations a Bradenhead test shall be performed if there has not been a reported Bradenhead test within the 60 days immediately preceding the start of plugging operations.</p> <p>1) If, before opening the Bradenhead valve, the beginning pressure is greater than 25 psi, sampling is required.</p> <p>2) If pressure remains at the conclusion of the test, or if any liquids were present during the test, sampling is required.</p> <p>The Form 17 shall be submitted within 10 days of the test. Sampling shall comply with Operator Guidance - Bradenhead Testing and Reporting Instructions. If samples are collected, copies of all final laboratory analytical results shall be provided to the COGCC within three (3) months of collecting the samples.</p>   |

**Attachment Check List**

**Att Doc Num**

**Name**

|           |                         |
|-----------|-------------------------|
| 402503720 | FORM 6 INTENT SUBMITTED |
| 402503721 | WELLBORE DIAGRAM        |
| 402503722 | WELLBORE DIAGRAM        |
| 402503723 | GYRO SURVEY             |

Total Attach: 4 Files

### General Comments

| <u>User Group</u> | <u>Comment</u>  | <u>Comment Date</u> |
|-------------------|---|---------------------|
| Engineer          | Verify existing cement coverage by CBL - submit to COGCC with the Subsequent.   | 10/07/2020          |
| Engineer          | 1) Deepest Water Well within 1 mile = 520'.<br>2) Fox Hills Bottom- N/A, per SB5.   | 10/07/2020          |
| Engineer          | In accordance with the Notice to Operators (NTO): Timing for COGCC Forms adopted on 05/01/2020, this Form 6 Notice of Intent to Abandon is valid for 12 months from the date of approval expiring on 10/07/2021. This NTO does not alter the deadlines for submission of, or compliance with any other Commission rule or Form. | 10/07/2020          |
| Permit            | -Confirmed as-drilled well location.<br>-No other forms in process.<br>-Production reporting up-to-date.<br>-Confirmed productive interval docnum: 1753514.<br>-Input gyro.<br>-Reviewed WBDs.<br>-Pass   | 10/06/2020          |

Total: 4 comment(s)